



I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Mail Stop Amendment, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on September 11, 2004.

Crystal Ross
Crystal Ross

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant : David Allison Bennett, et al.
Application No. : 09/684,866
Filed : October 6, 2000
Title : Apparatus, Systems and Methods For Online, Multi-Carrier, Multi-Service Parcel Shipping Management
Grp./Div. : 3629
Examiner : Edward R. Cosimano
Docket No. : PSTM0038/MRK

RECEIVED

SEP 17 2004

GROUP 3600

Substitute Specification Under 37 C.F.R. §1.125

Clean Copy



PSTM0038/MRK/STM

1 APPARATUS, SYSTEMS AND METHODS FOR ONLINE, MULTI-CARRIER, MULTI-
2 SERVICE PARCEL SHIPPING MANAGEMENT

3

4 CROSS REFERENCE TO RELATED APPLICATIONS

5 [0001] This application claims priority of U.S. Provisional Patent Application Serial No.
6 60/158,179, filed on October 6, 1999, U.S. Provisional Patent Application Serial No.
7 60/170,186, filed on December 10, 1999, U.S. Provisional Patent Application Serial No.
8 60/170,504, filed on December 13, 1999, U.S. Provisional Patent Application Serial
9 No. 60/192,692, filed on March 28, 2000, U.S. Provisional Patent Application Serial No.
10 60/192,723, filed on March 27, 2000, U.S. Provisional Patent Application Serial No.
11 60/193,899, filed on March 31, 2000, and U.S. Provisional Patent Application Serial No.
12 60/195,748, filed on April 6, 2000. The disclosures of U.S. Provisional Patent Application
13 Serial No. 60/158,179, filed on October 6, 1999, U.S. Provisional Patent Application Serial
14 No. 60/170,186, filed on December 10, 1999, U.S. Provisional Patent Application Serial No.
15 60/170,504, filed on December 13, 1999, are incorporated for all purposes herein by reference
16 as if fully stated here.

17

18 FIELD OF THE INVENTION

19 [0002] The field of the present invention is computer systems, and specifically computer
20 systems for parcel shipping management.

21

22 BACKGROUND OF THE INVENTION

23 [0003] Individuals, small businesses and major corporations the (“Shipper(s)”) ship
24 billions of parcels every year (small office/home office shippers are referred to as “SOHO”
25 Shippers). Each parcel, also sometimes referred to herein as a package, is shipped by a
26 Shipper using at least one parcel carrier (the “carrier(s)”, or “Carrier(s)”).

27 [0004] Each parcel is characterized by a set of “Parcel Specifications.” Parcel
28 specifications include but are not limited to such factors as: parcel dimensions, parcel weight,
29 parcel value and the like.

1 [0005] Each Shipper is faced with certain shipping requirements and limitations (“Shipping
2 Requirements”), such as the location from which the parcel is to be shipped, time frame
3 within which the particular parcel must arrive at its destination, the ability of the shipper to
4 drop off the parcel, budgetary constraints with regard to the cost of shipping, insurance
5 against loss, delivery notification, loss protection, and the like.

6 [0006] Each Carrier has its own unique rating schedule, and delivery and pickup rules and
7 schedules for each of a multitude of different services. In some cases, a particular Carrier’s
8 rules may be available in a standalone Carrier-provided paper-based or computer system.
9 Many Shippers attempt to work with each of the standalone, individual paper-based and
10 computer Carrier-provided systems (“standalone Carrier system environment”) in order to
11 ship a parcel.

12 [0007] A Shipper that uses standalone Carrier systems must sort through the various
13 services offered by each carrier and apply each Carrier’s rules to determine whether one or
14 more carriers offer a service with which to deliver a particular parcel according to the
15 Shipper’s requirements. If the Shipper determines that more than one carrier offers a service
16 with which to deliver a particular parcel according to the Shipper’s requirements, then the
17 particular Shipper might additionally be concerned with selecting a carrier and service that
18 provide shipping services at the optimal price.

19 [0008] A single system available over the Internet is needed for Shippers that provides
20 shipping management for each parcel that each Shipper needs to ship using any one of a
21 plurality of services offered by any one of a plurality of carriers.

22
23 SUMMARY OF THE INVENTION

24 [0009] The present invention provides apparatus, systems and methods providing a single
25 system available over the Internet that provides shipping management for each parcel that
26 each Shipper of a plurality of Shippers needs to ship using any one of a plurality of services
27 offered by any one of a plurality of carriers.

28
29
30

1 BRIEF DESCRIPTION OF THE DRAWINGS

2 [0010] These and other features of the present invention are more fully set forth in the
3 following description of exemplary embodiments of the invention. The description is
4 presented with reference to the accompanying drawings in which:

5 [0011] FIG. 1 is an entity relationship diagram depicting the interface relationships
6 provided by the System between Shippers as Sellers, Carriers, Recipients as Buyers,
7 eCommerce/eAuction Providers and the System in an exemplary embodiment of the System
8 in an independent system eCommerce environment;

9 [0012] FIG. 2 is an entity relationship diagram depicting the interface relationships
10 provided by the System between Shippers, Carriers, Recipients and the System in an
11 exemplary embodiment of the System in an Internet environment;

12 [0013] FIG. 3 is a graphic representation depicting an exemplary user computer
13 configuration and the user computer's interface with the System in an Internet environment;

14 [0014] FIG. 4 is a simplified schematic diagram of a user's computer and the interface
15 between the user's computer and the System servers using the Internet in an exemplary
16 embodiment of the invention in an Internet environment;

17 [0015] FIG. 5 is a simplified graphic representation of an exemplary configuration of the
18 System, and relationships between the System and Carriers and Users, in an exemplary
19 embodiment of the System in an independent system eCommerce environment;

20 [0016] FIG. 6 is a simplified graphic representation depicting an alternate view of the
21 System Data Center and its interfaces in an exemplary embodiment of the System in an
22 independent system eCommerce environment;

23 [0017] FIG. 7 is a simplified graphic representation of an exemplary configuration of the
24 System, and relationships between the System and Carriers and Shippers/Users, in an
25 exemplary simplified Internet embodiment of the invention;

26 [0018] FIG. 8 is a high level System component diagram depicting an exemplary System
27 Architecture in an exemplary embodiment of the System in an Internet environment;

28 [0019] FIG. 9 is a graphic representation of an exemplary menu architecture for the System
29 in an exemplary embodiment of the System in an independent system eCommerce
30 environment;

1 [0020] FIGS. 10A through 10E are high level logic flow diagrams depicting the logic flow
2 for processing both Shipper/Seller and Buyer/Bidder information in an exemplary
3 embodiment of the System in an independent system eCommerce environment;

4 [0021] FIG. 11 is a graphic representation depicting an exemplary embodiment of a
5 registration introduction screen in an exemplary embodiment of the System in an independent
6 system eCommerce environment;

7 [0022] FIG. 12 is a graphic representation depicting an exemplary embodiment of a User
8 address collection screen in an exemplary embodiment of the System in an independent
9 system eCommerce environment;

10 [0023] FIG. 13 is a graphic representation of an exemplary embodiment of a Shipping
11 Location screen in an exemplary embodiment of the System in an independent system
12 eCommerce environment;

13 [0024] FIG. 14 is a graphic representation depicting an exemplary embodiment of a
14 Locations screen in an exemplary embodiment of the System in an independent system
15 eCommerce environment;

16 [0025] FIG. 15 is a graphic representation depicting an alternative exemplary embodiment
17 of a Locations screen inset in an alternative exemplary embodiment of the System in an
18 Internet environment;

19 [0026] FIG. 16 is a graphic representation of an exemplary embodiment of a UPS
20 registration screen in an exemplary embodiment of the System in an independent system
21 eCommerce environment;

22 [0027] FIG. 17 is a graphic representation of an exemplary embodiment of an eCommerce
23 registration introduction screen in an exemplary embodiment of the System in an independent
24 system eCommerce environment;

25 [0028] FIG. 18 is a graphic representation of a registration complete screen in an exemplary
26 embodiment of the System in an independent system eCommerce environment;

27 [0029] FIG. 19 is a graphic representation of an exemplary embodiment of the Seller's
28 Carrier/Service Preferences Screen in an exemplary embodiment of the System in an
29 independent system eCommerce environment;

30 [0030] FIG. 20 is a graphic representation of an alternative embodiment of the Seller's

- 1 Carrier/Service Preferences Screen in an exemplary embodiment of the System in an
- 2 independent system eCommerce environment;
- 3 [0031] FIG. 21 is a graphic representation of an exemplary embodiment of a Seller's
- 4 Charges and Payment Preferences Screen in an exemplary embodiment of the System in an
- 5 independent system eCommerce environment;
- 6 [0032] FIG. 22 is a graphic representation of an alternative embodiment of the Seller's
- 7 Charges and Payment Preferences Screen in an exemplary embodiment of the System in an
- 8 independent system eCommerce environment;
- 9 [0033] FIG. 23 is a System interactivity data and logic flow diagram depicting an
- 10 exemplary embodiment of the Seller's eCommerce Registration process in an exemplary
- 11 embodiment of the System in an independent system eCommerce environment;
- 12 [0034] FIG. 24 is a graphic representation of a Registration Needs Completion Screen in an
- 13 exemplary embodiment of the System in an independent system eCommerce environment;
- 14 [0035] FIG. 25 is a graphic representation of an exemplary embodiment of a Create a
- 15 Seller's Link Screen in an exemplary embodiment of the System in an independent system
- 16 eCommerce environment;
- 17 [0036] FIG. 26 is a graphic representation of an alternative online screen that collects a
- 18 user's shipping specifications and preferences in an alternative exemplary embodiment of the
- 19 System in an Internet environment;
- 20 [0037] FIGS. 27A through 27C are high level logic flow diagrams control communications
- 21 with client machine peripheral devices in an exemplary embodiment of the System in an
- 22 Internet environment;
- 23 [0038] FIG. 28 is a graphic representation of an alternative online screen that collects
- 24 supplemental user shipping specifications and preferences in an alternative exemplary
- 25 embodiment of the System in an Internet environment;
- 26 [0039] FIG. 29 is a graphic representation of an alternative embodiment of a Create a
- 27 Seller's Link Screen in an exemplary embodiment of the System in an independent system
- 28 eCommerce environment;
- 29 [0040] FIG. 30 depicts an exemplary alternative embodiment of the Create a Seller's Link
- 30 screen in an exemplary embodiment of the System in an independent system eCommerce

1 environment;

2 [0041] FIG. 31 depicts the text of an exemplary hypertext link such as is created by an
3 exemplary embodiment of the “Create Link” feature in an exemplary embodiment of the
4 System in an independent system eCommerce environment;

5 [0042] FIG. 32 is a graphic representation depicting an alternative embodiment of a
6 hyperlink generated by the System in an exemplary embodiment of the System in an
7 independent system eCommerce environment;

8 [0043] FIGS. 33A and 33B represent a database schema diagram that depicts an exemplary
9 embodiment of tables in which data is stored by the System regarding a particular Seller
10 Account in an exemplary embodiment of the System in an independent system eCommerce
11 environment;

12 [0044] FIG. 34 is a graphic representation of an exemplary embodiment of a Seller’s
13 eCommerce/eAuction web site page in an exemplary embodiment of the System in an
14 independent system eCommerce environment;

15 [0045] FIG. 35 is a graphic representation of an exemplary Buyer shipping rating
16 information collection screen that the Buyer would see upon entry into the System in an
17 exemplary embodiment of the System in an independent system eCommerce environment;

18 [0046] FIG. 36A is a graphic representation depicting an exemplary embodiment of a
19 dynamically dimensioned, multi-carrier, multi-service shipping rates comparison Graphic
20 Array in an exemplary embodiment of the System in an independent system eCommerce
21 environment;

22 [0047] FIGS. 36B through 36E are high level data retrieval logic flow diagrams depicting
23 the data and high level logic that the system uses to calculate a shipping rate;

24 [0048] FIG. 36F is a graphic representation of an alternative exemplary Preview Rates
25 Screen (also referred to in some embodiments as a Rates and Times Screen) in an alternative
26 exemplary embodiment of the invention;

27 [0049] FIGS. 37A and 37B represent a System interactivity data and logic flow diagram
28 depicting an exemplary embodiment of the Create Link and the Buyer’s Preview Shipping
29 Rates functionality in an exemplary embodiment of the System in an independent system
30 eCommerce environment;

1 [0050] FIG. 38 is a high level flow diagram depicting an overview of the System logic to
2 generate a dynamically dimensioned, multi-carrier, multi-service shipping rates comparison
3 Graphic Array in an exemplary embodiment of the System in an Internet environment;

4 [0051] FIGS. 39A through 39C are high level flow diagrams depicting the initial timing and
5 rating logic to develop a dynamically dimensioned, multi-carrier, multi-service shipping rates
6 comparison Graphic Array in an exemplary embodiment of the System in an Internet
7 environment;

8 [0052] FIG. 40 is a graphic representation depicting an exemplary embodiment of a multi-
9 carrier, multi-service shipping rates comparison Graphic Array in an exemplary embodiment
10 of the System in an independent system eCommerce environment;

11 [0053] FIG. 41 is a graphic representation of a Seller's Buyer Information Screen in an
12 exemplary embodiment of the System in an independent system eCommerce environment;

13 [0054] FIG. 42 is a graphic representation of an exemplary embodiment of a Subject Parcel
14 data screen in an exemplary embodiment of the System in an independent system eCommerce
15 environment;

16 [0055] FIG. 43 is a graphic representation of an exemplary embodiment of a System-
17 prepared e-mail to the Buyer in an exemplary embodiment of the System in an independent
18 system eCommerce environment;

19 [0056] FIG. 44 is a graphic representation of an exemplary embodiment of the Buyer
20 Response Introduction screen in an exemplary embodiment of the System in an independent
21 system eCommerce environment;

22 [0057] FIG. 45 is a graphic representation of an exemplary embodiment of the Buyer
23 Shipping Information Collection screen in an exemplary embodiment of the System in an
24 independent system eCommerce environment;

25 [0058] FIG. 46 is a graphic representation depicting an alternative exemplary embodiment
26 of a dynamically dimensioned, multi-carrier, multi-service shipping rates comparison Graphic
27 Array in an alternative exemplary embodiment of the System in an independent system
28 eCommerce environment;

29 [0059] FIG. 47 is a graphic representation depicting an exemplary embodiment of a
30 Shipping Summary Screen in an exemplary embodiment of the System in an independent

1 system eCommerce environment;

2 [0060] FIG. 48 is a graphic representation depicting an alternative exemplary embodiment
3 of a Shipping Summary Screen in an exemplary embodiment of the System in an Internet
4 environment;

5 [0061] FIG. 49 is a graphic representation depicting an exemplary embodiment of a
6 Cardholder Information collection screen in an exemplary embodiment of the System in an
7 independent system eCommerce environment;

8 [0062] FIG. 50 is a graphic representation depicting an exemplary embodiment of a
9 System's Shipping Log in an exemplary embodiment of the System in an independent system
10 eCommerce environment;

11 [0063] FIG. 51 is a graphic representation depicting an exemplary embodiment of a Seller
12 notification e-mail in an exemplary embodiment of the System in an independent system
13 eCommerce environment;

14 [0064] FIG. 52 is a graphic representation of an exemplary embodiment of a Void Package
15 screen in an exemplary embodiment of the System in an independent system eCommerce
16 environment;

17 [0065] FIG. 53 is a graphic representation of an exemplary embodiment of a Reprint Label
18 screen in an exemplary embodiment of the System in an independent system eCommerce
19 environment;

20 [0066] FIG. 54 is a high level flow diagram depicting an exemplary embodiment of Label
21 Printing in an exemplary embodiment of the System in an Internet environment;

22 [0067] FIG. 55 is a high level flow diagram depicting an exemplary embodiment of Image
23 Printing in an exemplary embodiment of the System in an Internet environment;

24 [0068] FIGS. 56 through 58 are graphic representations of exemplary online screens with
25 which a user controls the final shipping and label printing for a particular package in an
26 alternative exemplary embodiment in an Internet environment;

27 [0069] FIG. 59 is a graphic representation of an exemplary embodiment of a Send Ship
28 Notification screen in an exemplary embodiment of the System in an independent system
29 eCommerce environment;

30 [0070] FIG. 60 is a graphic representation of an alternative exemplary embodiment of a

1 Send Ship Notification screen in an alternative exemplary embodiment of the System in an
2 Internet environment;

3 [0071] FIG. 61 is a graphic representation depicting an exemplary embodiment of a Ship a
4 Package Summary online report in an exemplary embodiment of the System in an
5 independent system eCommerce environment;

6 [0072] FIG. 62 is a graphic representation depicting an exemplary embodiment of a UPS
7 End-of-Day Screen in an exemplary embodiment of the System in an independent system
8 eCommerce environment;

9 [0073] FIG. 63 is a graphic representation of an exemplary embodiment of a Reprint Driver
10 Record Screen in an exemplary embodiment of the System in an independent system
11 eCommerce environment;

12 [0074] FIGS. 64A-1, 64A-2, 64B-1 and 64B-2 are System interactivity data and logic flow
13 diagrams depicting an exemplary embodiment of the process by which the System completes
14 the information necessary to ship a package in an exemplary embodiment of the System in an
15 independent system eCommerce environment;

16 [0075] FIGS. 65A and 65B represent a database schema diagram that depicts an exemplary
17 embodiment of tables in which data is stored by the System regarding a particular package
18 and a particular Seller's Account in an exemplary embodiment of the System in an
19 independent system eCommerce environment;

20 [0076] FIG. 66 depicts an exemplary XML formatted request for submitting a tracking
21 request to a Carrier in an exemplary embodiment of the System in an Internet environment;

22 [0077] FIG. 67 depicts an exemplary successful tracking response, also in XML format,
23 returned by the Carrier in an exemplary embodiment of the System in an Internet
24 environment;

25 [0078] FIG. 68 is a graphic representation of a Shipper online user input screen that is
26 displayed on the Shipper's display screen in an exemplary embodiment of the System in an
27 Internet environment;

28 [0079] FIG. 69 is a logic flow diagram that depicts the high level logic for tracking the
29 status of a particular package in an exemplary embodiment of the System in an Internet
30 environment;

1 [0080] FIG. 70 is a graphic representation of an exemplary embodiment of a Tracking
2 Failure Report Screen in an exemplary embodiment of the System in an Internet environment;

3 [0081] FIG. 71 is a graphic representation of an exemplary embodiment of a Successful
4 Tracking Report Screen for a package with Delivered status in an exemplary embodiment of
5 the System in an Internet environment;

6 [0082] FIG. 72 is a graphic representation of an exemplary embodiment of a Successful
7 Tracking Report Screen for a package with non-final status in an exemplary embodiment of
8 the System in an Internet environment;

9 [0083] FIG. 73 is a graphic representation of an exemplary CMS online user input screen in
10 an exemplary embodiment of the System in an Internet environment;

11 [0084] FIG. 74 is a graphic representation of an exemplary CMS display screen that reports
12 a successful tracking result in an exemplary embodiment of the System in an Internet
13 environment;

14 [0085] FIG. 75 is a graphic representation of an exemplary CMS error tracking report
15 display screen in an exemplary embodiment of the System in an Internet environment;

16 [0086] FIG. 76 is a graphic representation of an exemplary embodiment of a “My
17 Tracking” Screen in an exemplary embodiment of the System in an Internet environment;

18 [0087] FIG. 77 is a graphic representation of an exemplary embodiment of a Shipping Log
19 Screen;

20 [0088] FIG. 78 is a graphic representation of an exemplary embodiment of a Detailed
21 Shipping Log Entry Screen in an exemplary embodiment of the System in an Internet
22 environment;

23 [0089] FIG. 79 is a graphic representation of an exemplary embodiment of a detailed
24 “Quick Track” result screen in an exemplary embodiment of the System in an Internet
25 environment;

26 [0090] FIG. 80 is a graphic display of an exemplary embodiment of an “Add Inbound
27 Packages” Screen in an exemplary embodiment of the System in an Internet environment;

28 [0091] FIG. 81 is a graphic representation of an exemplary embodiment of a “View
29 Inbound Packages” Summary Screen in an exemplary embodiment of the System in an
30 Internet environment; and

1 [0092] FIG. 82 is a graphic representation of a View Inbound Packages Detail Screen in an
2 exemplary embodiment of the System in an Internet environment.

3

4 DETAILED DESCRIPTION OF THE INVENTION

5 [0093] A portion of the disclosure of this patent document, including but not limited to the
6 renderings of graphic user interface displays in FIGS. 10A through 10E, FIGS. 11 through 22,
7 FIGS. 24 through 26, FIGS. 28 through 30, FIGS. 34 through 35, FIG. 36A, FIG. 36F, FIGS.
8 40 through 53, FIGS. 56 through 63, FIGS. 68, and FIGS. 70 through 82, contains material
9 which is subject to copyright protection by Stamps.com, Inc. Stamps.com, Inc. has no
10 objection to the facsimile reproduction by anyone of the patent document or the patent
11 disclosure, as it appears in the Patent and Trademark Office patent file or records, but
12 otherwise reserves all copyright rights whatsoever.

13 [0094] “iShip.com™” (sometimes also referred to herein as “ISHIP.COM” or simply as
14 “iShip.com”), “iShip™” (sometimes also referred to herein as “ISHIP” or simply as “iShip”),
15 “The Internet Package Shipper™” (sometimes also referred to herein as “THE INTERNET
16 PACKAGE SHIPPER” or simply as “The Internet Package Shipper”), “Price It™”
17 (sometimes also referred to herein as “PRICE IT” or simply as “Price It”), “Sell It™”
18 (sometimes also referred to herein as “SELL IT” or simply as “Sell It”), “Track It™”
19 (sometimes also referred to herein as “TRACK IT” or simply as “Track It”), “Ship It™”
20 (sometimes referred to herein as “SHIP IT” or simply as “Ship It”), “Shipping Tools™”
21 (sometimes referred to herein as “SHIPPING TOOLS” or simply as “Shipping Tools”), “My
22 iShip™” (sometimes referred to herein as “MY ISHIP” or simply as “My iShip”) and
23 associated logos are trademarks of Stamps.com, Inc. The names of actual companies and
24 products mentioned herein may be the trademarks of their respective owners.

25

26 A. CONTEXTUAL OVERVIEW OF EXEMPLARY EMBODIMENT TYPES

27 [0095] Two types of exemplary Internet-related embodiments of the invention will be
28 described herein: 1.) an exemplary simplified Internet embodiment; and 2.) an exemplary
29 electronic commerce (“eCommerce”) embodiment. Because these two types of embodiments

1 differ somewhat in user interface interaction features and flow, a brief perspective overview
2 of these two exemplary embodiment types is provided below.

3

4 1. Exemplary Simplified Internet Embodiment.

5 **[0096]** In the exemplary simplified Internet embodiment of the invention, a system (the
6 “System”) exemplifying features of the invention provides a single automated computer
7 interface between users of the system who are shippers of parcels (“Shippers”) and multiple
8 carriers of parcels (“Carriers”). Each Shipper, using a client computer device, accesses the
9 System over a global communications network such as the Internet. Each Shipper uses the
10 System to arrange for, and manage the shipment of, one or more parcels. Each shipment
11 arranged by a Shipper is performed by a particular Carrier, using a particular service offered
12 by that particular Carrier. References herein to the words “parcel” and “package” include
13 letters, and larger items (*see, e.g.*, FIG. 15 below and Packaging types 1043 (Carrier Letter),
14 1044 (Carrier Pak), 1046 (Carrier Box), 1047 (Carrier Tube), and 1045 (Other Packaging)).

15 **[0097]** Each Carrier may provide one or more types of shipment services, such as, for
16 example, Next Day, Two-Day, etc. Each parcel shipped by the Shipper is shipped to a
17 particular Recipient. Each supported Carrier has a unique rating schedule, delivery and
18 pickup rules and schedules, and certification requirements (the “Carrier Rules”).

19 **[0098]** In the exemplary simplified Internet embodiment, the Shipper provides all
20 information required by the System to facilitate the shipping of each parcel to be shipped by a
21 Carrier designated by the Shipper; the recipient, once provided with a tracking number can
22 access the System to track the status of a package but is not called upon to provide any
23 information necessary to facilitate or manage the shipment. As is further described below, the
24 provision of information by the Shipper in the exemplary simplified Internet embodiment
25 differs from the exemplary eCommerce embodiment, in which both the Shipper (also referred
26 to as the “Seller”) and the Recipient (also referred to as the “Buyer”) provide information to
27 the System to facilitate and manage a particular shipment.

28

29 2. Exemplary eCommerce Embodiment.

1 [0099] In an eCommerce embodiment of the invention, the Shipper is a seller (the "Seller")
2 of goods through a particular eCommerce or electronic Auction ("eAuction") provider
3 (eCommerce or eAuction web site). The Seller/Shipper registers with a particular
4 eCommerce/eAuction provider (the "Provider") at the Provider's Web site to sell, advertise,
5 or otherwise describe, one or more items that the Seller/Shipper hopes to sell or award to the
6 highest bidder using an electronic auction facility.

7 [0100] As opposed to the exemplary simplified Internet embodiment where all information
8 necessary for arranging a particular shipment is provided by the Shipper, in the exemplary
9 eCommerce embodiment of the invention, the System prompts different individuals to
10 provide information necessary to rate and ship a particular parcel.

11 [0101] The Seller/Shipper (sometimes referred to herein simply as the "Seller," or as the
12 "Shipper") provides information to the System concerning the particular parcel that the Seller
13 will be selling/auctioning and subsequently shipping. The Seller also describes to the System
14 the Seller's rules by which potential and actual buyers (sometimes referred to herein as
15 "Buyers/Recipients", or simply as "Buyers", or as "Recipients") view the shipping, payment
16 and other options.

17 [0102] A potential Buyer of an item to be purchased from a particular Seller is prompted by
18 the System to initially provide certain limited shipping information (such as a destination zip
19 code) in order to preview shipping rates for the item that the Buyer is considering purchasing.

20 [0103] An actual Buyer is prompted by the System to provide shipping details such as the
21 Buyer's destination address. If the Seller has instructed the System to require the Buyer to pay
22 shipping costs, the System prompts the Buyer to make the final selection of Carrier and
23 Service.

24 [0104] The System in the exemplary eCommerce embodiment provides a communication
25 link between the Buyer and the Seller, sending certain types of notifications and information
26 between them.

27 [0105] Further differences between the exemplary eCommerce embodiment and the
28 exemplary simplified Internet embodiment include, among other things, the typical access
29 entry into the System. In the exemplary simplified Internet embodiment, the Shipper accesses

1 the Shipping site directly. In the exemplary eCommerce embodiment, the Seller/Shipper can
2 additionally “link” to the Shipping site from the relevant eCommerce Provider’s Site.

3 [0106] The System and screen flows for the exemplary simplified Internet and eCommerce
4 embodiments differ somewhat. A description of the features that are common between the
5 two types of embodiments of the present invention is provided below as is a description of the
6 differences between the two types of exemplary embodiments.

7 [0107] In the exemplary eCommerce embodiment described below, the present invention is
8 provided as a web-based application service from a common provider, sometimes referred to
9 herein as “iShip.com”. As such, the relevant eCommerce Provider does not have to install or
10 manage any server software; the Provider only provides a “link” to the System web site.

11 **B. SYSTEM OVERVIEW**

12

13 **1. Entity Interface Relationships**

14 [0108] FIG. 1 is a graphic representation depicting the interface relationships provided by
15 an exemplary eCommerce embodiment of the System 1 of the present invention between
16 electronic Commerce providers 2a-2n, Sellers/Shippers 3a-3n, Carriers 4a-4n, and
17 Buyers/Recipients 5a-5n. As conceptually depicted in FIG. 1, each Seller/Shipper 3a-3n
18 views the System 1 as an individualized automated Shipping System.

19 [0109] It should be noted that the use of suffixes such as “a” through “n” in connection with
20 numbered elements of the FIGURES herein are exemplary and are not a limitation of the
21 invention to any particular number. Rather, the suffixes “a” through “n” and “a” through “z”,
22 and similar notations, are used to represent any, but unknown, number of similar elements.

23 [0110] FIG. 2 depicts the interface relationships provided by an exemplary simplified
24 Internet embodiment of the System between the Shippers 3a-3n, Carriers 4a-4n, and
25 Recipients 5a-5n. As conceptually depicted in FIG. 2, each Shipper 3a-3n views the System 1
26 as an individualized automated Shipping System.

27 [0111] In both the exemplary eCommerce and simplified Internet embodiments, the System
28 1 provides Shippers/Users 3a-3n with a computerized shipping and tracking system that
29 allows shipment by the same Shipper/User 3a-3n of different packages using different

1 services provided by different Carriers 4a-4n. Carriers 4a-4n supported by the System include
2 Carriers such as Airborne, FedEx, United Parcel Service, USPS, and Yellow Freight. The
3 System 1 is completely expandable and scalable to include additional Carriers.

4

5 **2. System Configuration and Architecture**

6 [0112] In both the exemplary eCommerce and simplified Internet embodiments, as depicted
7 in FIG. 3, each User 7 (Shipper/Seller or Buyer/Bidder) has access to a computer 8, for
8 instance a personal computer ("PC"). The computer 8 is configured with a display device 9
9 that provides a display screen 10. The computer 8 is further configured with one or more user
10 input devices, such as, for example, a keyboard 11 and a mouse 12. The computer 8 is also
11 configured with a printing device 13, such as a laser printer. The computer 8 may also be
12 configured with a scale 1024 and a bar code reader 1027.

13 [0113] Users access 1003 and browse the Internet 15 using a web browser 14 that generally
14 resides and is executed on the user's PC 8. The web browser 14 is a computer program or set
15 of computer instructions that allows the Shipper/User 7 to retrieve and render hyper-media
16 content from one or more Server computers, e.g., 20a-21z available over the Web. Suitable
17 commercially available web browsers include, e.g., Netscape's Navigator™ (also sometimes
18 referred to herein as "NETSCAPE NAVIGATOR" or simply as "Netscape Navigator") and
19 Microsoft Internet Explorer™ (also sometimes referred to herein as "MICROSOFT
20 INTERNET EXPLORER" or simply as "Microsoft Internet Explorer").

21 [0114] FIG. 4 is a simplified schematic diagram of a user's computer and the interface
22 between the user's computer and the System servers, such as 20a-21z in FIG. 3, using the
23 Internet in an exemplary embodiment of the invention in an Internet environment. PCs 8a-8n
24 are used by the Shippers and are connected to the Internet 15 through communication links
25 1003a-1003n respectively. Optionally, a local network 1004 may serve as the connection
26 between some of the PCs 8a-8n, such as the PC 8a, and the Internet 15. Servers 20a-21z are
27 also connected to the Internet 15 through respective communication links.

28 [0115] Continuing with FIG. 4, each of the PCs 8a-8n includes a central processing unit
29 ("CPU") 1020a for processing and managing data; user input devices such as a keyboard 11a

1 and a mouse 12a for inputting data and a main memory 1023a such as a Random Access
2 Memory (“RAM”). Information in text, graphic and other forms is displayed on the display
3 monitor (“CRT”) 9a under the control of the CPU 1020a. A communication device 1028a,
4 such as a modem, provides access 1003a to the Internet 15. In some embodiments, one or
5 more Input/Output (“I/O”) devices, such as a printer 13a, scale 1024a, or a bar code reader
6 1027a are configured with the PC.

7 [0116] FIG. 5 is a graphic representation of an exemplary configuration of the System in an
8 exemplary eCommerce embodiment of the invention depicting interfaces with Carriers
9 through Carrier Servers, e.g., 23-2 through 27-2, and Shippers/Users through User Input, e.g.,
10 18. When a Shipper/User ships a package using the System 1, one or more of the System’s
11 Servers, e.g., 21a-21n, create a new System tracking number 19. When a new System
12 tracking number is created, one of the System’s Database Servers, e.g., 20a-20n, adds a new
13 package record with the newly created System tracking number to a Package Table 28. The
14 Package Table 28 resides in the System database 22 and contains package records for System
15 processed packages. The System database may be stored on any storage medium, such as but
16 not limited to, RAM, hard drive, disk drive, tape drive, or other memory device. An
17 exemplary embodiment of the Package Table contains the following information: 1) Package
18 Tracking State ID; 2) Package Shipping State ID; 3) Actual Delivery Time; 4) Delivered To
19 information; 5) Shipping Date; 6) Carrier Tracking Number; 7) System Tracking Number; 8)
20 Carrier ID; 9) Actual Package Weight; 10) Service Description; and 11) Package OID. The
21 content of these fields are described further below.

22 [0117] As depicted in FIG. 5, using the Carrier’s Internet URL, the System 1 (labeled
23 “iShip.com” in FIG. 5) then makes an HTTP (HyperText Transfer Protocol) connection over
24 the Internet 15 to the Carrier’s web server, e.g., 23-2, 24-2, 25-2, 26-2, or 27-2, using the
25 URL information for the particular Carrier’s web server.

26 [0118] The World Wide Web (WWW or Web) is an access protocol for HTTP (HyperText
27 Transfer Protocol is the communication protocol used by the Internet). The unique
28 identifier for a Server computer is called the IP (Internet Protocol) address; the unique
29 identifier for a web site (web page) is called the URL (Uniform Resource Locator). A URL

1 indicates, among other things, where the Server is located, the location of the web site on the
2 Server, the name of the web page and the file type of each document.

3 [0119] Depending upon the Carrier, the System's 1 request and report interface with the
4 Carrier's web server is programmed in HyperText Markup Language ("HTML") (e.g., 24-1,
5 25-1, 27-1), Extensible Markup Language ("XML") (e.g., 26-1), or both HTML and XML
6 (e.g., 23-1), described by way of example. Examples of XML formatted requests and
7 responses with respect to Carrier interface communications are described below in connection
8 with, and depicted in, FIGS. 66 and 67.

9 [0120] While the Shipper's/Seller's PC is connected to the Internet 15, a Shipper/Seller
10 may enter the System's 1 Internet interface in one of several ways. The two principle ways
11 discussed herein and described below are: 1) by entering an Internet address, e.g., URL, to the
12 System's home page; or 2) by clicking on an HTML link in an eCommerce/eAuction
13 provider's Web site that contains the URL address to one of the System's Internet pages, for
14 instance, an initial User registration page. A User may enter the System 1 in other ways,
15 among which include a direct communication interface between the User's computer system
16 and the System 1.

17 [0121] FIG. 6 is a graphic representation depicting an alternate view of the System
18 comprising the System Data Center's Server Computers 20a-20n and 21a-21z, the System
19 Database 22, and the System's interfaces with Seller and Buyer computers 8a-8n, Carrier
20 Server computers 23-2 through 27-2, and eCommerce/eAuction Providers 28a-28n, via the
21 Internet 15.

22 [0122] FIG. 7 is a simplified graphic representation of an exemplary configuration of the
23 System, and relationships between the System and Carriers and Shippers/Users, in an
24 exemplary simplified Internet embodiment of the invention. As depicted in FIG. 7, multiple
25 servers 20a-21z are provided in a Network Operations Center ("NOC"). At least one of the
26 Servers 20a-21z can handle multiple telecommunications connections such as over the
27 Internet 15 at one time. In the embodiment of the NOC depicted in FIG. 7, one Server 20a
28 provides the computer resources to perform Proxy & Firewall functions between the Internet
29 15 and the NOC; one Server, e.g., 21n provides the computer resources to act as the NOC

1 Client Server; one Server, e.g., 21s provides the computer resources to act as the Tracking
2 Server to obtain Carrier tracking information 1019 from the respective carrier's to provide to
3 Shippers over the Internet 15; one Server, e.g., 20a provides the computer resources to act as
4 the Database Server to access data from one or more databases 22 of information; one Server,
5 e.g., 21t provides the computer resources to act as the Shipping Server; one Server, e.g., 21m
6 provides the computer resources to act as the Web Server; and one Server, e.g., 21z provides
7 the resources to provide other services, such as the upload of manifest data 1018 to the Carrier
8 Host Systems, 23-2 through 23-7.

9 [0123] It should be understood that the overview configurations of the System depicted in
10 FIG. 5, 6 and 7 are exemplary. For example, the depiction of Server 20a in FIG. 7 as having
11 access to one or more databases 22 is not a limitation of the invention; in alternative
12 embodiments, such as depicted in FIG. 5, any or all of the Servers, 20a-20n, have access to
13 databases and external storage medium.

14 [0124] Continuing with FIG. 7, the Servers 20a-21z are connected to or otherwise capable
15 of communicating through, a communications network such as a global communications
16 network such as the Internet 15, which is in turn connected to, or capable of communicating
17 with one or more Personal Computers ("PC") or other like devices, e.g., 8a, 8b, . . . 8n.

18 [0125] Continuing with FIG. 7, Users access and browse the Web using a web browser that
19 generally resides and is executed on the user's PC, e.g., 8a, 8b, 8c . . . 8n (and as were
20 depicted in FIG. 4).

21 [0126] The Internet works based on a client/server model. The present invention uses the
22 client/server model to support the communication with and processing for each of multiple
23 Shippers. For example, as depicted in FIG. 7, the Servers 20a-21z are the server side of the
24 client/server model; each Shipper's PC 8a, 8b, . . . 8n is a client. The present invention uses
25 the web browser with which each Shipper's PC accesses the Internet to perform certain
26 functions as further described herein.

27 [0127] Web sites are locations on Servers, such as one or more of the Servers, 20a-21z, that
28 are accessible through the Internet 15. The Servers 20a-21z host one or more web sites which
29 are accessible by Shipper users with PCs (e.g., 8a, 8b, . . . 8n) connected with the Internet 15.

1 [0128] Carrier Rules, Shipper account information and other content is stored by the
2 Servers, e.g., 20a in databases e.g. 22. Shippers with PCs (e.g., 8a, 8b, . . . 8n) connected to
3 the Internet 15 access Carrier Rules, Shipper account information and other content that is
4 stored by the Servers, e.g., 20a in databases e.g. 22 through a User Interface, which is
5 described in detail below.

6 [0129] An overview of an exemplary System architecture is depicted in FIG. 8. The
7 overview depicted is exemplary and meant to be illustrative; it is not a limitation of the
8 invention. As depicted in FIG. 8, one embodiment of the invention uses a three-tiered
9 architecture.

10 [0130] The Data Management Tier 1201 is comprised of a Database Storage component
11 1202 that in the embodiment depicted uses an SQL Server; a Message Queue Storage
12 component 1203 that in the embodiment depicted uses MS Message Queue; and a File
13 Storage component 1204 that in the embodiment depicted uses NTFS, and DFS. Each of the
14 Database Storage component 1202, the Message Queue Storage component 1203, and the File
15 Storage component 1204, communicate with the Component Tier 1208 of the System
16 architecture, communications by each component with the Component Tier 1208 represented
17 by elements 1205, 1206 and 1207 respectively. According to the embodiment depicted in
18 FIG. 8, the Server Components of the Component Tier 1208 use C++ programming language
19 and COM Objects.

20 [0131] The Application Tier 1212 of the System Architecture is comprised of a Web
21 Shipper Client component 1213 (which uses HTML, ASP and JavaScript), the NOC
22 Administration component 1214 (which uses HTML, ASP, VB, and C++), and the Web
23 Shipping Station component 1215 (which uses HTML, ASP, JavaScript, C++, and ActiveX
24 Controls). Each of the Web Shipper Client component 1213, the NOC Administration
25 component 1214, and the Web Shipping Station component 1215 communicate with the
26 Server Components of the Component Tier 1208 as represented by the communication
27 elements 1209, 1210 and 1211 respectively.

28 [0132] In one embodiment, the System is implemented in an NT environment. The
29 description of the System as being implemented in an NT environment is exemplary and is

1 not a limitation of the invention.

2

3 3. Menu Architecture

4 [0133] In both the exemplary eCommerce and simplified Internet embodiments, a User can
5 enter the System by entering an Internet address, e.g., a URL, to the System's home page
6 using the User's client web browser.

7 [0134] FIG. 9 is a graphic representation of an exemplary menu architecture as would be
8 displayed on an exemplary home page in an exemplary eCommerce embodiment of the
9 System 1 as viewed by the User on a display device, e.g., 9 and 10 as depicted in FIG. 3 and
10 9a as depicted in FIG. 4, connected to the User's Computer, e.g., 8 as depicted in FIG. 3 and
11 8a as depicted in FIG. 4. The term display as used herein will be understood by those with
12 ordinary skill in the art to include visual display on a display device, e.g., 9 and 10 as depicted
13 in FIG. 3 and 9a as depicted in FIG. 4, connected to the User's Computer, e.g., 8 as depicted
14 in FIG. 3 and 8a as depicted in FIG. 4.

15 [0135] Other menu configurations and descriptions can be implemented without departing
16 from the spirit of the invention. As depicted in FIG. 9, a main menu bar 34 presents several
17 selection options, including Home 30a, Sell It 31a, Ship It 32a, and Track It 33a. If a User
18 selects, such as by using a keyboard device 11 as shown in FIG. 3, 11a as shown in FIG. 4, or
19 a mouse device 12 as shown in FIG. 3, 12a as shown in FIG. 4, the Home 30a option, the
20 System 1 will display a Home submenu 30b.

21 [0136] References to a User selecting will be understood by those with reasonable skill in
22 the art to include selection using a user input device, such as a keyboard device 11 as shown
23 in FIG. 3, 11a as shown in FIG. 4, or a mouse device 12 as shown in FIG. 3, 12a as shown in
24 FIG. 4, connected to the User's Computer, e.g., 8 as depicted in FIG. 3 and 8a as depicted in
25 FIG. 4.

26 [0137] Using the exemplary menu architecture depicted in FIG. 9, if the User selects the
27 Sell It 31a option, the System 1 will display a Sell It submenu 31b. If the User selects the
28 Ship It option, the System 1 will display a Ship It submenu 32b. If the User selects the Track
29 It 33a option, the System 1 will display a Track It submenu 33b.

1 [0138] In an exemplary simplified Internet embodiment of the invention, the Main Menu
2 would not provide a Sell It 31a application or the submenus and screens associated with the
3 Sell It 31a application.

4

5 **C. THE SELLER'S EXPERIENCE**

6 [0139] In an exemplary eCommerce embodiment of the System, if the User enters the
7 System through a link from a Provider, the System 1 will ask the User to log in. (A User that
8 is a Buyer/Bidder that enters the System with a particular Buyer/Bidder URL (Universal
9 Resource Locator), such as through a hypertext e-mail link as is discussed below, is not
10 required to follow the log in procedure.) The log in and registration processes described
11 below are also provided in a similar manner by some simplified Internet embodiments.

12 [0140] When a User attempts to log in, the System 1 will attempt to validate the User's log
13 in identification and password. If the User's log in is successful, the System 1 will prompt
14 the User to select one of the available menu options. Otherwise, the System 1 will prompt the
15 User to register and will display the first of several information collection screens to prompt
16 the User through the registration process. Following is a description of the registration User
17 Interface and the associated System 1 processing in an exemplary eCommerce embodiment of
18 the invention.

19 [0141] FIGS. 10A through 10E are high level logic flow diagrams depicting the logic flow
20 for processing both Shipper/Seller and Buyer/Bidder information in an exemplary
21 eCommerce embodiment of the invention. An overview of FIGS. 10A through 10E is
22 provided immediately below for context. However, the detailed description of FIGS. 10A
23 through 10E is provided in conjunction with the detailed user interface screens depicted in
24 summary on FIGS. 10A through 10E. Accordingly, the description of FIGS. 10A through
25 10E is provided gradually below with intervening descriptions of the details concerning the
26 user interface screens described in more detailed FIGURES that are also described below.

27 [0142] FIG. 10A depicts general Seller/Shipper/User registration procedures. FIG. 10B
28 depicts eCommerce/eAuction Seller registration procedures, including the Creation of a Link
29 that the Seller can copy and paste in the Seller's Web page description of the item to be

1 sold/shipped. FIG. 10C depicts the actual sales of the item to be shipped and depicts the
2 Buyer 80 experience of viewing the shipping rates and times comparison provided by the
3 System and purchasing or bidding on the item as the case may be. FIG. 10D depicts the
4 collection of shipping and payment information by the Seller and the System 1 from the
5 Buyer 80. FIG. 10E depicts post sale shipment and payment processing, tracking and
6 notification. The components of each of FIGS. 10A through 10E are discussed in detail
7 below.

8 [0143] FIG. 10A depicts general User registration procedures. As depicted in FIG. 10A, the
9 System 1 displays a registration introduction screen 41 to prompt a new eCommerce/eAuction
10 Seller 40 to register with the System 1.

11 [0144] FIG. 11 is a graphic representation depicting an exemplary embodiment of a
12 registration introduction screen 41 depicted in FIG. 10A. As depicted in FIG. 11, the
13 registration introduction screen 41 displays introductory text 101 that prompts the User to
14 proceed to the Next screen to provide certain information, such as the User's e-mail and
15 return address and to identify the Carriers with which the User wishes to ship. The User is
16 instructed to press the Next button 102 if the User is ready to proceed with registration. It
17 will be understood by those with ordinary skill in the art that a User "presses" or "clicks" an
18 onscreen button by using a user input device, such as a keyboard device 11 as shown in FIG.
19 3, 11a as shown in FIG. 4, or a mouse device 12 as shown in FIG. 3, 12a as shown in FIG. 4,
20 connected to the User's Computer, e.g., 8 as depicted in FIG. 3 and 8a as depicted in FIG. 4.

21 [0145] Alternatively, the User can "press", or "click", on the Reset button 103 which, when
22 clicked, re-initializes the registration application and returns the User to the Introduction
23 page; the Cancel button 104, which when clicked returns the User to the Logged Off Home
24 page; or the Help button 105, which when clicked, displays contextual help text in a pop-up
25 window.

26 [0146] If the User clicks on Next button 102, if the User is using a browser that is not
27 supported by the System 1, the System 1 prevents the User from continuing and displays a
28 message to the User that the User's browser is unsupported. Otherwise, if the User clicks the
29 Next button 102, the System 1 will display the next screen 42 in the registration process as

1 depicted in FIG. 10A, which is a User address collection screen.

2 [0147] FIG. 12 is a graphic representation depicting an exemplary embodiment of a User
3 address collection screen. As depicted in FIG. 12, the System prompts the User to provide
4 the User's name 106, e-mail address 107, company name 108, street address 109, floor/room
5 number 110, department name 111, city 112, state 113a (using a pull down menu button
6 113b), telephone number 114, zip code 115, and fax number 116. As with the previous
7 registration introduction screen 41, the Next 102, Reset 103, Cancel 104, and Help 105
8 buttons are provided with results similar in nature to the operations of these respective buttons
9 as described above. In addition, a Back button 117 is provided. If the User clicks the Back
10 button 117, the System returns the User to the screen from which the User entered the present
11 screen, in this case, the registration information screen 41. If the User clicks the Next button
12 102, the System performs validation edits on the data entered. If any required fields have not
13 been completed, or if any fields contain data found to be in error, the System notifies the User
14 and requests that corrected data be entered. Because of the similar nature from screen to
15 screen in the System with which the Back 117, Next 102, Reset 103, Cancel 104 and Help
16 105 buttons operate, the operation of these buttons will not be further described.

17 [0148] If the data entered is successfully validated, the System displays the next screen,
18 which in this case is the Shipping Location screen 43 as depicted in FIG. 10A. FIG. 13 is a
19 graphic representation of an exemplary embodiment of a Shipping Location screen 43. In the
20 Shipping Location screen 43, the System prompts the User to identify a default location 120a
21 from which the User will typically ship packages and to provide the city 122, state 123a-123b,
22 and zip code 124 of that location 120b. The Shipping Location screen provides a shipping
23 location input field 121a and a shipping location pull down menu button 121b. If the user
24 clicks on the shipping location pull down menu button 121b, the System will display a
25 selection menu of possible shipping locations. Example shipping location selection options
26 include: self-service center/drop box; staffed shipping counter; my location by calling for
27 pickup; my location through regular pickup; and my local Mail Boxes Etc. center. Exemplary
28 shipping location options are described further below with regard to FIG. 26.

29 [0149] If the User selects the "my local Mail Boxes Etc. center" then a Locations screen is

1 displayed. FIG. 14 is a graphic representation depicting an exemplary embodiment of a
2 Locations screen. The Locations screen displays a Locations button 126, that when clicked,
3 causes the System to display a list 127 of Mail Boxes Etc. centers in the area in and around
4 the User's zip code. Each entry in the list 127 contains the name and address of the location
5 128, pickup times 129, and comments 130. The User will be asked to highlight and thereby
6 select one of the centers. According to the User's selection, the System will display
7 additional comments if appropriate, e.g., 131. Otherwise, for the other shipping location
8 selection options, the User is required to enter the city, state, and zip code of the location.

9 [0150] FIG. 15 depicts an alternative exemplary embodiment of a Locations screen as a
10 screen inset. If the Shipper selects a particular "ship center" type from a shipping location pull
11 down menu (not shown) as the shipping location, the User Interface will display, as shown in
12 FIG. 15, three elements: 1) a table 1058 with the Location Address, Pickup Times and
13 Comments Area; 2) a Browse button 1059; and 3) a destination Zip Code field 1042. Clicking
14 the Browse button 1059 will display additional Drop Off Locations in a Pop-up window (not
15 shown).

16 [0151] Returning to FIG. 14, if the User clicks the Next button 102, and if the data entered
17 in the Shipping Locations screen is successfully validated, the System displays the next
18 screen, which in this case is the UPS registration screen 44 as depicted in FIG. 10A. FIG. 16
19 is a graphic representation of an exemplary embodiment of a UPS registration screen 44. If
20 the User indicates that the User will ship through the System using UPS and that the User
21 already has a UPS account 140, the User will be asked to provide the UPS account number
22 141 and the scheduled pickup time 142a, a.m. 142b, and p.m. 142c. The System provides the
23 User with other UPS shipping options, such as dropping the UPS shipments at a shipping
24 center such as a Mail Boxes Etc 143, or not using the System for shipping UPS 144.
25 Depending on the User's selection, the System provides appropriate special circumstance
26 notification 145 if required.

27 [0152] If User clicks the Next button 102, and if the data entered in the UPS registration
28 screen is successfully validated, the System displays the next screen, which in this case is the
29 eCommerce registration introduction screen 45 as depicted in FIG. 10A. FIG. 17 is a graphic

1 representation of an exemplary embodiment of an eCommerce registration introduction
2 screen 45. The eCommerce registration introduction screen 45 provides a textual description
3 150 of the procedure to setup selling preferences for eCommerce transactions.

4 [0153] If the user clicks the Finish button 152 on the eCommerce registration introduction
5 screen 45, the System finalizes the registration process 46 and sends the User to a registration
6 complete screen 48a as depicted in FIGS. 10A and 10B. FIG. 10B depicts
7 eCommerce/eAuction Seller registration procedures, including the Creation of a Link that the
8 Seller can copy and paste in the Seller's Web page description of the item to be sold/shipped.

9 [0154] FIG. 18 is a graphic representation of a registration complete screen 48a. The
10 System informs the User that the User is registered 153 and that the User's ID and password
11 will be e-mailed to the User 154. The System summarizes the registration information for the
12 User 155 and instructs the User 156 to click on the Close button 157 to log on to the System
13 for the first time. If the User clicks on the Close button 157 and logs on to the system, a
14 Welcome screen, e.g., 48b as depicted in FIG. 10B, is displayed from which the User can
15 request that a Seller's Link be created.

16 [0155] If the user clicks the Continue button 151 on the eCommerce registration
17 introduction screen 45, the System will display 47 the next screen, which is an eCommerce
18 registration screen 49 as depicted in FIGS. 10A and 10B.

19 [0156] FIG. 19 is a graphic representation of an exemplary embodiment of the Seller's
20 Carrier/Service Preferences Screen 49 as depicted in FIG. 10B. With the Seller's
21 Carrier/Service Preferences Screen 49, the System requests 159 the User to identify the
22 Carriers and the Services of each Carrier (e.g. Overnight Air Express 161a, Next Afternoon
23 Service 161b and Second Day Service 161c for Airborne Express 160; First Overnight 163a,
24 Priority Overnight 163b, Standard Overnight 163c, 2 Day 163d and Express Saver 163e for
25 FedEx 162; Next Day Air Early AM 165a, Next Day Air 165b, Next Day Air Saver 165c, 2nd
26 Day Air AM 165d, 2nd Day Air 165e, Three Day Select 165f and Ground 165g for UPS 164;
27 and Express Mail 167a and Priority Mail 167b for USPS 166) that the User is willing to allow
28 Buyers/Bidders to choose for shipping the item(s) to be shipped. Each supported Carrier,
29 e.g., Airborne Express 160, FedEx 162, UPS 164, and USPS 166 is available for selection by

1 the User. Further, each service offered by a particular Carrier is also available for User
2 selection. For example, for Airborne Express, Overnight Air Express 161a, Next Afternoon
3 Service 161b, and Second Day Service 161c are available for User selection. The User
4 selects a Carrier or a service by clicking on the selection button, e.g., 160.

5 [0157] FIG. 20 is a graphic representation of an alternative embodiment of the Seller's
6 Carrier/Service Preferences Screen 49. In the example depicted in FIG. 20, the User has
7 selected all Carriers and all services for all Carriers.

8 [0158] If the User clicks the Next button 102 on the Seller's Carrier/Service Preferences
9 Screen 49, the System will display the next screen, which is Seller's Charges and Payment
10 Preferences Screen 50 as depicted in FIG. 10B. FIG. 21 is a graphic representation of an
11 exemplary embodiment of a Seller's Charges and Payment Preferences Screen 50. The
12 System asks the User to select a format for presentation of shipping charges to the
13 Buyer/Bidder 169. The User can select any one of the following choices: 1) the item cost
14 includes shipping charges 170; 2) buyer pays actual shipping charges 171; or 3) buyer pays
15 shipping plus additional charges 172.

16 [0159] If the User chooses the option that the buyer pays shipping charges plus additional
17 charges, then the User must select the types of additional charges that apply, and the value to
18 be added: 1) add percentage of shipping cost 173 and specify percentage 174; 2) add fixed
19 handling charge 175 and specify the amount of the handling charge 176; and/or 3) add System
20 Service Fee 177.

21 [0160] The System also requires that the User select at least one payment method 178: Visa
22 179a, American Express 179b, Personal Check 179c, Cashier's Check 179d, MasterCard
23 179e, Discover 179f, and/or Money Order 179g. The User is also given the option of
24 requesting that the System collect credit card information and provide the information to the
25 User so that the User can process the information 180.

26 [0161] If the User clicks the Finish button 152 on the Seller's Charges and Payment
27 Preferences Screen 50, then the System will display the Registration Completion Screen 48a
28 previously described above.

29 [0162] FIG. 22 is a graphic representation of an alternative embodiment of the Seller's

1 Charges and Payment Preferences Screen 50 depicting User selections of some of the
2 available options. If the User clicks the Save button 181, the System validates the
3 information, saves the User's choices and specifications, and completes the registration
4 process.

5 [0163] Similarly, with respect to FIG. 21, if the user clicks the Finish button 152 on the
6 Seller's Charges and Payment Preferences Screen 50, the System finalizes the registration
7 process and displays the registration complete screen 48a as depicted in FIG. 10B. As was
8 previously described above, in the registration complete screen 48a, the System summarizes
9 the registration information for the User 155 and instructs the User 156 to click on the Close
10 button 157 to log on to the System for the first time. If the User clicks on the Close button
11 157 and logs on to the system, a Welcome screen, e.g., 48b as depicted in FIG. 10B, is
12 displayed from which the User can request that a Seller's Link be created.

13 [0164] FIG. 23 is a System interactivity data and logic flow diagram depicting an
14 exemplary embodiment of the Seller's eCommerce Registration process. FIG. 23 depicts the
15 interactivity between the User's client machine (Seller's computer) 8 and the System's server
16 computers 20a-21z. Also depicted are the data accesses to the System database 22. An arrow
17 230 extending from the top of the diagram and pointing down towards the bottom of the
18 figure graphically represents the passage of time.

19 [0165] As depicted in FIG. 23, the Seller clicks on the Pricing Preferences submenu option
20 231 (equivalent to 31b-1 as depicted in FIG. 24 under the Sell It option 31a of the main menu
21 34 as depicted in FIG. 9). The System servers 20a-20n then access the System database 22 to
22 determine whether the Seller's preferences have previously been set 232. In the case that no
23 preferences are found for the specified Seller 233, the System servers 21a-21z generate the
24 signals necessary to display the Carriers and Services Screen 234 to the Seller's computer 8.
25 The Seller selects the Seller's preferred Carriers and Services and clicks the Next button 235
26 returning control to the System servers 21a-21z. The System servers 21a-21z next generate
27 the signals necessary to display the Charges and Payment screen 236 to the Seller's computer
28 8. The Seller selects the Charges and Payment options and clicks the Save button 237. The
29 System servers 21a-21z validate the Seller preference information and the System servers

1 20a-20n store 238 the information on the System database 22. The System servers generate
2 the signals necessary to notify the Seller at the Seller's computer 8 that the Seller's
3 preferences have been saved 239.

4 [0166] There are different ways by which a User can request the System to create a Seller's
5 Link. One way is for the User to enter the System's home page, log in 48b, e.g., as depicted
6 in FIG. 10B, and click on the Sell It 31a, or equivalent, application on the main selection bar
7 34 as depicted in FIG. 9. Another way is to click on the System logo icon as provided in an
8 eCommerce/eAuction Provider's web site. There are other ways that a User can enter the
9 System. For instance, the eCommerce/eAuction Provider might provide a hyperlink to the
10 System web site.

11 [0167] If the User enters the System Web site, and clicks on the Sell It selection 31a, the
12 System presents either a submenu such as 31b as depicted in FIG. 9, or displays a default first
13 screen in the Sell It application, depending on the embodiment.

14 [0168] If the User has not completely registered for the System and for eCommerce
15 shipping processing, then the System prompts the User to complete the necessary registration
16 process by displaying a Registration Needs Completion screen 51 as depicted in FIG. 10B.

17 [0169] FIG. 24 is a graphic representation of a Registration Needs Completion Screen 51.
18 Similar to the screen depicted in FIG. 17, the System requests the User to provide the
19 necessary information by completing the information requested in subsequent screens 150-1.
20 If the User clicks the Next button 102, the System displays the Seller's Carrier/Service
21 Preferences Screen 49, and the Seller's Charges and Payment Preferences Screen 50 as
22 depicted in FIG. 10B.

23 [0170] Once the User has completed registration for the System and for eCommerce
24 shipping processing, the System allows the User to select the Create Link submenu option
25 31b-2 in the Sell It Application 31a of the System. If the User selects the Create Link option
26 31b-2, the System displays a Create a Seller's Link Screen 52 as depicted in FIG. 10B. FIG.
27 25 is a graphic representation of an exemplary embodiment of a Create a Seller's Link Screen
28 52.

29 [0171] Before the System can create a Seller's link, the User must tell the System

1 information about the particular package that will be shipped. Accordingly, as depicted in
2 FIG. 25, the System asks the User to enter the shipping weight and value of the item to be
3 shipped 190. The User is asked to enter the Shipping Weight 191a.

4 [0172] FIG. 26 depicts an exemplary alternative embodiment of a screen for the input of
5 Shipper Parcel Specifications, which in the exemplary alternative embodiment depicted is
6 titled the Location and Package Screen. The Location and Package Screen depicted in FIG. 26
7 collects Shipper input similar to a portion of the information that which was described in
8 connection with FIGS. 13 and 25.

9 [0173] As shown in FIG. 26, the Shipper is asked to input the location 1040 from which the
10 parcel will be shipped. A pull down menu activation mechanism 1041 is provided to allow
11 the user to pull down a menu (not shown) of different shipping locations. It should be noted
12 that the exemplary selection mechanisms, e.g., “pull down menu”, “drop down selection”, and
13 others, described herein are used for illustrative purposes and are not a limitation of the
14 invention.

15 [0174] The Shipper activates the pull down menu by placing the cursor of the Shipper’s PC
16 over the pull down menu activation mechanism 1041 and leaving the cursor in the same
17 position for a certain period of time (this method of activating a selection mechanism will be
18 referred to herein as a “Pause Activation”). In alternative embodiments, the Shipper activates
19 the pull down menu by placing the cursor of the Shipper’s PC over the pull down menu
20 activation mechanism 1041 and clicking the Shipper’s user input device (this method of
21 activating a selection mechanism will be referred to herein as a “Click Activation”). It should
22 be understood that for each activation mechanism depicted in the User Interface of the Present
23 Invention, that the exemplary embodiments of the User Interface depicted herein use the
24 Pause Activation method; alternative embodiments use the Click Activation method.

25 [0175] References herein to “clicking” mean that the Shipper places the cursor of the
26 Shipper’s PC on the subject item and clicks the Shipper’s user input device.

27 [0176] If the Shipper activates the pull down menu activation mechanism 1041, a menu of
28 different shipping locations (not shown) appears in the Location area 1074 of the screen. The
29 Shipper then selects one of the shipping locations by placing the cursor of the Shipper’s PC

1 over a particular shipping location in the shipping location menu and clicking the Shipper's
2 user input device, e.g., mouse.

3 [0177] It should be understood that for each selection mechanism depicted in the exemplary
4 embodiments of the invention, selection of a particular choice from such a selection menu is
5 made by the Shipper clicking the Shipper's user input device.

6 [0178] There are two types of shipping locations, ship centers and customer drop offs. Ship
7 centers are those locations which refer to a database of specific locations, from which a
8 specific location from the available locations must be selected to determine rates, such as an
9 "iShip Center". Customer drop offs are those shipping locations from which a specific
10 location need not be selected to determine rates, such as a "drop box", "carrier counter" or
11 "call for pickup". The shipping location pull down menu displays each shipping location
12 category, e.g., iShip Center, other specific shipping center types, drop box, carrier counter,
13 call for pickup, etc.

14 [0179] As was described with regard to FIG. 15 above, if the Shipper selects a particular
15 "ship center" type from the shipping location pull down menu (not shown) as the shipping
16 location, the User Interface will display, as shown in FIG. 15, three elements: 1) a table 1058
17 with the Location Address, Pickup Times and Comments Area; 2) a Browse button 1059; and
18 3) a destination Zip Code field 1042. Clicking the Browse button 1059 will display additional
19 Drop Off Locations in a Pop-up window (not shown).

20 [0180] Returning to FIG. 26, if the Shipper selects a "customer drop off" as the shipping
21 location, the User Interface will display, as shown in FIG. 26, two elements: 1) Origin Zip
22 Code Field 1053; and 2) Destination Zip Code Field 1042.

23 [0181] For either class of shipping location, if an iShip Shipping Station will not be present
24 at the selected shipping location, the System displays a notice (not shown) to the customer
25 telling them that they must have a laser printer to ship using the specified location.

26 [0182] If the Shipper is Logged On to the System and has established an account, the
27 System will default the Shipping Location to the Shipper's specified Preferences which the
28 Shipper inputs (not shown) the first time that the Shipper logs into the System. If the
29 Shipper's specified Preference is a "customer drop off" location, the System populates the

1 Origin Zip Code with the Shipper's default Zip Code which the Shipper inputs (not shown)
2 the first time that the Shipper logs into the System.

3 [0183] If no location is selected by the Shipper, the System displays a message (not shown)
4 asking the Shipper to select a shipping location.

5 [0184] In the Package area 1075 of the screen depicted in FIG. 26 there are the following
6 controls or control groups: 1) "Packaging" which includes various types of parcel packaging ,
7 as shown in item numbers 1043-1047 and includes Length 1048, Width 1050 and Height
8 1049 which are required data fields for parcels designated by the Shipper as the type "Other
9 Packaging"; 2) Weight 1051 (If the Shipper specifies one of the recognized carrier packaging
10 types (Letter, Pak, Box, Tube) the field will be auto filled with "letter", "pak", etc.); and 3)
11 additional handling 1052. If "Letter" is selected the weight will be set by the System to 0.5
12 lbs. Otherwise, weight may be input by the Shipper (612, FIG. 27A) using a user input
13 device such as a keyboard, with weights ranging from 1 to 150 lbs. If a specific weight is
14 selected or input, the Packaging Type will be set to Carrier Box.

15 [0185] In order to identify the weight of the parcel to the System, in one embodiment of the
16 invention, the Shipper's PC is configured with a scale and the System communicates with the
17 Shipper's scale using the user's client web browser. FIGS. 27A through 27C depict the logic
18 flow for communications between the System and a Shipper's PC and a scale configured with
19 the Shipper's PC. As depicted in FIGS. 27A through 27C, the Shipper establishes in the
20 System certain information about the Shipper's PC configuration at the time the Shipper sets
21 up an Account 601. If the Shipper's PC is configured with a scale, the Shipper specifies scale
22 configuration information 602 such as: the make and model of scale, and the type of port
23 (e.g., serial or parallel) with which the scale is configured with the PC. Further, the System
24 provides storage and access 603 for the Shipper's scale configuration information in a
25 database 604.

26 [0186] Continuing with FIGS. 27A through 27C , the System supports various makes and
27 models of scales. Each scale make and model has a set of features and requirements for which
28 the System must be programmed in order for the System to communicate properly with each
29 particular scale. The System provides an ActiveX control dedicated to communications with

1 peripheral devices configured with client PCs (“Shipping Station ActiveX Control”) 607.
2 Contained within the Shipping Station ActiveX Control is a table (the “scale table”) 608
3 containing entries for each supported scale make and model and provides logic to process the
4 communication information for each scale make and model as appropriate. It should be
5 understood by someone skilled in the art that the Shipping Station ActiveX Control facilitates
6 communications with various devices on the client machine. The Shipping Station ActiveX
7 Control 607 and the scale table 608 are requested 606 by the web page (the “System/scale
8 interface”) containing the Weight field 1051 at the time that the Shipper activates 605 the
9 Weight field 1051. Once the web page requests the Shipping Station ActiveX Control 607,
10 the Shipping Station ActiveX Control 607 is automatically installed on the client 609. In the
11 event that the Shipping Station ActiveX Control is updated to facilitate the support of
12 additional scale makes and models, the Shipping Station ActiveX Control is automatically
13 reinstalled on the particular client PC the next time that the Shipper activates the Shipping
14 Station ActiveX Control.

15 [0187] Continuing with FIGS. 27A through 27C, the Shipper places 610 the Subject Parcel
16 on the scale, such as, e.g., the scale 1024a depicted in FIG. 4, and 1024n depicted in FIG. 7.
17 The Shipper activates the Shipping Station ActiveX Control by placing the cursor of the
18 Shipper’s PC on the Weight field 1051 (such as the Weight field 1051 depicted in FIGS. 15
19 and 26). The System checks the Shipper’s scale configuration information to determine 611
20 whether the Shipper’s PC is configured with a scale. If so, the System activates the
21 System/scale interface 613. Otherwise, the user may input the weight 612 in the Weight field
22 1051 as depicted in e.g., FIG. 26.

23 [0188] In one embodiment of the System/scale interface aspect of the invention, the System
24 uses ActiveX control language and the client’s web browser, such as Internet Explorer
25 browser. Continuing with FIGS. 27A through 27C, using the Shipper’s scale configuration
26 information, the System calls Windows libraries 615 to open the serial or parallel port with
27 which the scale is configured, as the case may be and as is specified in the Shipper’s scale
28 configuration information. Windows is an operating system used with most PCs.

29 [0189] Continuing with FIGS. 27A through 27C, the System uses the information for the

1 particular scale make and model from the scale table 608 of scale makes and models to send a
2 communication query to the particular scale 616. Typically, the communication query
3 information required by a particular scale make and model is a particular set of characters.
4 Each scale make and model recognizes a unique set of characters as a request for a weight.
5 Accordingly, the appropriate set of characters that means a request for weight to a particular
6 scale make and model is stored in the scale table for a particular scale make and model.

7 [0190] Continuing with FIGS. 27A through 27C, after a proper query, a scale will return a
8 data stream containing the weight of the parcel 617. Depending on the scale make and model,
9 other types of information may be contained in the return data stream. The System accesses
10 the scale table 608 to interpret 618 the return data stream according to the scale make and
11 model rules as stored in the scale table and as programmed in the Shipping Station ActiveX
12 Control.

13 [0191] Other scale communication information is contained in the scale table for each scale
14 make and model, including, for example: the character string that communicates a request as
15 to whether or not the weight is stabilized; the default contents of the return data stream of the
16 weight from a particular scale make and model; and the character string to request that the
17 scale send the weight mode with the return data stream. Weight mode is the mode with which
18 the scale measures weight (e.g., pounds, kilograms, etc.).

19 [0192] In one embodiment, if no weight difference is determined, as long as the Shipper's
20 cursor remains on the Weight field 1051 (such as the Weight field 1051 depicted in FIGS. 15
21 and 26), the System polls the scale repeatedly requesting the weight and requesting
22 notification that the weight is stabilized 619. Each time the System polls the scale, the System
23 tests to determine 620 whether or not there is a difference in the weight as compared with the
24 last time that the System polled the scale. If the System determines a difference in weight,
25 then the System uses the Shipping Station ActiveX Control to fire an event 621 to the client
26 web browser to display on the User Interface screen that the weight has changed.

27 [0193] In one embodiment, once the Shipper removes the cursor from the Weight field
28 1051, the System stops polling the scale 622. If prior to the last polling to the scale, the scale
29 notifies the System that the weight has stabilized 623, the System will proceed with preparing

1 the Graphic Array if requested to do so by the Shipper 625. Otherwise, if the System
2 determines a difference in weight, the System notifies the Shipper that the weight is not stable
3 624.

4 [0194] The Shipper can use the Shipper's input device connected to the Shipper's PC, such
5 as a mouse 12a, as depicted in FIG. 4, to position the cursor on one of the navigational
6 buttons 102-105 shown at the bottom of the screen as depicted in FIG. 26 described above. If
7 the Shipper clicks the "Next" button 102, the System will display the next Screen, which, in
8 the embodiment depicted, is the Rates and Times Screen (an exemplary embodiment of which
9 is depicted in FIG. 36A described below). If the Shipper clicks the "Reset" button 103, the
10 System will clear the values displayed on the current screen. If the Shipper clicks the
11 "Cancel" button 104, the System will cancel the Shipper's Parcel Specifications and the
12 Shipper's service request. If the Shipper clicks the "Help" button 105, the System will
13 display help text to explain to the Shipper the appropriate possible actions.

14 [0195] Returning to FIG. 25, Shipping Weight can be input by clicking the Shipping
15 Weight pull down menu button 191b which will cause a display of commonly selected
16 weights, such as "Letter - 0.5 lbs" and weights from 1 to 150 lbs. Alternatively, in one
17 exemplary embodiment, the User inputs the weight of the package by placing the actual
18 package on a scale that is configured with the User's computer and with which the System is
19 programmed to interact as disclosed above.

20 [0196] The User is also asked to identify whether the item is irregular or requires non-
21 standard packaging 192. Regarding Loss Protection, the default is Basic Coverage 193. If
22 the User instead selects Declared Value 194, the User is required to enter a value 195 greater
23 than \$0.00 and less than or equal to \$50,000.00.

24 [0197] Once the User has entered the package specific information 191a-195, as described
25 above, the User can request the System to preview the shipping charges that will be presented
26 to a Buyer/Bidder. To do so, the User may either: 1) choose an example destination 196a and
27 uses the destination pull down menu button 196c to select a sample destination city 196b
28 from a list of cities; or 2) choose to enter an example zip code 197a by entering a sample zip
29 code 197b. Then the user clicks the Preview button 198 to display the sample charges. If a

1 sample destination city was selected from the pull down list of cities, once the User clicks the
2 Preview button 198, the System identifies the appropriate zip code for the selected city and
3 moves that zip code into the Destination Zip code field 197b.

4 [0198] FIG. 28 depicts an exemplary further supplemental Shipper Parcel Specification
5 Screen such as in a simplified Internet embodiment of the invention, which in the
6 embodiment depicted is titled the Service Options Screen. The Service Options Screen
7 provides for Shipper input of Service Option Selections (1076, 1077, 1078, 1083-1088) and
8 displays a Single Day Rate Graphic Array. The Service Options supported in the depicted
9 embodiment are: 1) Loss Protection (Declared Value) 1076; Delivery Notification 1077,
10 namely 2) E-Mail Delivery Notification 1083; 3) Verbal Delivery Confirmation 1085; and
11 other options 1078, namely 4) "Service must be guaranteed" 1086; 5) "Destination is a
12 Residence" 1087; and 6) "Signature not Required" 1088. Selection of an option on the screen
13 depicted in FIG. 28 is accomplished by the Shipper placing the cursor on the option selection
14 mechanism and clicking the Shipper's user input device.

15 [0199] With respect to the Loss Protection (Declared Value) Service Option, if the Shipper
16 selects the Declared Value Option 1081, the Shipper must enter a value 1082 of greater than
17 \$100.00, and equal to or less than \$50,000.00. The default for Loss Protection is "Basic
18 Coverage" 1080 which provides automatic coverage for the first \$100.00 of Declared Value
19 If the Declared Value option 1081 is selected and a value 1082 entered, the System will
20 update the Single Day Rate Graphic Array 1096 with changes for each individual Carrier's
21 rates, e.g., 1097.

22 [0200] It should be noted that the Carrier Rules described herein, such as in the case of the
23 defaults, threshold values, and the like concerning Loss Protection, are contained in the
24 Carrier Rules database (e.g., 1404a through 1404n as depicted in FIG. 38), and for special
25 cases, are programmed as part of the System. Carrier Rules vary from Carrier to Carrier;
26 Carrier Rules are subject to change. The Carrier Rules described herein are therefore not a
27 limitation of the invention.

28 [0201] With respect to the E-Mail Delivery Notification Option, two controls are provided -
29 a checkbox 1083 and an "E-Mail Others" button 1084. If the E-Mail Delivery Notification

1 Option checkbox 1083 is checked the rates, such as those displayed in the Single Day Rate
2 Graphic Array 1096, will be updated to reflect each Carrier's charges for the provision of E-
3 Mail Notification services. If Shipper clicks the "E-Mail Others" button 1084, the following
4 will occur: 1) If the checkbox 1083 has not already been checked, it will be checked by the
5 System; and 2) an "E-Mail Others" pop-up window will be displayed by the System as
6 depicted in FIG. 60 and described below.

7 [0202] With respect to the Verbal Delivery Confirmation Option, if the Verbal Delivery
8 Confirmation Option checkbox 1085 is checked, the rates, such as those displayed in the
9 Single Day Rate Graphic Array 1096, will be updated to reflect each Carrier's charges for the
10 provision of Verbal Delivery Confirmation services. If the Verbal Delivery Confirmation
11 Option checkbox 1085 is checked, the System will use the Shipper's Return Address Phone
12 and Name as supplied by the Shipper during Account setup (not shown), as the information to
13 be supplied to UPS.

14 [0203] With respect to the "Service must be guaranteed" Option, if the "Service must be
15 guaranteed" Option checkbox 1086 is checked, the rates and Carrier/Service cells, such as
16 those displayed in the Single Day Rate Graphic Array 1096, will be updated to remove any
17 Carrier/Service cell for which service is not guaranteed.

18 [0204] With respect to the "Destination is a Residence" Option, if the "Destination is a
19 Residence" Option checkbox 1087 is checked, the rates and Carrier/Service cells, such as
20 those displayed in the Single Day Rate Graphic Array 1096, will be updated to remove any
21 Carrier/Service cell which does not provide service to Residence Destinations.

22 [0205] With respect to the "Signature not Required" Option, in the embodiment depicted in
23 FIG. 28, if the "Signature not Required" Option checkbox 1088 is checked, no change will be
24 applied to the rate graphic. In the embodiment depicted in FIG. 28, the "Signature not
25 Required" Option is a FedEx only flag and does not effect any other Carrier or any Carrier
26 rate.

27 [0206] The Single Day Rate Graphic Array as displayed in FIG. 28 is similar to the Graphic
28 Array described below as depicted in FIG. 36A in that the Single Day Rate Graphic Array is
29 dynamically dimensioned and reflects the Carriers (1032-1 through 1032-7) that provide the

1 delivery service requested by the Shipper for a particular Subject Parcel. As with the Graphic
2 Array, the embodiment of the Single Day Rate Graphic Array depicted in FIG. 28 uses a
3 color-coded legend 1091 and color (e.g., 1140a, 1141a, 1142a) to distinguish the rates for
4 each Carrier (e.g., 1140b, 1141b, 1142b) from the rates for the other Carriers.

5 [0207] The Single Day Rate Graphic Array contains a number of elements. First, the
6 selected delivery date 1090 is displayed at the top of Single Day Rate Graphic Array. The
7 displayed date is bordered on the left 1098 and right 1099 with arrow buttons. If the Shipper
8 clicks the left arrow button 1098, the date will go back one valid delivery date. If the Shipper
9 clicks the right arrow button 1099, the date will move forward one valid delivery date. The
10 range of valid delivery dates is determined by the System according to the Expected Ship
11 Date (element 1060 as depicted in FIG. 36A).

12 [0208] Sorted, valid delivery times 1093-1 through 1093-5 for all valid dates are displayed
13 down the left side of the Single Day Rate Graphic Array. Above the delivery times are up
14 and down arrow buttons 1101a and 1101b respectively. If an up or down arrow button (1101a
15 and 1101b respectively) is pressed, the list of available times 1093-1 through 1093-5 will
16 scroll up or down appropriately, if and only if the list exceeds the Single Day Rate Graphic
17 Array display area 1096.

18 [0209] A Ship Location Type field 1066 and Ship Location drop down menu activator
19 1067, are displayed below the Single Day Rate Graphic Array and operate in a manner as
20 described in FIG. 36A. If the Shipper changes the Ship Location selection, the System will
21 update the Single Day Rate Graphic Array to reflect any rate changes or surcharges that result
22 from the change.

23 [0210] As with the Rates and Times Screen (described below as depicted in FIG. 36A), the
24 Single Day Rate Graphic Array is color coded by Carrier in a color-coding legend 1091 - that
25 is, a distinct color is visually depicted in a legend as corresponding to each respective Carrier.
26 Carrier cell entries, e.g., 1097, for each Carrier are presented in a color-coded display of the
27 available rate, by date and time.

28 [0211] As depicted in FIG. 28, the color for the Carrier identified as "Airborne" 1140b is
29 depicted in the color coding legend 1091 with a right-diagonal cross-hatch symbol 1140a.

1 Accordingly, each Carrier cell entry, e.g., 1097, contained within the Single Day Graphic
2 Array with a particular distinct color, in this case depicted with the right-diagonal cross-hatch
3 symbol 1140a, corresponds to a delivery of the Subject Parcel supported by the Carrier
4 “Airborne” 1140b.

5 [0212] Each Carrier cell entry, e.g., 1097, contains a graphic element, e.g., 1097a, which
6 contains what is known as “ALT text”. A Shipper viewing the Single Day Rate Graphic
7 Array online can place the PC’s cursor on the graphic element, e.g., 1097a of a particular
8 Carrier cell entry, e.g., 1097, to display a pop-up screen (not shown) that displays the ALT
9 text for that particular Carrier cell entry. The ALT text contains information about the
10 Carrier, as described in FIG. 36A, such as the full Carrier name and the full Carrier service
11 name. The contents of the ALT text described herein is exemplary and is not a limitation of
12 the invention.

13 [0213] Appearing in each of each of the color-coded Carrier cell entries is a monetary
14 value, e.g., 1097b, of the price that the corresponding Carrier would charge to deliver the
15 Subject Parcel according to the time and date specified. For example, as depicted in FIG. 28,
16 the Carrier cell entry 1097, depicted with the right-diagonal cross-hatch symbol 1140a,
17 contains the amount \$9.00 (1097b). Accordingly, the amount \$9.00 (1097b) is the price that
18 the Carrier Airborne would charge to deliver the Subject Parcel at the identified time of 12:00
19 p.m. 1093-3 on the identified date of Monday, September 28, 1999 1090.

20 [0214] Similarly, as depicted in FIG. 28, the color for the Carrier identified as “FedEx”
21 1141b is depicted in the color coding legend 1091 with a left-diagonal cross-hatch symbol
22 1141a. Accordingly, each Carrier cell entry contained within the Graphic Array with the left-
23 diagonal cross-hatch symbol, e.g., 1107, corresponds to a delivery of the Subject Parcel
24 supported by the Carrier “FedEx.”

25 [0215] Further, as depicted in FIG. 28, the color for the Carrier identified as “UPS” 1142b
26 is depicted in the color coding legend 1091 with a vertical cross-hatch symbol 1142a.
27 Accordingly, each Carrier cell entry contained within the Graphic Array with the vertical
28 cross-hatch symbol, e.g., 1108, corresponds to a delivery of the Subject Parcel supported by
29 the Carrier “UPS.”

1 [0216] In the embodiment of the Service Options Screen depicted in FIG. 28, the
2 navigational buttons operate much the same as has been previously described except that
3 clicking the “Back” button 117 will display the previous screen, which in the embodiment
4 depicted is the Rates and Times Screen (FIG. 36A); clicking the “Next” button 102 will
5 display the next screen, which in the embodiment depicted is the Summary Screen (FIG. 48).
6 The Shipper must select a Carrier cell entry before the System will display the Summary
7 Screen. To select a Carrier cell entry, the Shipper places the cursor over the entry and clicks
8 the user input device. In an alternative embodiment, the Shipper double clicks a Carrier cell
9 entry to select the entry. Clicking the Reset button 103 will clear all fields in the Service
10 Option Screen depicted in FIG. 28 and return the display of the Location and Package Screen
11 (as described above with regard to FIGS. 15 and 26).

12 [0217] Returning to FIG. 25, once the User is satisfied with the previewed charges, the User
13 can create a Seller’s link. To do so, the User must choose the type of Link, HTML 199 or
14 Web Address only 200, enter the Link Text 201 that will be displayed, and click the Go
15 button 202.

16 [0218] Once the User clicks on the “Go” button 202, the System generates an HTML
17 hyperlink and moves the HTML hyperlink in the “Link” box 203a. If the HTML hyperlink
18 text exceeds the space available on the Create a Seller’s Link Screen, the User can click on
19 the up and down scroll buttons, 203b1 and 203b2 respectively.

20 [0219] FIG. 30 depicts an exemplary alternative embodiment of the Create a Seller’s Link
21 screen. In this embodiment, the System collects the package specific information when the
22 Seller enters the System and then presents the screen as depicted in FIG. 30 to display the
23 generated hyperlink.

24 [0220] On the Seller’s Link Screen depicted in FIG. 30, an Affiliate’s Logo 215 is
25 displayed. The Affiliate’s Logo 215 represents the logo of an affiliated eCommerce/eAuction
26 provider. When Affiliate co-branding is desired, an affiliate identifier is appended to the end
27 of the URL that refers to the Sell It application as that URL is provided in the affiliate
28 Provider’s Web site. An affiliate identifier is an account number that begins with the prefix
29 “AFF”. When a Seller clicks on a logo or hyperlink for the System that has an affiliate

1 identifier, the affiliate identifier is sent to the System with the hyperlink. If the System
2 receives an affiliate identifier in a hyperlink, the System accesses the System database 22 as
3 depicted in FIG. 5, retrieves the affiliate's logo and color scheme, and uses the affiliate's
4 logo, page element specifications, and color scheme to alter page elements of the System
5 screens.

6 [0221] In one embodiment, the System generates an HTML hyperlink by executing a JAVA
7 script routine (in alternative embodiments, other scripts are used). The JAVA routine extracts
8 the Seller's package-specific information from the Create a Seller's Link HTML page (i.e.,
9 Weight, Irregular or Non-Standard Packaging, Loss Protection, Destination Zip code, Link
10 Type and Link Text) and integrates the information with a URL (Universal Resource Locator)
11 that points to the address at which a System web page exists, or a series of System web pages
12 exist, that will display shipping cost comparisons for a Buyer/Bidder. In one embodiment,
13 the URL information is hard coded in the web page. The hyperlink built by the System
14 contains data as well as an address. In an alternative embodiment, the URL is dynamically
15 generated.

16 [0222] In order to create the Link, the System places the appropriate HTML tags and text in
17 a sequence that can be rendered by a web browser. An example of a hypertext link, like the
18 one generated in FIGS. 25 and 29, that the "Create Link" application creates is depicted in
19 FIG. 31. Some of the text of the Link (a hyperlink) depicted in FIG. 31 is a template.
20 However, several components are customized according to the Seller's and the specific item's
21 information. For instance, the example hyperlink depicted in FIG. 31 contains a variable data
22 item named "K" 210-1 which is set equal to the account number 210-2 ("A6V1XZ" in this
23 case) of the Seller's account 210. The example hyperlink depicted in FIG. 31 also contains a
24 variable named "W" which is set equal to the weight in pounds of the package to be shipped
25 (in this case "10") 211; a variable named "V" set equal to the declared value for loss
26 protection of the package (in this case "0") 212; and a variable named "H" which is set equal
27 to an indicator, which if set to "1", the package has irregular or non-standard packaging, if set
28 to "0" (as in this case"), the package is regular with standard packaging 213.

29 [0223] After the System generates the HTML hyperlink, the Seller can copy the HTML

1 hyperlink text 203a as depicted in FIG. 30 using generally available text editing features such
2 as click, drag and copy. The Seller then returns to the Seller's web site or to the
3 eCommerce/eAuction Provider's from which the Seller entered the System and paste the Link
4 text in the Seller's eCommerce/eAuction item description.

5 [0224] The Buyer's/Bidder's experience is described in detail below. However, for
6 purposes of describing the Seller's Link, when the Buyer/Bidder clicks on the Seller's Link in
7 the Seller's web page, the Buyer's/Bidder's Web Browser will use the URL to locate the
8 System Web page that is addressed by the Link. The System will be presented with and
9 receive as input the information in the hypertext link, including the variables and their
10 respective contents as described above 210-213 in connection with FIG. 31.

11 [0225] With the Seller's account number 210, the System accesses the System database 22
12 as depicted in FIG. 5 and retrieves the following types of information about the Seller: 1)
13 Package origin address; 2) Carriers and services that the Seller has chosen to use; 3) Custom
14 and public carrier rates the Seller can use; 4) Additional handling charges that the Seller
15 wants to imposes; and 5) Payment methods the Seller will allow the buyer to use. This type
16 of information was collected by the System during the Seller's Registration process as was
17 described above (e.g., in connection with FIGS. 9-14, 16-25).

18 [0226] With the Seller's information as collected through the Registration process and with
19 the package specific information as provided by the hyperlink Seller's Link, the System, at
20 the address provided by the URL, is programmed to interact with the Buyer, as will be
21 described in detail below, to facilitate shipping of the package, payment information
22 collection, and depending upon the previously provided (during Seller registration)
23 instructions of the Seller, payment processing.

24 [0227] FIG. 32 depicts an alternative embodiment of a hyperlink generated by the System.
25 Instead of the hyperlink explicitly containing the Seller's account number 210 and package
26 specific information, e.g., 211-213, as depicted in FIG. 31, the hyperlink depicted in FIG. 32
27 provides a Package Identifier ("PID") 220. A PID hides Seller account information and
28 package specific information from the Buyer/Bidder by replacing the explicit embedded
29 information with a single string of facially meaningless characters. In an embodiment of the

1 System that generates a PID for each package/Seller's Link, every time a Seller creates a
2 URL with a PID, the System creates a new and unique PID. Without access to the iShip
3 database, there is no information in a PID from which to determine a Seller's information.
4 [0228] The System stores the PID 220 in a PID table in the System database 22 (such as
5 depicted in FIG. 5) and stores the Seller's account and package specific information, e.g.,
6 210-213 (such as depicted in FIG. 31) with the PID.

7 [0229] In another embodiment, the details associated with the Seller's account, such as the
8 Seller's various eCommerce and shipping preferences, are stored in detail with the PID 220.
9 Storing detailed information with a PID 220 provides for additional flexibility in that new
10 Seller information can be associated with the new PID while not influencing a previously
11 generated PID and its associated set of information.

12 [0230] FIGS. 33A and 33B represent a database schema diagram that depicts an exemplary
13 embodiment of tables in which data is stored by the System regarding a particular Seller
14 Account, and from which information is retrieved in order to begin the process of presenting
15 to the Buyer/Bidder a shipping cost multi-carrier, multi service comparison Graphic Display,
16 which itself will be discussed in more detail below.

17 [0231] As depicted in FIGS. 33A and 33B, the database schema 250 is comprised of an
18 Account User table 251 (comprising, e.g., 251-1, 251-2, 251-3, 251-4), a Users table 252
19 (comprising, e.g., 252-2, 252-2, 252-3, 252-4), an Account User Configuration table 253
20 (comprising, e.g., 253-1, 253-2, 253-3, 253-4), a Carrier Account table 254 (comprising e.g.,
21 254-1, 254-2, 254-3, 254-4, 254-5), an Account table 255 (comprising, e.g., 255-1, 255-2,
22 255-3, 255-4), an Account and Carrier Account table 256 (comprising, e.g., 256-1, 256-2,
23 256-3), an Address table 257 (comprising, e.g., 257-1, 257-2, 257-3, 257-4, 257-5, 257-6,
24 257-7), a Site Type table 258 (comprising, e.g. 258-1, 258-2, 258-3, 258-4), an Account and
25 Site Type table 259 (comprising, e.g., 259-1, 259-2), an Account and Site table 260
26 (comprising, e.g., 260-1, 260-2), and a Site table 270 (comprising 270-1, 270-2, 270-3). As
27 depicted in FIGS. 33A and 33B, the Account User table 251 comprises, e.g., an account
28 number ("AccountNo") 251-1, a user ID ("UserID") 251-2, an OID Address ("AddressOID")
29 251-3, a date of creation ("CreateDate") 251-4, etc. Users table 252 comprises a user ID

1 ("UserID") 252-1, a LogOnName 252-2, a Password 252-3, an active indicator ("Active")
2 252-4, etc. The Account User Configuration table 253 comprises, e.g., an account number
3 ("AccountNo") 253-1, a UserID 253-2, an Item 253-3, a Value 253-4, etc. The Carrier
4 Account table 254 comprises a Carrier Account ID 254-1, a Carrier Account Name 254-2, a
5 Billing Address OID 254-3, an Active indicator 254-4, a Commissioned indicator 154-4, etc.
6 The Account table 255 comprises, e.g., an Account Number 255-1, a Mailing Address OID
7 255-2, an Active indicator 255-3, Tracking Number information 255-4, etc. The Account and
8 Carrier Account table 256 comprises, e.g., an Account Number 256-1, a Carrier Account ID
9 256-2 and a Carrier ID 256-3. The Address table 257 comprises, e.g., an Address OID 257-1,
10 a Contact Name 257-2, an email address 257-3, a Company Name 257-4, an Address 257-5, a
11 City 257-6, a State 257-7, etc. The Site Type table 258 comprises, e.g., a Site Type ID 258-1,
12 a Site Type OID 258-2, a Description 258-3, a Name 258-4, etc. The Account and Site Type
13 table 259 comprises an Account Number 259-1 and a Site Type ID 259-2. The Account and
14 Site table 260 comprises, e.g., an Account Number 260-1 and a Site OID 260-2. The Site
15 table 270 comprises a SiteOID 270-1, an Active indicator 270-2, and an Address OID 270-3.
16 [0232] The Account table 255 holds, among other things, information about each Seller's
17 account. In preparing the multi-carrier shipping cost comparison Graphic Display, the System
18 accesses the Account table in order to determine whether the Account number 210-2
19 contained in the hyperlink text is a valid Account number 255-1 and in an Active state 255-3.
20 [0233] The Account User table 251 is used, among other things, to associate the Seller's
21 account information with the Seller's security and address information. An address pointer
22 251-3 into the Address table 257 is used 257-1 to retrieve the Seller's origin address.
23 [0234] The Account User Configuration table 253 contains the Seller's preference settings
24 (not shown) as specified by the Seller. These include Seller's choice of carriers, services,
25 payment options, type of drop-off / pickup option, and any handling charges the Seller wishes
26 to impose on the buyer.
27 [0235] The Address table 257 holds all the addresses that are used in System applications.
28 In addition to normal mailing address information, other items stored in this database table
29 include the Seller's e-mail address and phone numbers.

1 [0236] The Carrier Account table 254 holds the carrier account information that the System
2 uses when a Seller ships a package. As well, this table 254 contains information for
3 generating each Seller's rates for each carrier.

4 [0237] The Account and Carrier Account table 256 ties the carrier accounts 254-1 from the
5 carrier Account table 254 to the Carrier Accounts 256-2 with which the Seller has specified as
6 a preferred Carrier to a particular Seller's account 256-1.

7 [0238] The Site Table 270 contains information about drop off and pickup site locations.
8 The Site Type table 258 contains information about each type of site.

9 [0239] The Account and Site table 260 relates a particular Seller Account 260-1 to a
10 particular site pointer 260-2 which in turn points to a particular site record 270-1 in the Site
11 table 270.

12 [0240] The Account and Site Type table 259 relates a particular Account 259-1 to a
13 particular site type 259-2 which in turn points to a particular site type record 258-1.

14 [0241] In one embodiment, once the Seller has decided upon the Seller's preferred options,
15 the information in the Site Type, Account and Site Type, Account and Site and Site tables
16 258-270 are stored in the Account User Configuration table 253.

17 [0242] Most eCommerce web sites and eAuction sites allow the Seller to generate a custom
18 Seller's web page for each item being sold. Typically, the Seller's web page utilizes HTML
19 for the layout, and descriptions and pictures of the item sold or auctioned. During the process
20 of establishing an eCommerce/eAuction web page, the Seller utilizes the System to register
21 for the System's shipping management services, to enter the Seller's preferences as described
22 above, and to enter parameters such as, for example, the weight and packaging, loss
23 protection and value of the package, as described above that describe the particular item the
24 Seller is selling/auctioning. The Seller then uses the Create a Seller's Link function of the
25 System to create a hyperlink. The Seller then uses customary edit controls to copy the
26 hyperlink and paste the hyperlink into the description of the item to be sold at the Seller's web
27 site. The result is an HTML hyperlink to view the shipping charges from the auction item
28 description field, an exemplary embodiment of which is depicted in FIG. 34.

29 [0243] As depicted in FIG. 34, the exemplary item bidding requirements and circumstances

1 301 are described in the Seller's auction web site page. A description of the item available
2 for bidding is provided 302. The Seller has used the System to copy the hyperlink 203a
3 created by the system into the description 302 of the item. After returning to the Seller's
4 auction web site page describing the particular item, the Seller used customary edit controls to
5 paste the hyperlink into the description 302 of the item 303. The Seller's web site page 53 is
6 depicted in FIG. 10C.

7

8 **D. THE BUYER'S EXPERIENCE IN AN ECOMMERCE EMBODIMENT**

9 [0244] In an eCommerce embodiment of the present invention, the Buyer/Bidder enters the
10 Seller's eCommerce/eAuction web site page, such as the one depicted in FIG. 34, and reviews
11 the Seller's description of the item to be sold/auctioned. If the Buyer/Bidder is interested in
12 the item, the Buyer/Bidder may click on the System hyperlink 303 for that Seller's item
13 shipping charges.

14 [0245] If the Buyer (80, FIG. 10C) clicks on the System hyperlink 303, as depicted in FIG.
15 10C, the Buyer/Bidder enters the System at the URL address supplied by the hyperlink. FIG.
16 35 is a graphic representation of an exemplary Buyer shipping rating information collection
17 screen that the Buyer would see upon entry into the System. As depicted in FIG. 35, the
18 System displays a Buyer data collection screen 55 (in FIG. 10C) to the Buyer, instructing the
19 Buyer to enter the Buyer's zip code and other options, and to click on the Get Rates button
20 317 to get a comparison of rates 310. The Buyer enters the deliver-to zip code 311, identifies
21 whether the delivery will be made to a business address 312 or a residence 313, and whether
22 yes 314 or no 315 the Buyer wants the selected Carrier/service to guarantee a delivery time.
23 The System instructs the Buyer to click the "Back" button on the Buyer's web browser to
24 return to the Seller's item web site page 316.

25 [0246] Once the Buyer has supplied the necessary information, if the Buyer clicks the Get
26 Rates button 317, the System validates the information supplied by the Buyer and then
27 combines the information supplied by the Buyer with the information set for the Seller during
28 the Seller's registration/eCommerce registration and calculates and displays a multi-carrier,
29 multi-service rate and time shipping cost comparison Graphic Array 56 (as depicted in FIG.

1 10C).

2 [0247] An exemplary embodiment of a multi-carrier, multi-service rate and time shipping
3 cost comparison Graphic Array in an exemplary simplified Internet embodiment of the
4 invention is depicted in FIG. 36A.

5

6 a) THE GRAPHIC ARRAY DISPLAY

7 [0248] FIG. 36A depicts an exemplary Dynamically Dimensioned Multi-Carrier, Multi-
8 Service Graphic Array online display as part of an exemplary supplemental Shipper Parcel
9 Specification Input Screen. FIG. 36A depicts a Graphic Array for an exemplary simplified
10 Internet embodiment. In the embodiment of the Graphic Array depicted in FIG. 36A, the
11 particular screen is titled the Rates and Times Screen.

12 [0249] As depicted in FIG. 36A, the exemplary Graphic Array contains the following
13 information and display elements: 1) valid delivery dates 1063 (1063-1 through 1063-3)
14 across the top of the graphic display for the selected Ship Date; 2) sorted, valid delivery times
15 1064 (1064-1 through 1064-6) for all valid dates down the left side of the graphic display; and
16 3) color coded by Carrier, Carrier cell entries, e.g., 1065, for each available rate, by date and
17 time.

18 [0250] In the exemplary embodiment depicted in FIG. 36A the Graphic Array comprises an
19 array of intersecting rows and columns. Each column corresponds to a day and date of parcel
20 delivery. In FIG. 36A, the days and dates of delivery shown are "TUE 28 SEP 99" (1063-1),
21 "WED 29 SEP 99" (1063-2) and "THU 30 SEP 99" (1063-3). As depicted in FIG. 36A,
22 space for other columns (1063-4 through 1063-7) are available for display; in the case of the
23 example depicted in FIG. 36A however, no dates are displayed in those columns.

24 [0251] Each row of the Graphic Array corresponds to a time of delivery. In FIG. 36A, the
25 times of delivery are shown as "8:00 AM" (1064-1), "10:30 AM" (1064-2), "12:00 PM"
26 (1064-3), "3:00 PM" (1064-4), "4:30 PM" (1064-5), and "5:00 PM" (1064-6).

27 [0252] At the intersection of each row (1064-1 through 1064-6) and column (1063-1
28 through 1063-7) of the Graphic Array is a "cell." In FIG. 36A, cells will be referred to by the
29 element 1071, and by the intersecting row (1 through 6) and column (1 through 7) the

1 intersection of which forms the space for each cell (1071-1-1, 1071-1-2, . . . 1071-6-7). Some
2 of the cells depicted in FIG. 36A are empty, e.g., 1071-5-1, 1071-6-1, 1071-6-3, 1071-6-4.
3 Empty cells represent the circumstances that none of the Carriers supported by the System
4 (the “supported Carriers”) support delivery of the Subject Parcel for the time and date for
5 which that cell represents the intersection.

6 [0253] Some cells depicted in FIG. 36A have one or more cell entries. In FIG. 36A, each
7 cell entry represents a particular Carrier. Each Carrier cell entry is color coded with a unique
8 color, the unique color corresponding to a particular Carrier as is discussed in more detail
9 below; each Carrier cell entry contains a graphic element, e.g., 1147a, and a monetary
10 amount, e.g., 1147b, which represents the price for which the corresponding Carrier would
11 deliver the subject parcel. For instance, cell 1071-1-1 contains a single Carrier cell entry
12 1148. Cell 1071-3-1 contains two Carrier cell entries 1065 and 1149.

13 [0254] A color-coding legend 1062 is displayed on the Screen to identify by a name
14 (1140b, 1141b, 1142b, and 1143b) and a color-coding symbol (1140a, 1141a, 1142a, and
15 1143a), each of the supported Carriers (e.g., 1140, 1141, 1142, 1143) that provide the service
16 according to the particular Shipper’s Parcel Specifications for the particular Subject Parcel.

17 [0255] For purposes of this application, unique colors are depicted with graphic symbols.
18 For example, a right-diagonal hash mark symbol 1140a is used herein to represent the color
19 red; a left-diagonal hash mark symbol 1141a is used herein to represent the color purple; a
20 vertical hash mark symbol 1142a is used to represent the color amber; and a horizontal hash
21 mark symbol 1143a is used to represent the color blue. The particular hash mark symbols
22 used herein and the colors mentioned herein are exemplary and are not a limitation of the
23 invention.

24 [0256] Each cell of the Graphic Array that is not empty contains one or more color-coded
25 Carrier cell entries. For example, in FIG. 36A, cell 1071-3-1 contains two Carrier cell entries,
26 1065 and 1149. Carrier cell entry 1065 is color-coded with the right-diagonal hash mark
27 symbol (representing the color red) which, according to the color-coding legend 1062,
28 corresponds 1140a with the Carrier identified as “Airborne” 1140b. Carrier cell entry 1149 is
29 color coded with the horizontal hash mark symbol (representing the color purple) which,

1 according to the color-coding legend 1062, corresponds 1143a with the Carrier identified as
2 "USPS" 1143b.

3 [0257] Each Carrier cell entry, e.g., 1065, contains a graphic element, e.g., 1065a, which
4 contains what is known as "ALT text". As depicted in FIG. 36A, a Shipper viewing the
5 Graphic Array online can place the PC's cursor on the graphic element, e.g., 1065a of a
6 particular Carrier cell entry, e.g., 1065, to display a pop-up screen 1069 that displays the ALT
7 text for that particular Carrier cell entry. In some embodiments, the ALT text will be
8 displayed by merely placing the cursor over the graphic element for a particular Carrier cell
9 entry and leaving the cursor in that position for a certain time interval. In alternative
10 embodiments, the Shipper must click on the graphic element for a particular Carrier cell entry
11 in order to display the ALT text. In the exemplary embodiment depicted in FIG. 36A, the
12 displayed ALT text, e.g., the text displayed in pop-up screen 1069, contains the full Carrier
13 name (in the depicted case, "Airborne Express") and the full Carrier service name (in the
14 depicted case, "Express Overnight Service") for the Carrier 1140b (in this case, Airborne) to
15 which that Carrier cell entry corresponds.

16 [0258] As depicted in FIG. 36A, the color for the Carrier identified as "Airborne" 1140b is
17 depicted in the color coding legend 1062 with a right-diagonal cross-hatch symbol 1140a.
18 Accordingly, each Carrier cell entry contained within the Graphic Array with the right-
19 diagonal cross-hatch symbol, e.g., 1065, corresponds to a delivery of the Subject Parcel
20 supported by the Carrier "Airborne." Appearing in each of the color-coded Carrier cell
21 entries, e.g., 1065 is a graphic element, e.g., 1065a, and a monetary value, e.g., 1065b. The
22 monetary value, e.g., 1065b corresponds to the price that the corresponding Carrier would
23 charge to deliver the Subject Parcel according to the time 1064-3 and date 1063-1 specified
24 according to the row and column of which the intersection (which, in the case described is
25 cell 1071-3-1) contains the Carrier cell entry 1065. For example, as depicted in FIG. 36A, the
26 Carrier cell entry 1065, depicted with the right-diagonal cross-hatch symbol, contains the
27 monetary amount "\$9.00." Accordingly, the amount \$9.00 is the price that the Carrier
28 Airborne would charge to deliver the Subject Parcel at the identified time of 12:00 p.m. 1064-
29 3 on the identified date of Tuesday, September 28, 1999 1063-1.

1 [0259] Similarly, as depicted in FIG. 36A, the color for the Carrier identified as “FedEx”
2 1141b is depicted in the color coding legend 1062 with a left-diagonal cross-hatch symbol
3 1141a. Accordingly, each Carrier cell entry contained within the Graphic Array with the left-
4 diagonal cross-hatch symbol, e.g., 1147, corresponds to a delivery of the Subject Parcel
5 supported by the Carrier “FedEx.”

6 [0260] Further, as depicted in FIG. 36A, the color for the Carrier identified as “UPS” is
7 depicted in the color coding legend 1062 with a vertical cross-hatch symbol 1142.
8 Accordingly, each Carrier cell entry contained within the Graphic Array with the vertical
9 cross-hatch symbol, e.g., 1148, corresponds to a delivery of the Subject Parcel supported by
10 the Carrier “UPS.”

11 [0261] Similarly, as depicted in FIG. 36A, the color for the Carrier identified as “USPS” is
12 depicted in the color coding legend 1062 with a horizontal cross-hatch symbol 1143.
13 Accordingly, each Carrier cell entry contained within the Graphic Array with the horizontal
14 cross-hatch symbol, e.g., 1149, corresponds to a delivery of the Subject Parcel supported by
15 the Carrier “UPS.”

16 [0262] In the embodiment of the Graphic Array depicted in FIG. 36A, the Graphic Array is
17 dynamically dimensioned. For instance, only the dates and days (1063-1 through 1063-3) for
18 which delivery that conforms to the particular Shipper’s Parcel Specifications for the
19 particular Subject Parcel are displayed across the top of the graphic. For example, for the
20 date Tuesday, September 28, 1999 (1063-1), at the time 5:00 p.m. (1064-6), no Carrier
21 supports delivery of the Subject Parcel.

22 [0263] Further, as depicted in FIG. 36A, only the times (1064-1 through 1064-6) during
23 which at least one of the Carrier/Services identified as supporting the delivery are displayed
24 along the viewer’s left side of the Dynamically Dimensioned Multi-Carrier Graphic Array
25 online display.

26 [0264] Still further, as depicted in FIG. 36A, a Carrier cell entry, e.g., 1065, is displayed for
27 each of, but only for each of, the Carriers/Services that support delivery for a particular day
28 and time in the cell of the Graphic Array that represents delivery on a particular day and at a
29 particular time. When the circumstances require, the System displays one or more Carrier

1 cell entries in a single cell. For instance, cell 1071-3-1 contains two entries, 1065 and 1149;
2 whereas cell 1071-1-1 contains only a single cell. Accordingly, as depicted in FIG. 36A, the
3 cell size expands vertically to accommodate multiple Carrier cell entries.

4 [0265] In the exemplary embodiment depicted in FIG. 36A, the color-coding legend 1062
5 for each of the Carriers/Services represented in the Graphic Array is displayed with color-
6 coding graphic elements (1140a through 1143a) and identification labels (1140b through
7 1143b) for each relevant Carrier/Service along the viewer's right side of the rating and timing
8 graphic. Alternatively, instead of the printed name, the logo for the particular Carrier/Service
9 can be displayed. As another alternative, the Carrier/Service logo can be displayed in color in
10 the color-coding legend 1062.

11 [0266] The particular arrangement of the color legend 1062 depicted in FIG. 36A and the
12 particular colors used in the color legend depicted therein are exemplary and are not a
13 limitation of the invention. In an alternative embodiment, instead of using color, other
14 visually distinctive methods are used to differentiate between different Carriers/Services. For
15 instance, other visually distinctive methods of Carrier/Service differentiation include but are
16 not limited to: three-dimensional texture effects, other three-dimensional effects, two-
17 dimensional markings (for instance, dots, cross-hatching, and the like), lighting effects,
18 graphic symbols (for instance, the logos of the Carriers/Services) and any combination of the
19 aforementioned features with color.

20 [0267] In the embodiment of the Graphic Array depicted in FIG. 36A, the exemplary
21 Graphic Array is depicted as horizontally wide enough to accommodate seven delivery days
22 (1063-1 through 1063-7) within a particular delivery timespan. The depiction in FIG. 36A of
23 the Graphic Array as a fixed size accommodating up to seven delivery days is exemplary and
24 is not a limitation of the invention. In alternative embodiments, the Graphic Array online
25 display collapses or expands in total size to reflect the actual number of rows and columns
26 that need to be present in order to display the Carrier cell entries for the Carriers/Services that
27 support delivery of the Subject Parcel according to the Shipper's Parcel Specifications.

28 [0268] The arrangement as depicted in FIG. 36A of the parcel delivery days and dates
29 (1063-1 through 1063-7) across the top and the parcel delivery times (1064-1 through 1064-6)

1 along the left side of the Graphic Array is exemplary and is not a limitation of the invention.
2 In one alternative embodiment, the parcel delivery days and dates are displayed across the
3 bottom, and the parcel delivery times are displayed on the viewer's right side, of the Graphic
4 Array. In other alternative embodiments, the parcel delivery days are arranged on one of the
5 two sides of the Graphic Array and the parcel delivery times are arranged along the top or the
6 bottom of the Graphic Array. In such an alternative embodiment, the cells of the Graphic
7 Array are expandable horizontally to accommodate the appropriate number of relevant
8 Carriers/Services.

9 [0269] As depicted in FIG. 36A, the Shipper is asked to input the Expected Ship Date 1060.
10 In the exemplary embodiment depicted, a drop down menu activation mechanism 1061
11 provides the Shipper the ability to activate a pull down menu (not shown) of seven entries
12 beginning with the current date and includes the six days immediately following the current
13 date. The format used is "M/D/YY - Day name". "Today" and "Tomorrow" are displayed
14 appropriately. The number of entries provided by the selection mechanism, the format of the
15 Expected Ship Date, and other features described herein are exemplary and are not a
16 limitation of the invention.

17 [0270] In the exemplary embodiment depicted in FIG. 36A, once the Shipper selects the
18 Expected Ship Date, the System uses the Expected Ship date and the other information
19 provided by the Shipper, as in the screens depicted in FIGS. 15 and 26 described above, to
20 access the Carrier Rules, apply the Carrier Rules, and prepare the Graphic Array containing
21 the delivery prices and delivery times for the Subject Parcel according to the Shipper's Parcel
22 Specifications. The System will then generate the signals necessary to display the Graphic
23 Array and cause the Graphic Array to be displayed on the Shipper's PC.

24 [0271] Once the Graphic Array is displayed, the Shipper can change previously input
25 information and the System will automatically regenerate the Graphic Array with the delivery
26 rates and delivery times that have been updated to reflect the new information. For instance,
27 if the Shipper selects a new shipping date, the System will regenerate the Graphic Array with
28 the appropriate new rates and times. The logic for regenerating the Graphic Array is
29 described in more detail below.

1 [0272] In the exemplary embodiment depicted in FIG. 36A, a Ship Location Type drop
2 down menu activator 1067 is located below the Graphic Array. The particular location of the
3 Ship Location Type selection mechanism as described herein is exemplary and is not a
4 limitation of the invention. The list of locations is the same as the Shipping Location Type
5 drop down menu described above in the description of FIGS. 15 and 26. If the Shipping
6 Location class is a "ship center", a "Find Location" button 1068 is displayed next to the drop
7 down menu. In order to open the Drop Off Locator in a pop-up window, the Shipper places
8 the Shipper's PC cursor on the "Find Location" button 1068 and clicking the Shipper's user
9 input device. The Origin Zip Code and Ship Location type values supplied by the Shipper are
10 used as parameters for the Drop Off Locator to locate a list possible Drop Off Location
11 choices. The Shipper can select a Drop Off Location from the Drop Off Locator menu. The
12 system dynamically responds to changes by the Shipper to Origin Zip Code and Ship
13 Location type to present choices of Drop Off Location choices.

14 [0273] Navigational buttons appear at the bottom of the Rates and Times Screen depicted in
15 FIG. 36A. Clicking the "Back" button 117 will return the Shipper to the previously displayed
16 screen, which in the embodiment depicted is the Location and Package Screen as depicted in
17 FIGS. 15 and 26. Clicking the "Next" button 102 will cause the next screen, which in the
18 embodiment depicted is the Service Option Screen (FIG. 28), to be displayed but only if the
19 Shipper has selected a particular Carrier cell entry. For example, if the Shipper click on a
20 particular Carrier cell entry such as 1065, the System will allow the Shipper to then click on
21 the "Next" button 102 and proceed to the Service Option Screen as depicted in FIG. 28.

22 [0274] If a user returns to the Rates and Times Screen (FIG. 36A) from the Service Option
23 Screen (FIG. 28), any Service Options selected by the Shipper from the Service Option
24 Screen (FIG. 28) will effect the displayed rates and will be displayed (not shown) as
25 abbreviations below the Shipping Location field 1066.

26 [0275] The System in an exemplary eCommerce embodiment such as the one described
27 here creates a multi-carrier, multi-service, shipping cost comparison Graphic Array in much
28 the same way as is disclosed above with regard to the creation of the Graphic Array in an
29 exemplary simplified Internet embodiment. The difference is that in an eCommerce

1 embodiment, instead of collecting only Shipper input, the System collects origination data
2 including origin zip code, subject parcel data, and Carrier/Service filtering data from the
3 Seller, and then completes the Parcel Specifications for the subject parcel by collecting input
4 from the Buyer, including destination zip code.

5 [0276] Using the subject parcel's Parcel Specifications, the System is programmed to
6 access databases containing information about each supported Carrier. Each supported
7 Carrier has a unique rating schedule, delivery and pickup rules and schedules, and
8 certification requirements (the "Carrier Rules"). The System is further programmed to apply
9 each supported Carrier's Rules to each Shipper's Parcel Specifications for the corresponding
10 Subject Parcel. The System calculates the Shipping Charges based on zip-to-zip pricing
11 where the Seller has provided the origin zip code and the Buyer has provided the destination
12 zip code.

13 [0277] In an eCommerce embodiment, if the Seller selected as the Seller's preference,
14 "Item cost includes shipping charges" (170, FIG. 21), then the rates displayed will be
15 "FREE". If the Seller selected as the Seller's preference, "Buyer pays actual shipping
16 charges" (171, FIG. 21), then the rates displayed will be the total shipping charge as
17 calculated according to each Carrier's rules for each Service available according to the
18 Seller's expressed preferences. If the Seller selected as the Seller's preference, "Buyer pays
19 shipping and additional charges" (172, FIG. 21), then the System will calculate and display
20 rates that are the sum of: 1) the shipping rate for the applicable service according to each
21 Carrier's rules; 2) If the Seller checked "Add Percentage of Shipping Cost" (173, FIG. 21),
22 the product of the percentage entered in the Percentage of Shipping Cost field (174, FIG. 21)
23 and the total shipping rate calculated according to the Carrier's rules; 2) if the Seller checked
24 "Add Fixed Handling Charge" (175, FIG. 21), the dollar value entered in the Fixed Handling
25 Amount field (176, FIG. 21); and 4) if the Seller indicated "Add System Service Fee" (177,
26 FIG. 21), then the System Service Fee amount as indicated in the System database 22.

27 [0278] The Dynamically Dimensioned Multi-Carrier, Multi-Service Graphic Array online
28 display presents only rating and delivery timing information for the Carriers that offer
29 shipping of the particular Subject Parcel according to the particular Shipper's Parcel

1 Specifications and which conform with the Seller's Carrier/Service preferences as selected
2 according to the available options as described above regarding e.g., FIGS. 19 and 20.

3 [0279] FIG. 36F is a graphic representation of an alternative exemplary Dynamically
4 Dimensioned Multi-Carrier, Multi-Service Graphic Array online display as a Preview Rates
5 Screen (also referred to in some embodiments as a Rates and Times Screen) in an alternative
6 exemplary embodiment of the invention. The Graphic Array format of the Preview Rates
7 Screen depicted in FIG. 36F is sortable by price (i.e.,cheapest first), by delivery time (i.e.,
8 fastest is first), or preferred carrier, as governed by the enterprise and User preferences. The
9 Preview Rates Screen provides the User with the capability to optimize the Rates 5308
10 according to the Best Price 5136, or the Fastest Delivery 5135.

11 [0280] The exemplary Preview Rates Screen depicted in FIG. 36F depicts an array of dates
12 for delivery 5303-5305, multiple Carriers, e.g., 5128 (UPS), 5310 (FedEx), and 5311
13 (Airborne Express). If the Carriers that provide Services to ship the package according to the
14 User's specifications provide such services on more days than space exists on a single screen
15 display of the Rate Grid, left and right scroll buttons (not shown) are provided.

16 [0281] The exemplary Preview Rates Screen depicted in FIG. 36F is expandable for each
17 Carrier to display multiple Services for that Carrier, e.g., 5300 for UPS. The Services for a
18 Carrier can be displayed by the User by clicking a scroll down button, e.g., 5129 for UPS.
19 Each listed Service for the Carrier identifies the time for delivery, e.g, 5306. When the
20 Preview Rates Screen is displayed, the Carrier for which the User has specified a preference
21 (if such a preference has been specified) is displayed in the expanded mode, such as is
22 depicted in FIG. 36F for UPS so that all Services supporting shipment of the subject parcel
23 according to the User's specifications are displayed 5300; Carriers for which no preference
24 has been indicated are displayed in contracted mode, such as is the case for Fed Ex 5310,
25 Airborne Express 5311 and UPS 5128.

26 [0282] In the embodiment depicted in FIG. 36F, only the Carriers and Services that support
27 shipment of the subject parcel according to the User's specifications are displayed. In one
28 embodiment of the invention, the User can limit the default display of Carrier and Service
29 comparison to certain Carriers and certain Services. In one such embodiment of the

1 invention, a Show All button (not shown) is provided. Clicking the Show All button causes
2 the System to display all Carriers, Services, and Days of Delivery that support shipment of
3 the subject parcel according to the User's specifications, even if the User has previously
4 limited the available Carriers, Services and Days of Delivery.

5 [0283] A price is displayed in an Array cell, e.g., 5307, 5302, for Carrier/Service that
6 supports delivery of the subject parcel on the specified day of delivery 5303-5305. According
7 to the User's Optimization Selection 5135-5136, an Optimizer icon 5301 is displayed in the
8 particular Graphic Array cell entry that reflects the optimal Carrier/Service.

9 [0284] As was described above, each Carrier is represented in the Graphic Array/Rate Grid
10 by a different color. In the embodiment of the Rate Grid depicted in FIG. 36F, the optimally
11 rated shipping entry for each Carrier is highlighted in the color for that Carrier; all other
12 entries for that Carrier are in grey. The presence or absence of Carriers in the Graphic Array
13 display is driven by User-specified preferences, if any, and by service choices the user has
14 made (for example, by choosing a billing option that only certain Carriers support).

15 [0285] The rates calculated and displayed in the Graphic Array are customizable. Some
16 Users may wish to see the iShip System transaction charge included in the rate quote. In one
17 embodiment of the invention, a Rating button is provided on the same screen on which the
18 Graphic Array is displayed, with which the User can toggle the rates displayed in the Graphic
19 Array back and forth between the actual shipping rates (including all discounts and fees) and
20 the rate that the Carrier charges for shipping.

21

b) GENERATION OF THE GRAPHIC ARRAY DISPLAY

23 [0286] To develop the rates for display in a Graphic Rates Comparison Array such as the
24 ones depicted in FIGS. 36A and 36F, the System rating component is instantiated in the
25 server-side script. The rating component's rate information method is invoked with the rate
26 parameters embedded in the URL. Based on Carriers' business rules, the rates and their
27 service option charges for all Carriers/Services are calculated from each respective Carrier's
28 zone data, service/delivery time data and rate data.

1 [0287] The System keeps the Carrier data up-to-date in the System database 22. The
2 application does not use any carriers' Application Program Interface (API) functions to get the
3 rate information. All of carrier rate data is stored in the System database 22 and all business
4 rules to calculate the rates are implemented within the System.

5 [0288] FIGS. 36B through 36E are high level data retrieval and logic flow diagrams
6 depicting the data and high level logic that the system uses to calculate a shipping rate. As
7 depicted in FIG. 36B, the following shipping information is used to calculate a shipping rate:
8 Origin postal code, Destination postal code, Weight, Packaging, Drop off / Pickup, Country
9 code 3001. For each Carrier 3002, the rating component of the System uses the origin and
10 destination postal codes 3003. The rating component of the System obtains 3003 the zone id
11 from the zone table 3008 and gathers 3004 the time for deliveries for all available services
12 from the service delivery time table 3009. From the rate table 3010, the rating component
13 obtains services charges for the zone id, packaging type and weight 3005. For each service,
14 the rating component gathers all possible service options charges 3006. After gathering
15 necessary information, the rating component returns an array of rate information 3007. Each
16 element in the array represents a Carrier/Service and consists of service charge, service option
17 charges, and delivery times.

18 [0289] The System calculates the rates according to the following overview logic as
19 depicted in FIGS. 36C-36D. As depicted in FIGS. 36C through 36D, the System retrieves all
20 rate IDs (published, net, and retail) by joining the following database tables on the System's
21 AccountNo: AccountAndCarrierAcnt; CarrierAccount; RateDefinition 3020.

22 [0290] As depicted in FIGS. 36C through 36D, the System then determines the billing rules
23 for all of the Carrier/Service combinations and their service options by joining the following
24 tables on CarrierID, ServiceID, and ServiceOptionID: BillingOption;
25 BillingOptionAndService; BillingOptionAndServiceOption 3021.

26 [0291] As depicted in FIGS. 36C through 36D, for each carrier 3022, the System performs
27 the following procedures: 1) determine if the particular carrier supports the given billing
28 option based on step 2, 3026. If not, continue with the next carrier 3027; 2) Apply carrier

1 business rules, including: a) Calculate dimensional weight 3023; b) Determine billable weight
2 3024: actual weight, dimensional weight, oversize weight or letter weight; c) Validate
3 package weight and dimensions 3025; (If the rate input violates carrier business rules 3026,
4 continue to next carrier 3027); 3) Determine the zone ID from CarrierZone table for the given
5 origin/destination postal codes 3028; 4) Determine service delivery times 3029 (including
6 Saturday/Sunday delivery times) by joining the following tables on destination postal code: a)
7 CarrierDeliveryArea; b) CarrierServiceDelTime; 5) Determine all service charges from
8 CarrierRate table by RateID, ZoneID, ServiceID and Weight 3030; 6) Determine the service
9 option charges for each Carrier/Service 3031 by joining the following tables on CarrierID and
10 ServiceID: ServiceOption; ServiceOptionAttribute ServiceAndServiceOption; and 7) Apply
11 billing options to service option charges 3032 (different service option charges could be billed
12 to different parties for various billing options).

13 [0292] As depicted in FIG. 36E, the expected delivery times for each Carrier/Service
14 returned in the rate information determine the placement of the rate grid for the particular
15 Carrier/Service cell: the delivery date determines the columns 3040 while the delivery time
16 resolves the rows 3041. In the event that multiple rate entries collide (yes to test 3042), the
17 alphabetical order of the particular Carrier's name is further used to determine the Graphic
18 Array entry order within the same date and time bucket 3043. If there is no collision or once a
19 collision is resolved 3043, the same Carrier/Service can be placed in a second time slot in the
20 grid under Saturday or Sunday column 3045 if the Saturday or Sunday delivery is applicable
21 to the particular Carrier/Service 3044. If Saturday or Sunday delivery does not apply (no to
22 test 3044), or once a Saturday/Sunday time slot is indicated 3045, the System returns 3046.

23 [0293] In an eCommerce embodiment of the invention, a Shipper/Seller can preview a
24 shipping rate comparison Graphic Array prior to copying the System-created Link, e.g., 203a
25 as depicted in FIG. 25, for the Seller's eCommerce site. To preview the Graphic Array
26 comparison of shipping costs, the Seller clicks on the Preview button 198, such as is depicted
27 in FIG. 25. FIGS. 37A and 37B represent a System interactivity data and logic flow diagram
28 depicting an exemplary embodiment of the Create Link and the Buyer's Preview Shipping
29 Rates functionality in an eCommerce embodiment of the present invention. FIGS. 37A and

1 37B depict the interactivity between the Seller's 8-1 and Buyer's 8-2 client computers and the
2 System's server computers 20a-21z regarding this functionality. Also depicted are the data
3 accesses to the System database 22. An arrow 230 extending from the top of the diagram and
4 pointing down towards the bottom of the figure graphically represents the passage of time.

5 [0294] As depicted in FIGS. 37A and 37B, the Seller, using the Seller's computer 8-1,
6 clicks on the Create a Seller's Link selection option 331 notifying the System servers, e.g.,
7 21a-21z, to generate a display of the Create a Seller's Link screen 332 for display on the
8 display monitor of the Seller's computer 8-1. In one embodiment, the Servers 21a-21z send
9 332 the necessary information and instructions to build the hyperlink to the Seller's computer
10 8-1. The Seller enters the link text and clicks the go button and the Seller's computer 8-1
11 creates the Link 333. The Seller then copies the link, returns to the Seller's web page, and
12 pastes the link 334 in the description of the item to be sold at the eCommerce/eAuction
13 Provider's web site 345.

14 [0295] The Buyer, using the Buyer's computer 8-2, enters the Seller's web page 335 at the
15 eCommerce/eAuction Provider's web site 345. The Seller's web page at the
16 eCommerce/eAuction Provider's web site 345 displays the item description with the
17 hyperlink to the System 336 to the Buyer's computer 8-2. The Buyer clicks on the hyperlink
18 337, causing the System's servers 20a-20z to access 338 the System database 22 to retrieve
19 339 the Seller's account and eCommerce shipping preference information. The System
20 servers 21a-21z send a screen to the Buyer's computer 8-2 requesting delivery destination
21 information 340. The Buyer at the Buyer's computer 8-2 enters the delivery destination
22 information and clicks on the Get Rates button 341 which signals the System Servers 20a-21z
23 to prepare the multi-carrier, multi-service Graphic Array. The System Servers 20a-20n access
24 342 the System data base 22 and retrieve 343 the Seller's preferences and account
25 information. The System Servers 21a-21z calculate the rates and prepare the Graphic Array
26 344 for display on the display monitor of the Buyer's computer 8-2.

27 [0296] Whether or not the Buyer/Bidder (sometimes simply referred to herein as the Buyer)
28 uses the hyperlink 303 to preview the shipping charges, if the Buyer buys (or is the high

1 bidder), the Seller is provided with the Buyer's (or high bidder's) email address and name 54
2 (as depicted in FIG. 10C) either directly or by the sponsoring Provider. At that point, the
3 Seller enters the System to supply the System with Buyer information (57 and 58 as depicted
4 on FIG. 10D) so that the System can contact the Buyer (80, FIG. 10D) for details and to
5 facilitate the purchase and shipping of the item.

6 [0297] In contrast to the collection of both Seller and Buyer information in an eCommerce
7 embodiment, the generation of the Graphic Array in the exemplary simplified Internet
8 embodiment is accomplished using input from the Shipper only. FIG. 38 is a simplified flow
9 diagram depicting an exemplary high level overview logic flow of the System and the
10 interaction with the Shipper/User such as in an exemplary simplified Internet embodiment of
11 the invention. As depicted in FIG. 38, at least one of the Servers 20a-21z are programmed to
12 provide a User Interface ("UI") that prompts each Shipper user for information about a
13 particular parcel (the "Subject Parcel") and the Shipper's shipping and delivery requirements
14 ("Shipper Parcel Specifications") 1401a-1401n. At least one of the Servers 20a-21z is
15 programmed to receive as a set of input data a particular Shipper's Shipper Parcel
16 Specifications for a particular Subject Parcel 1402. In response to each Shipper's Shipper
17 Parcel Specifications, at least one of the Servers 20a-21z accesses 1403 one or more databases
18 of information concerning, among other things, the Carrier Rules for each of the Carriers
19 supported by the System (the "Supported Carriers") 1404a through 1404n. The Carrier Rules
20 for each of the Supported Carriers are contained in one or more databases 1404a through
21 1404n.

22 [0298] As further depicted in FIG. 38, the System then applies the Carrier Rules for all
23 Supported Carriers to each particular set of Shipper Parcel Specifications 1403. From the
24 result of the application by the System of the Carrier Rules to a particular set of Shipper
25 Parcel Specifications, the System prepares a Graphic Array that displays a rating and timing
26 comparison of the delivery services by the supporting Carriers that are available to provide
27 the delivery of the Subject Parcel according to the Shipper's Parcel Specifications 1405. The
28 System then formats the Graphic Array for display on the Shipper's PC 1406, and generates
29 the signals to the Shipper's PC to display the formatted Graphic Array 1407.

1 [0299] In one embodiment of the invention, the System provides multiple modes of
2 operation, among which are the Service Comparison Mode and the Shipping Mode. The
3 Service Comparison Mode requires origin and destination zip codes but does not require full
4 address information. The purpose of the Service Comparison Mode is to provide the Shipper
5 with multi-Carrier comparisons of rates, and shipping and delivery options and requirements
6 for each of multiple Carriers. In the Shipping Mode, the Shipper must provide the full
7 address and contact information. The purpose of the Shipping Mode is to print a shipping
8 label or otherwise provide the information necessary to prepare a shipping manifest
9 document. Shipper Parcel Specifications are input in both the Service Comparison Mode and
10 the Shipping Mode.

11 [0300] FIGS. 39A through 39C are simplified flow diagrams depicting the initial Timing
12 and Rating procedure to generate a Graphic Array in an exemplary simplified Internet
13 embodiment of the invention. In the embodiment of the invention depicted in FIGS. 39A
14 through 39C, the functions of the Shipper entering shipping information 1150, displaying
15 errors to the Shipper that insufficient shipping information has been provided and prompting
16 the Shipper for additional information 1153, and displaying the Carrier/Service rate and time
17 graphic 1160, are all processed by the Web Browser at the Client. In the embodiment
18 depicted, all other functions and processes depicted in FIGS. 39A through 39C are performed
19 by one or more of the NOC Servers.

20 [0301] It should be noted that the depicted separation of functions between the Web
21 Browser at the Client on the one hand and the NOC Servers on the other hand represents an
22 initial procedure to construct the Graphic Array in response to initial Shipper input of Shipper
23 Parcel Specifications. As is explained in more detail below, after the initial construction of
24 the Graphic Array, the System can distribute certain of the functions for supplemental
25 regeneration of the Graphic Array to the Web Browser Client.

26 [0302] As depicted in FIGS. 39A through 39C, the Shipper (User) enters shipping
27 information (Shipper Parcel Specifications) 1150. The System validates the shipping
28 information 1151.

1 [0303] In the embodiment depicted, at a minimum, the System requires Source Postal Code,
2 Destination Postal Code, Parcel Weight, Type of Shipment, and the Shipping Location in
3 order to determine a timing schedule and rates for each supported Carrier. If at 1152 the
4 Shipper has not provided at least these minimum specifications, then the System displays
5 error messages 1153 prompting the Shipper to input further Shipper Parcel Specifications
6 1150.

7 [0304] Continuing with FIGS. 39A through 39C, if the Shipper has supplied the minimum
8 required specifications, then the System accesses the Shipper Database 1195 to identify any
9 user-specified Carrier designations and to determine the Carrier accounts for the appropriate
10 Shipper 1154. Using the Shipper Parcel Specifications, the System then accesses the Carrier
11 Databases (1404a through 1404n) and determines all possible Carrier/Services that support
12 shipping of the subject parcel 1155.

13 [0305] It should be noted that in some embodiments, the Shipper can restrict the identity of
14 Carriers to be used in the construction of the Graphic Array. A Shipper may choose to restrict
15 the System to certain Carriers, for instance, if the Shipper prefers to work only with certain
16 Carriers.

17 [0306] Continuing with FIGS. 39A through 39C, the System then examines each
18 Carrier/Service in the set of supporting Carrier/Services 1156. The next step 1157 is a
19 juncture for return of control from a number of points in the System logic and is performed
20 for each Carrier/Service in the set of supporting Carrier/Services.

21 [0307] If the System has examined all possible supporting Carrier/Services 1158, the
22 System assembles the Graphic Array from the delivery rate set 1159 and displays the Graphic
23 Array to the user 1160. As was previously explained, the dimensions of the Graphic Array are
24 dynamic.

25 [0308] As long as there are further Carrier/Services that remain to be examined in the set of
26 supporting Carrier Services, the System continues to perform the process described below.

27 [0309] Using the Expected Shipping Date, the System switches the Carrier/Service's
28 shipping timespan into possible delivery dates and times 1161. Next 1162, the System

1 determines whether the shipping timespan ends on a Saturday 1163. If so, the System
2 accesses the Carrier Database (1404a through 1404n) to determine whether the particular
3 Carrier/Service supports Saturday Delivery 1164. If the particular Carrier/Service does not
4 support Saturday Delivery, then the particular Carrier/Service is eliminated 1177 from the
5 delivery rate set and the System proceeds with the next Carrier/Service in the delivery rate set
6 1157.

7 [0310] If the particular Carrier/Service supports Saturday Delivery, the System determines
8 the appropriate Saturday delivery rate for the particular Carrier/Service 1165.

9 [0311] Continuing with FIGS. 39A through 39C, next, the System determines whether the
10 shipping timespan ends on a Sunday 1168. If the shipping timespan ends on a Sunday, the
11 System accesses the Carrier Database (1404a through 1404n) to determine whether the
12 particular Carrier/Service supports Sunday delivery 1166. If the particular Carrier/Service
13 does not support Sunday delivery, then the particular Carrier/Service is eliminated from the
14 delivery rate set 1177 and the System proceeds with the next Carrier/Service in the delivery
15 rate set 1157.

16 [0312] If the particular Carrier/Service supports Sunday Delivery, the System determines
17 the appropriate Sunday delivery rate for the particular Carrier/Service 1167.

18 [0313] The System then determines whether there is a business day delivery within the
19 shipping timespan 1169. If so, the System accesses the Carrier Database (1404a through
20 1404n) to determine whether the particular Carrier/Service supports business day delivery
21 1170. If the particular Carrier/Service does not support business day delivery, then the
22 particular Carrier/Service is eliminated from the delivery rate set 1177 and the System
23 proceeds with the next Carrier/Service in the delivery rate set 1157.

24 [0314] If the particular Carrier/Service supports business day delivery, the System
25 determines the appropriate business day delivery rate for the particular Carrier/Service 1171.

26 [0315] Continuing with FIGS. 39A through 39C, the System next determines whether the
27 Shipper has requested E-Mail delivery notification 1172. If so, the System accesses the
28 Carrier Database (1404a through 1404n) to determine whether the particular Carrier/Service

1 supports E-Mail delivery notification 1173. If the particular Carrier/Service does not support
2 E-Mail delivery notification, then the particular Carrier/Service is eliminated from the
3 delivery rate set 1177 and the System proceeds with the next Carrier/Service in the delivery
4 rate set 1157.

5 [0316] If the particular Carrier/Service supports E-Mail delivery notification, the System
6 adds the appropriate charge for the E-Mail delivery notification service to each of the
7 particular Carrier/Service's delivery rates 1174.

8 [0317] Continuing with FIGS. 39A through 39C, the System then determines whether the
9 Shipper has requested verbal delivery notification 1175. If so, the System accesses the
10 Carrier Database (1404a through 1404n) to determine whether the particular Carrier/Service
11 supports verbal delivery notification 1176. If the particular Carrier/Service does not support
12 verbal delivery notification, then the particular Carrier/Service is eliminated from the delivery
13 rate set 1177 and the System proceeds with the next Carrier/Service in the delivery rate set
14 1157.

15 [0318] If the particular Carrier/Service supports verbal delivery notification, the System
16 adds the appropriate charge for the verbal delivery notification service to each of the
17 particular Carrier/Service's delivery rates 1178.

18 [0319] Next 1179, the System determines whether the Shipper has requested that the
19 Carrier/Service guarantee delivery time 1180. If so, the System accesses the Carrier Database
20 (1404a through 1404n) to determine whether the particular Carrier/Service supports
21 guaranteed delivery times 1181. If the particular Carrier/Service does not support guaranteed
22 delivery times, then the particular Carrier/Service is eliminated from the delivery rate set
23 1177 and the System proceeds with the next Carrier/Service in the delivery rate set 1157.

24 [0320] If the particular Carrier/Service supports guaranteed delivery times, the System adds
25 the appropriate charge for the guaranteed delivery times service to each of the particular
26 Carrier/Service's delivery rates 1182.

27 [0321] Continuing with FIGS. 39A through 39C, the System then determines whether the
28 Shipper has requested a "Call for Pickup" shipping location 1184. If so, the System accesses

1 the Carrier Database (1404a through 1404n) to determine whether the particular
2 Carrier/Service supports “Call for Pickup” services 1185. If the particular Carrier/Service
3 does not support “Call for Pickup” services, then the particular Carrier/Service is eliminated
4 from the delivery rate set 1177 and the System proceeds with the next Carrier/Service in the
5 delivery rate set 1157.

6 [0322] If the particular Carrier/Service supports “Call for Pickup” services, the System adds
7 the appropriate charge for the “Call for Pickup” service to each of the particular
8 Carrier/Service’s delivery rates 1186.

9 [0323] Continuing with FIGS. 39A through 39C, the System next determines whether the
10 Shipper has requested a “Residential Delivery” 1187. If so, the System accesses the Carrier
11 Database (1404a through 1404n) to determine whether the particular Carrier/Service supports
12 “Residential Delivery” services 1188. If the particular Carrier/Service does not support
13 “Residential Delivery” services, then the particular Carrier/Service is eliminated from the
14 delivery rate set 1177 and the System proceeds with the next Carrier/Service in the delivery
15 rate set 1157.

16 [0324] If the particular Carrier/Service supports “Residential Delivery” services, the System
17 adds the appropriate charge for the “Residential Delivery” service to each of the particular
18 Carrier/Service’s delivery rates 1189.

19 [0325] The System then determines whether the Shipper has requested a “Loss Protection”
20 services 1190. If so, the System accesses the Carrier Database (1404a through 1404n) to
21 determine whether the particular Carrier/Service supports “Loss Protection” services 1191. If
22 the particular Carrier/Service does not support “Loss Protection” services, then the particular
23 Carrier/Service is eliminated from the delivery rate set 1177 and the System proceeds with the
24 next Carrier/Service in the delivery rate set 1157. The System then determines 1192 whether
25 the requested loss protection is within the service’s range; if not, the System proceeds with
26 the next Carrier/Service in the delivery rate set 1157.

27 [0326] Continuing with FIGS. 39A through 39C, if the particular Carrier/Service supports
28 “Loss Protection” services, and if the requested loss protection is within the service’s range

1 the System calculates the appropriate charge for the “Loss Protection” service and adds the
2 appropriate charge to each of the particular Carrier/Service’s delivery rates 1193 before
3 proceeding with the next Carrier/Service in the delivery rate set 1157.

4 [0327] FIG. 40 is a graphic representation depicting an exemplary embodiment of a multi-
5 carrier, multi-service shipping rates comparison Graphic Array 320 in an exemplary
6 eCommerce embodiment of the invention.

7

c) AUTOMATIC DYNAMIC REGENERATION OF DISPLAY

[0328] In the exemplary embodiments of the invention described here, the System automatically and dynamically regenerates the display of the Graphic Array and certain portions of other screens when the Shipper makes online changes to Shipper input. To do this, the System generates executable code which it distributes with certain displayable frames to the Web Browser Client. This distribution of code for purposes of regenerating the Graphic Array differs from the initial generation of the Graphic Array as was described above. For example, in the embodiment of the invention depicted in FIGS. 39A through 39C, in the initial development of the Graphic Array, the System distributes the functions that initially generate the Graphic Array as follows: the Shipper entering shipping information 1150, displaying errors to the Shipper that insufficient shipping information has been provided and prompting the Shipper for additional information 1153, and displaying the Graphic Array 1160, are all processed by the Web Browser at the Client; all other functions and processes depicted in FIGS. 39A through 39C are performed by one or more of the NOC Servers 20a-21z.

23 [0329] Distribution to the Web Browser Client by the System of executable code that
24 regenerates the Graphic Array provides the capability to dynamically reflect in the Graphic
25 Array any changes that the Shipper may enter to the various Shipper Parcel Specifications;
26 the Graphic Array immediately displays the new information without requiring the Shipper to
27 request a recalculation, such as by clicking on a “Regenerate” button or the like.

28 [0330] To facilitate regeneration of the Graphic Array, the System generates executable

1 code which it distributes with the frame, such as the frame that is displayed to the user for
2 collecting the Parcel Specifications, to the Web Browser Client. A displayable frame is a set
3 of information for display on the client display device. For example, in FIG. 36A, in one
4 embodiment of the invention, a first frame of the screen depicted in FIG. 36A comprises the
5 Title “Rates & Times” 1109a, the instruction “Click on the price to select a delivery date,
6 time and carrier.” 1109b, the legend “Date you expect to ship your package.” 1109c, the input
7 field for the Expected Shipping Date 1060, the legend “I’ll ship the package from.” 1109d
8 and the input field for the Shipping Location 1066; a second frame of the screen depicted in
9 FIG. 36A comprises the Graphic Array.

10 [0331] As the System generates the display of each frame, the System generates executable
11 code which it distributes with, e.g., the Rate & Times frame, to the Web Browser Client.
12 Thereafter, the Web Browser Client uses the executable code to automatically regenerate the
13 display of the Graphic Array each time the Shipper makes changes to the Shipper Parcel
14 Specifications. In one embodiment of the dynamic regeneration aspect of the invention, the
15 executable code distributed to the Web Browser Client uses JavaScript.

16 [0332] In some cases, the executable code sent to the Web Browser Client provides the
17 information and the capability to regenerate the Graphic Array without any further
18 communication with the Server. In other cases, the Web Client Browser must return control to
19 the Server so that the Server can access data maintained by or accessible by the Server; the
20 Server then regenerates the Graphic Array or otherwise provides the Web Browser Client
21 with the information necessary to regenerate the Graphic Array.

22 [0333] In an exemplary embodiment of the automatic dynamic regeneration aspect of the
23 invention, the executable code distributed to the Web Browser Client contains the logic to
24 apply Carrier Rules to Shipper Parcel Specification changes. For instance, Shipper changes to
25 the Service Options screen as depicted in FIG. 28 would be automatically processed by the
26 Web Client Browser and the Web Client Browser would regenerate the Single Day Rate
27 Graphic Array depicted therein to reflect the Shipper changes. In one such automatic
28 dynamic regeneration embodiment, only those functions that do not require further access to

1 the relevant Carrier's database are distributed to the Web Browser Client.

[0334] It should be noted that, according to the automatic dynamic regeneration aspect of the invention, if after the Shipper views the Graphic Array the Shipper enters changes to any of the factors with which the System calculates the rates and develops the Graphic Array, the System uses a similar logic flow to regenerate the Graphic Array as was explained above in relation to FIGS. 39A through 39C.

[0335] The dynamic regeneration capability is used to automatically regenerate response screens in many places throughout the System. For instance, as was mentioned above, as in the case of FIG. 36A, if the Shipper changes Origin Zip Code and/or Ship Location Type, the System will automatically regenerate a list of possible Drop Off Location choices.

11

d) **COMPLETING PARCEL SPECIFICATIONS AND THE BUYER'S INFORMATION**

14 [0336] In an eCommerce embodiment of the invention, the System collects information
15 from both a Seller (the Shipper) and a Buyer (the Recipient). The Seller (Shipper) inputs
16 information about the parcel to be shipped and initial information about the Buyer. The Buyer
17 then inputs information such as shipping address and payment information. Depending upon
18 the Seller's preferences, the Buyer may also be asked to choose one of multiple carriers and
19 multiple shipping services.

20 [0337] FIG. 41 is a graphic representation of a Seller's Buyer Information Screen (57, FIG.
21 10D) in an eCommerce embodiment of the invention. The Seller enters the screen in one
22 embodiment by logging in to the System and then selecting the Sell It option 31a and by
23 selecting the Request Buyer Info submenu option 31b-3. The System provides the Seller with
24 instructions to complete the requested data 350. The Seller inputs the Buyer's Name 351, the
25 Buyer's e-mail address 352, an Order/Item number 353, a Description of the Goods to be
26 Shipped 354a (the Seller may scroll through the description using the scroll buttons 354b and
27 354c if the description exceeds the online screen window for the description text), and a
28 message to the buyer 355a (the Seller may scroll through the message using the scroll buttons

1 355b and 355c if the message exceeds the online screen window for the message text).

2 [0338] Buyer information and package/item information is mapped by the System into the
3 appropriate shipping data fields (i.e., Buyer name is mapped to Recipient Company/ name;
4 Buyer e-mail is mapped to Recipient e-mail, item/order number is mapped to reference
5 number, etc.).

6 [0339] Clicking on the Next button 102 will cause the System to display the Next screen,
7 which in this case is the package specific information screen (58, FIG. 10D) as depicted in
8 FIG. 42.

9 [0340] FIG. 42 is a graphic representation of an exemplary embodiment of a Subject Parcel
10 data screen. The Seller inputs the weight by clicking on the weight pull down menu button
11 358-2 and selecting a weight 358-1 from the list. An “Irregular or Non-Standard Packaging”
12 indicator 359 is provided. The Seller selects Loss Protection, the default being Basic
13 Coverage 360, or Declared Value 361. If the Seller selects Declared Value 361, the Seller
14 must enter a value 362 greater than \$0.00 and less than or equal to \$50,000.00. The Seller
15 also enters the Item Cost to be displayed to the Buyer 364 and indicates whether or not the
16 System should show the Buyer the total of the Item Cost and Shipping Charges 363. Once the
17 Seller has entered the information, if the Seller clicks on the Send button 365, the System
18 validates the information input and prepares an e-mail to the Buyer (59, FIG. 10D).

19 [0341] At this point, the System generates a System package tracking number. A System
20 tracking number is a unique number generated internally by the System to identify a particular
21 package shipped using the System. One embodiment of the way in which the System
22 generates a System package tracking number is disclosed below in the Tracking section of the
23 disclosure of the present invention.

24 [0342] FIG. 43 is a graphic representation of an exemplary embodiment of a System-
25 prepared e-mail to the Buyer. The System builds the e-mail to contain the identification of the
26 System as the sender 370, the e-mail of the Buyer 352 as supplied by the Seller, a Subject
27 identification containing the item number 353 as supplied by the Seller, the Buyer name 351
28 as supplied by the Seller, the Seller name 375 as retrieved from the Seller’s account

1 information retrieved after the Seller logged into the System before entering Request Buyer
2 Info 31b-3 (e.g., as depicted in FIG. 24), a Reference number as provided by the Seller 353,
3 instructions to the Buyer 371 to click on the embedded hyperlink 372, and some further
4 instructions to the Buyer 374. The System builds the hyperlink 372 according to a preset
5 URL location 372-1 as provided from the System database 22, and specifying the System
6 package tracking number 372-3 as the value for a variable named “T=” 372-2.

7 [0343] If the Buyer's e-mail program is integrated with the Buyer's web browser, then the
8 Buyer can click on the hyperlink/URL 372 contained in the e-mail. Otherwise, the Buyer
9 must copy the hyperlink/URL 372 into the Address/Location field of the web browser. When
10 the Buyer clicks on the hyperlink/URL 372, the System displays the first screen (60, FIG.
11 10D) in the Buyer Response process.

12 [0344] FIG. 44 is a graphic representation of an exemplary embodiment of the Buyer
13 Response Introduction screen. The System provides the Buyer with instructions 380. The
14 System instructs the Buyer 382 to indicate 383 the Buyer's choice not to supply the requested
15 shipping information and an explanation as to why 384-1. The Buyer can scroll through the
16 explanation using the up and down scroll keys 384-2 and 384-3 if the text of the description
17 exceeds the online screen window for the text. The Buyer sends the refusal notification and
18 message by clicking the Send button 385. Otherwise, if the Buyer wishes to proceed, the
19 Buyer clicks the Next button 381 which will cause the System to display a Buyer Shipping
20 Information Collection screen (61, FIG. 10D).

21 [0345] FIG. 45 is a graphic representation of an exemplary embodiment of the Buyer
22 Shipping Information Collection screen (61, FIG. 10D). The System requests that the Buyer
23 input the Buyer's delivery address information and then click the Next button 389. The Buyer
24 inputs the delivery address information including the Company/Name 390, the Attention to
25 name 391, the street address 392, the floor/room number 393, the department 394, the city
26 395, the state 396-1 using the pull down menu button 396-2, the zip code 397, the telephone
27 number 398, the fax number 399, and whether the delivery address is a business 400 or a
28 residence 401. If the Buyer then clicks the Next button 102, the System validates the

1 information supplied by the Buyer and displays a screen (62, FIG. 10D) as depicted in FIG. 46
2 containing a selection as to whether yes 405 or no 406 the Buyer wants a guaranteed delivery
3 time. Once the Buyer selects the guarantee choice, then the Buyer clicks the Get Rates button
4 407 to request that the System prepare and display the multi-carrier, multi-service shipping
5 rates comparison Graphic Array 320.

6 [0346] An exemplary embodiment of the Graphic Array 320 in an exemplary eCommerce
7 embodiment of the invention is depicted in FIG. 46. The Graphic Array 320 presents a multi-
8 carrier, multi service rate and time shipping cost comparison as similarly disclosed above and
9 described with respect to FIG. 36A.

10 [0347] The System creates the Graphic Array in much the same way as is disclosed above
11 with respect to FIG. 36A except that, with respect to the eCommerce embodiment, instead of
12 only Shipper input, the System collects origination data including origin zip code, subject
13 parcel data, and Carrier/Service filtering data from the Seller, and then completes the Parcel
14 Specifications for the subject parcel by collecting input from the Buyer, including destination
15 zip code.

16 [0348] Using the subject parcel's Parcel Specifications, the System 1 is programmed to
17 access databases containing information about each supported Carrier. Each supported
18 Carrier has a unique rating schedule, delivery and pickup rules and schedules, and
19 certification requirements (the "Carrier Rules"). The System 1 is further programmed to
20 apply each supported Carrier's Rules to each Shipper's Parcel Specifications for the
21 corresponding Subject Parcel. The System calculates the Shipping Charges based on zip-to-
22 zip pricing where the Seller has provided the origin zip code and the Buyer has provided the
23 destination zip code.

24 [0349] The System provides an online display of a Dynamically Dimensioned Multi-Carrier
25 Graphic Array such as is depicted in FIG. 46. If the Seller selected as the Seller's preference,
26 "Item cost includes shipping charges" (170, FIG. 21), then the rates displayed will be
27 "FREE". If the Seller selected as the Seller's preference, "Buyer pays actual shipping
28 charges" (171, FIG. 21), then the rates displayed will be the total shipping charge as

1 calculated according to each Carrier's rules for each Service available according to the
2 Seller's expressed preferences. If the Seller selected as the Seller's preference, "Buyer pays
3 shipping and additional charges" (172, FIG. 21), then the System will calculate and display
4 rates that are the sum of: 1) the shipping rate for the applicable service according to each
5 Carrier's rules; 2) If the Seller checked "Add Percentage of Shipping Cost" (173, FIG. 21),
6 the product of the percentage entered in the Percentage of Shipping Cost field (174, FIG. 21)
7 and the total shipping rate calculated according to the Carrier's rules; 2) if the Seller checked
8 "Add Fixed Handling Charge" (175, FIG. 21), the dollar value entered in the Fixed Handling
9 Amount field (176, FIG. 21); and 4) if the Seller indicated "Add System Service Fee" (177,
10 FIG. 21), then the System Service Fee amount as indicated in the System database 22.

11 [0350] The Dynamically Dimensioned Multi-Carrier, Multi-Service Graphic Array online
12 display presents only rating and delivery timing information for the Carriers that offer
13 shipping of the particular Subject Parcel according to the particular Shipper's Parcel
14 Specifications and which conform with the Seller's Carrier/Service preferences as selected
15 according to the available options as described above regarding FIGS. 19 and 20.

16 [0351] The Buyer uses a user input device such as a mouse, track ball, or the like, to pick a
17 Carrier and Service. To make the selection, the Buyer, for instance, places the cursor of the
18 Buyer's PC on the displayed Carrier cell entry (e.g., 408 as depicted in FIG. 46; e.g., 1065 as
19 depicted in FIG. 36A) in the Graphic Array and clicks the Buyer's user input device (the
20 "Selected Carrier").

21 [0352] Once the Shipper selects a particular Graphic Array Carrier cell element, (e.g., 408
22 as depicted in FIG. 46; e.g., 1065 as depicted in FIG. 36A) the System then processes the
23 shipping transaction. In an exemplary simplified Internet embodiment of the invention, the
24 System processes the Shipper's shipping transaction using Shipper information from the
25 Shipper Database 1195 (e.g., as depicted in FIG. 39A) and information for the Selected
26 Carrier from the Carrier Database 1404a through 1404n (e.g., as depicted in FIG. 39A). In an
27 exemplary eCommerce embodiment of the invention, the System processes the shipping
28 transaction using information supplied by both the Seller/Shipper and the Buyer/Recipient and

1 information for the Selected Carrier.

2 [0353] In an eCommerce embodiment of the invention, once the Buyer selects a Carrier and
3 Service, the System prepares a Shipping Summary Screen (63, FIG. 10D) an exemplary
4 embodiment of which is depicted in FIG. 47. The System reports a summary of the Shipping
5 information including the delivery address 410, the Carrier/Service 411 and the itemized and
6 total charges for the item and shipping 412. In addition, if the Seller requested the System to
7 collect payment information, the System provides a drop down selection menu button 413-2
8 which when clicked will display a list of the methods of payment 413-1 previously selected by
9 the Seller (e.g., 179a-179g, and 180, as depicted in FIG. 21). If a credit card payment method
10 is indicated, the Buyer is required to supply a credit card number 414, and the expiration date
11 month 415-1 (using a drop down menu button 415-2) and year 416-1 (using a drop down
12 menu button 416-2). The Buyer is instructed to click the Cardholder Information button 417
13 if the cardholder name and address are different than the shipping name and address 419. If
14 the Cardholder and shipping information match, the Buyer clicks the Send button 418 to send
15 the payment information to processing.

16 [0354] In an exemplary simplified Internet embodiment of the invention, the System
17 generates a Shipping Summary Screen once the Shipper has picked a particular
18 Carrier/Service entry from a Graphic Array comparison. FIG. 48 depicts an alternative
19 exemplary embodiment of a Shipping Summary Screen such as in an exemplary simplified
20 Internet embodiment of the invention. In the embodiment depicted in FIG. 48, the Shipper has
21 picked a particular Carrier/Service entry from a Graphic Array comparison (e.g., 1065 as
22 depicted in FIG. 36A). The Shipping Summary Screen depicted in FIG. 48 displays the
23 Shipper Parcel Specifications 1110 and provides a detailed list and total, of the selected
24 Carrier's charges 1111. Clicking on the "Next" button 102 causes the display of the first of a
25 series of several screens (not shown) requesting the necessary Shipper and Recipient
26 information. Once the Shipper has input all of the necessary information, the Shipper is
27 presented with a final Summary and Payment Screen (not shown), which in addition to the
28 fields depicted in FIG. 48, further requests Payment information, such as Payment Method,
29 Credit Card No., Expiration Date, and Credit Card Type.

1 [0355] Returning to the eCommerce embodiment depicted in FIG. 47, if the Buyer clicks
2 the Cardholder Information button 417, the System displays a Cardholder Information
3 collection screen (64, FIG. 10D), an exemplary embodiment of which is depicted in FIG. 49.
4 The Buyer is asked to supply the Cardholder name 420, Street address 421, State 422-1 (using
5 a pull down menu button 422-2), and zip code 423. The Buyer clicks the Save button 424 to
6 save the cardholder information.

7 [0356] As depicted in FIG. 10D, once the Buyer in an eCommerce embodiment has
8 completed all Buyer Response screens, the System enters the System package tracking
9 number in the System's Shipping Log for the Seller, an exemplary embodiment of which is
10 depicted in FIG. 50. The System also notifies the Seller via e-mail (66, FIG. 10D) that the
11 Buyer has completed all of the necessary shipping and payment information.

12

13 E. SHIPPING THE PACKAGE

14 [0357] In an exemplary eCommmerce embodiment of the invention, the System notifies the
15 Seller via e-mail (66, FIG. 10D) once the Buyer has completed all of the necessary shipping
16 and payment information. An exemplary embodiment of a Seller notification e-mail is
17 depicted in FIG. 51. In the Seller notification e-mail, the System identifies the System as the
18 sender 370, the Seller's e-mail 107 (e.g., as depicted in FIG. 12) as the recipient 375, and the
19 item number 353. The e-mail contains a message 425 and instructions 427 to log on to the
20 System 426 to view a Shipping Log. The Shipping Log provides a platform with which the
21 Shipper/Seller controls the shipping and attendant functions for all packages shipped or to be
22 shipped by the particular Shipper/Seller.

23 [0358] The Seller can view the Shipping Log by selecting the View Shipping Log submenu
24 option 32b-2 from the Ship It menu option 32b (which provides various submenu options
25 including Shipping Preferences 32b-1, View Shipping Log 32b-2, Ship a Package 32b-3, Price
26 a Package 32b-4, Send Shipment Notification 32b-5, UPS End of Day 32b-6 and Log Off
27 32b-7). The Shipper/Seller can control the display order of the Shipping Log by selecting
28 from a choice of several reporting controls. The Shipping Log (65, FIG. 10D) as depicted in

1 FIG. 50 provides reporting controls such as Display selection 430 (with a pull down menu
2 button 431), time period 432 (with a pull down menu button 433), and sort by 434 (with a pull
3 down menu button 435). The Seller can click on the Update View button 436 to request an
4 up-to-date report. Each Shipping log line item contains the System tracking number 438, the
5 addressee name 437, the Carrier 440 and Service 439, the Ship date 441 and delivery date
6 442, and control buttons that allow the Seller to request details 443, instruct the system to ship
7 the item 444, void the shipment 445, or reprint a label 446.

8 [0359] FIG. 52 is a graphic representation of an exemplary embodiment of a Void Package
9 screen that the System displays if the Seller clicks on the Void button 445 on the Shipping
10 Log. The Void Package screen provides a summary report of the information about the
11 particular package 452, provides a View Details button 451 if the Seller wants additional
12 detailed information about the package, and a Void Package button 453 if the Seller finally
13 decides to void the identified package.

14 [0360] FIG. 53 is a graphic representation of an exemplary embodiment of a Reprint Label
15 screen which provides a report about the package 454, a View Details button 451, and a
16 Generate Label button 455. If the User clicks the Generate Label button 455, the System will
17 generate and print a shipping label (69, FIG. 10E) for according to the appropriate Carrier and
18 Service, as limited by the Seller and as finally selected by the Buyer.

19 [0361] As mentioned above, in some embodiments, the Shipper can use the System to
20 locally print on the Shipper's printer device a bar-coded shipping label according the Selected
21 Carrier's certification standards. In some embodiments, the bar-coded shipping label,
22 including two dimensional bar code labels, and other types of shipping labels, can be printed
23 on either a thermal label printer or on a laser printer. The Shipper specifies the type of printer
24 to the system during initial setup procedures. Thereafter, the System uses, as appropriate, the
25 thermal printer or laser printer module to prepare the label image for printing on the Shipper's
26 printer.

27 [0362] FIG. 54 depicts a flow diagram of one embodiment of the aspect of the invention
28 that provides printing of bar-coded shipping labels on printer devices which are compatible

1 with the client system on which the web browser is running, such as an HP-compatible laser
2 printer. As depicted in FIG. 54, one of the NOC Servers, for instance, the Shipping Server,
3 e.g., 21t as depicted in FIG. 7, gets the Label Size from the Carrier Label Specification 1250,
4 the Label Layout from the Carrier Label Specification 1251, Label Data from the Shipper
5 Database 1252, and the Label Quality in Dots Per Inch (“DPI”) as set by the Server 1253, and
6 uses this information to Generate the Label 1254.

7 [0363] The Server then creates, and causes the display on the client browser’s display
8 device of, a text string with a specified font face and in a specified font size in an HTML table
9 data cell with a specified width 1255. If the client browser is using a 096 display device DPI,
10 the display device will display said text string in the HTML table data cell in a single line. If
11 on the other hand, the client browser is using a 120 display device DPI, the display device will
12 display said text string in the HTML table data cell in two lines.

13 [0364] In creating the display of the text string, the Server also sends a message to the
14 Shipper asking the Shipper to answer the following question: do you see the text string
15 displayed on your screen as a single line or as wrapped text in multiple lines? The Server
16 receives the Shipper’s response and determines from the response whether the Shipper’s
17 display device has displayed the text as a single line or as wrapped text in multiple lines 1256.
18 If the text is displayed as a single line, then the client browser 1258 display device DPI is 96.
19 Otherwise, the client browser 1257 display device DPI is 120.

20 [0365] Next, the Server calculates the shipping label HTML image size in pixels 1259 by
21 multiplying the Carrier-specified label size from the Carrier Label Specification times the
22 client browser display device DPI as determined by the previous step.

23 [0366] Next, the System displays the generated label image in the client browser 1260 with
24 an HTML image tag and an HTML image size in pixels as calculated in the prior step.

25 [0367] The client browser calculates the size of the label to be printed in inches by dividing
26 the label HTML image size in pixels as calculated in a prior step by the client browser display
27 device DPI 1261; the client browser then prints out the label with the size calculated 1261.

28 [0368] FIG. 55 depicts a flow diagram of an exemplary embodiment of the aspect of the

1 invention that provides printing of dimensionally accurate images, such as dimensionally
2 sensitive symbologies including two-dimensional bar codes and other two-dimensional
3 machine readable symbologies. This aspect of the invention provides the printing of such
4 dimensionally accurate images on various types of printer devices including among others
5 HP-compatible laser printers. The printer devices can be configured with remote computers,
6 such as PC's, that will receive signals to print the dimensionally accurate image over a
7 communications network such as the Internet. Each PC having a client browser or executing
8 like software, and each PC being configured with a pre-established Image Resolution that
9 applies to the display device and the printer device configured with the PC.

10 [0369] As depicted in FIG. 55, a computer, such as Server 20t as depicted in FIG. 7,
11 determines the Image Size 1350, the Image Layout 1351, any relevant Image Data 1352, and
12 the Image Resolution in Dots Per Inch ("DPI") or in any other measure of Image Resolution
13 1353. The Server 20t uses this information to Generate the Image.

14 [0370] Alternatively, the Image has previously been created; the Server 20t determines from
15 the Image, the Image Size 1350, the Image Layout 1351, any relevant Image Data 1352, and
16 the Image Resolution in DPI or in any other measure of Image Resolution 1353 (collectively
17 referred to hereinafter as the "Image Characteristics").

18 [0371] The Server 20t determines the possible Image Resolution Categories and associated
19 values for client PC's 1354. Image Resolution Categories and associated values include
20 information such as the number of text strings, and the length of and characteristics (font face,
21 font size, and HTML table cell width) of each of the identified number of, text strings that
22 must be used to determine the Image Resolution of client display devices 1355-1356.

23 [0372] An HTML table cell width is fixed in that the physical width of the display of the
24 HTML table cell does not change depending upon the resolution of the client device; a text
25 string comprised of characters having a particular font and font size has a scalable width,
26 depending upon the resolution of the client device resolution. Use of an HTML table cell to
27 measure the resolution of client devices is not a limitation of the invention. In an alternative
28 embodiment, a graphic element other than an HTML table cell, having a fixed width, is used

- 1 to measure the resolution of client devices.
- 2 [0373] The possible Image Resolution Categories and values are stored in the memory of
3 the Server 20t and updated on some basis. In an alternative embodiment, the possible Image
4 Resolution Categories and values are input into the Server computer.
- 5 [0374] The Server 20t then analyzes the Image Characteristics, and the possible Image
6 Resolution categories and/or values 1355, and creates the appropriate number of text strings
7 and associated HTML table cells 1356. Each text string is created to have a specified font
8 face, a specified font size, and an associated HTML table cell with a specified width 1356.
9 The computer then causes the display of the text strings in the associated HTML table cells on
10 the remote client PC's display device 1358.
- 11 [0375] In creating the display of the text string, the Server also sends a message to the
12 recipient PC asking the user to answer the following question: is the first text string displayed
13 on your screen as a single line or as wrapped text in multiple lines? The Server 20t receives
14 the remote user's response and determines from the response whether the remote user's PC's
15 display device has displayed each of the text strings as a single line or as wrapped text in
16 multiple lines 1256. The Server 20t then sets the PC's Remote Image Resolution for printing
17 the Image 1359 according to the results of the user's PC's display of the text strings.
- 18 [0376] Next, the Server calculates the Remote HTML Image Size in pixels 1360 by
19 multiplying the Image Size times the PC's Remote Image Resolution as determined by the
20 previous step.
- 21 [0377] Next, the Server displays the generated image on the display device of the remote
22 PC 1361 with an HTML image tag and the Remote HTML Image Size in pixels as calculated
23 in the prior step.
- 24 [0378] The client browser of the remote PC calculates the size of the Image to be printed
25 ("Remote Print Image Size") in inches by dividing the Remote HTML Image Size in pixels by
26 the Remote Image Resolution 1362; the client browser then prints out the Image with the
27 Remote Print Image Size 1362.
- 28 [0379] In one embodiment of the invention, instead of printing a shipping label at the

1 Shipper's printer, a Package Number 1120 is displayed online on a Package Number Screen
2 with notification that the label will be printed at a shipping location previously designated by
3 the Shipper. FIG. 56 depicts an exemplary embodiment of a Package Number Screen. The
4 Shipper can Void the Package Label at this point by clicking the Void Package button 1121.
5 The Shipper can request shipping of a new parcel by clicking the "New Package" button 1122
6 or can indicate completion of shipping instructions by clicking the "Done" button 1123.

7 [0380] FIG. 57 depicts an exemplary embodiment of a Generate Shipping Label Screen in
8 an exemplary simplified Internet embodiment of the invention. The Shipper is given
9 instructions 1125 as to how to print the label. Clicking the "Generate Label" button 1124
10 causes the bar-coded label to be generated.

11 [0381] FIG. 58 depicts an exemplary embodiment of a Print Label Screen in an exemplary
12 simplified Internet embodiment of the invention. At the top of the Screen, an instruction 1130
13 is displayed to scroll to the bottom of the screen for instructions. The generated label 1131 is
14 displayed in the main body of the screen. Instructions for printing the label 1132 are
15 displayed at the bottom of the screen. Clicking the "Print Label" button 1133 (visible only for
16 supported web browsers) will cause the label to be printed. Clicking the "Done" button 1134
17 will close the web browser window.

18 [0382] Returning to the exemplary eCommerce embodiment, if the Seller chooses to ship a
19 specified package, e.g., by clicking on the Ship button 444 as depicted in FIG. 50, the System
20 requests the Seller to input information to e-mail a notification to the Buyer that the package
21 is being shipped. FIG. 59 is a graphic representation of an exemplary embodiment of a Send
22 Ship Notification screen (67, as depicted in FIG. 10E). In one eCommerce embodiment, this
23 information is automatically prepared by the System and an e-mail (e.g., 70 as depicted in
24 FIG. 10E) is automatically sent to the Buyer (80, e.g., FIG. 10E) when the Seller ships the
25 package. In one embodiment, the Seller completes the information in this screen only if the
26 Seller ships the package with a Carrier or a service that is not supported by the System.

27 [0383] In an exemplary FIG. 60 depicts an exemplary E-Mail Others "Messages" pop-up
28 Window in an exemplary simplified Internet embodiment which allows the Shipper to identify

1 the “To” or “cc” status of the desired notification 1101 using a drop down menu activator
2 1102 and which allows the user to enter each e-mail recipient’s Name 1103 and E-Mail
3 Address 1104. FIG. 60 depicts two Recipients 1107 and 1108; the screen is exemplary and is
4 not a limitation of the invention.

5 [0384] Returning to the exemplary eCommerce embodiment, when the Seller chooses to
6 ship a specified package, the System prepares and displays a Ship a Package Summary report
7 (68, FIG. 10E) an exemplary embodiment of which is depicted in FIG. 61.

8 [0385] If the Seller/Shipper ships packages using UPS, the Seller will need to run UPS End
9 of Day processing (71, FIG. 10E) at least once each day a package is shipped using UPS.
10 FIG. 62 is an exemplary embodiment of the UPS End of Day screen. The System provides
11 instructions 470 and a Perform End-of-Day button 471. The System also provides Reprint
12 instructions to reprint a driver record from a previous End-of-Day process 472 and a Find
13 Driver Record button 473.

14 [0386] FIG. 63 is a graphic representation of an exemplary embodiment of a Reprint Driver
15 Record Screen that lists prior driver records 480, each record provides a Reprint button 481
16 which when clicked will reprint the driver record (72, FIG. 10E).

17 [0387] After the Seller has completed printing the label, the Seller must give the package to
18 the Carrier (73, FIG. 10E) so that it can be delivered via the Carrier (74, FIG. 10E).

19 [0388] The System provides complete tracking and reporting capabilities for packages
20 shipped through it, and for packages for which a Carrier tracking number is known as
21 described below and as disclosed in U.S. Provisional Patent Application Serial No.
22 60/170,186 previously attorney docket number 36618/DBP/I249 now attorney docket number
23 36620/DBP/I249, the disclosure of which has previously been incorporated for all purposes
24 herein by reference.

25 [0389] FIGS. 64A-1, 64A-2, 64B-1 and 64B-2 are System interactivity data and logic flow
26 diagrams depicting an exemplary eCommerce embodiment of the process by which the
27 System completes the information necessary to ship a package. References in the explanation
28 and description of FIGS. 64A-1, 64A-2, 64B-1 and 64B-2 to the Buyer mean to the Buyer and

1 the Buyer's computer 8-2; references to the Seller mean to the Seller and the Seller's
2 computer 8-1; references to the System mean the System servers, 20a-20n (the database
3 servers) and 21a-21z (the other System servers); references to the System database mean to
4 the entire logical System database 22.

5 **[0390]** The Seller eCommerce Preference setup Processes 231 through 239 have been
6 previously described herein above. After the Seller has completed setting up eCommerce
7 preferences, and after the Seller is notified of a sale, the Seller enters the System and prepares
8 to enter Buyer information by clicking on the Buyer information submenu option 501. The
9 System then displays a Buyer Information screen 502 to the Seller. The Seller then enters
10 Buyer information and clicks the Next button 503. The System responds by displaying the
11 Item and Cost screen 504. The Seller enters the item and cost information and sends the
12 information to the System 505.

13 **[0391]** The System uses the information provided by the Seller to create a new package
14 record in the System database and sets the status of the package to "waiting for buyer's
15 response" 506. The System prepares and sends an e-mail to the Buyer requesting information
16 to complete the shipment and including a URL hyperlink to the System web site page that is
17 available to intake the Buyer's information, the URL containing a System package tracking
18 number for the specified package 507. The System also prepares and sends an e-mail to the
19 Seller informing the Seller that the e-mail has been sent to the Buyer 508.

20 **[0392]** The Buyer upon receipt of the System e-mail, uses a web browser to navigate the
21 URL in the System e-mail and enter the System 509. The System retrieves the System
22 package tracking number from the URL provided by the user's browser to access 510 and
23 retrieve 511 the package information from the System database. The System provides the
24 Buyer with an introduction and instructions to complete the process 512. If the Buyer chooses
25 to proceed, the Buyer clicks the Next button 513. The System then requests Buyer shipping
26 information 514. The Buyer completes the Buyer shipping information and clicks the Next
27 button 515. The System accesses 516 and retrieves 517 from the System database rating
28 information, including the Seller's preferences. The System uses the rating information and

1 prepares and displays for the Buyer a multi-carrier, multi-service shipping cost comparison
2 Graphic Array 518. The Buyer selects a Carrier/Service entry from the Graphic Array to ship
3 the package 519. The System verifies the information and requests payment information from
4 the Buyer in accordance with the Seller's preferences 520. The Buyer selects a payment
5 method, enters payment information and Sends the information to the System 521. The
6 System stores all Buyer information and associates that information with the package, and
7 updates the package status to "buyer has replied" 522. The System sends an e-mail to the
8 Seller notifying the Seller that the Buyer has replied 523. The System in some embodiments
9 sends an e-mail to the Buyer notifying the Buyer that the System has informed the Seller that
10 the Buyer has replied 524.

11 [0393] The Seller requests a Shipping Log of "Today's Packages" 525. The System
12 accesses the System database 526 to retrieve 527 a Shipping Log of the Seller's packages that
13 need to be processed. The System displays the Shipping Log to the Seller 528. The Seller
14 locates the package to which the Buyer responded and clicks the Ship button 529. The
15 System displays the Shipping screen to the Seller 530.

16 [0394] FIGS. 65A and 65B represent a database schema diagram that depicts an exemplary
17 embodiment of tables in which data is stored by the System regarding a particular package
18 and a particular Seller's Account, and from which information is retrieved in order to facilitate
19 the shipment of a package. The database schema depicted in FIGS. 65A and 65B provides an
20 Account User table 251, a Users table 252, an Account User Configuration table 253, a
21 Carrier Account table 254, an Account table 255, an Account and Carrier Account table 256,
22 an Address table 257, a Site Type table 258, an Account and Site Type table 259, an Account
23 and Site table 260, and a Site table 270, all of which were previously described herein above
24 with respect to FIGS. 33A and 33B. The database schema with respect to package
25 information further provides the Package Table 261. The Package Table 261 contains for
26 each package, among other things, a Package OID (a pointer) 261-1, the actual weight 261-2,
27 length 261-3, width 261-4, height 261-5, System package tracking number 261-6, site type ID
28 261-7, Site OID (a pointer) 261-8, Account number 261-9, User ID 261-10, From contact
29 name 261-11, From address 1 261-12, To contact name 261-13, To address 1 261-14, Bill

1 contact name 261-15, and the Bill address 1 261-16.

2

3 F. TRACKING

4 [0395] The tracking features described below apply similarly to both an exemplary
5 simplified Internet embodiment and to an exemplary eCommerce embodiment of the
6 invention.

7

8 1) USER REQUESTED TRACKING

9 [0396] In order to track a particular package using the System, a Shipper identifies a
10 tracking number for that package to the System and requests that the System report the status
11 of the package. Two types of tracking numbers are used to track packages: 1) Carrier tracking
12 numbers and 2) System tracking number.

13 [0397] Each Carrier assigns each package a tracking number that uniquely identifies each
14 package and which is used to trace packages as the package moves through the particular
15 Carrier's system to the package's destination. The Shipper or the package recipient uses the
16 tracking number for a particular package to track, locate, and verify delivery of the particular
17 package.

18 [0398] A System tracking number is a unique number generated internally by the System to
19 identify a particular package shipped using the System. The Shipper inputs the Shipper's
20 Parcel Specifications for the Subject Parcel. Using each Shipper's Parcel Specifications, the
21 System is programmed to access databases containing information about each supported
22 Carrier. Each supported Carrier has a unique rating schedule, delivery and pickup rules and
23 schedules, and certification requirements (the "Carrier Rules"). The System is further
24 programmed to apply each supported Carrier's Rules to each Shipper's Parcel Specifications
25 for the corresponding Subject Parcel. The System provides an online display of a
26 Dynamically Dimensioned Multi-Carrier, Multi-Service Graphic Array as depicted, e.g., in
27 FIGS. 36a and 46 described above.

1 [0399] The Shipper in this case uses a user input device to pick the preferred Carrier, by for
2 instance placing the cursor of the Shipper's PC on the displayed Carrier cell entry, e.g. 1065a,
3 in the Graphic Display as depicted in FIG. 36A and clicking the Shipper's user input device
4 (the "Selected Carrier").

5 [0400] As a result of the Shipper selecting a Carrier cell entry in the Graphic Display to ship
6 a package, the System assigns the package a System package tracking number and adds a
7 record containing all of the pertinent information about the package to the System database
8 22. Following are exemplary Shipping tracking numbers: MAGGY841VRY50;
9 MAGGY84B496RF; MAGGY84X0FJ45. In one embodiment, the System Tracking
10 Number is based on a Base-33 number system. The characters available are: Zero (0) through
11 nine (9) and A through Z excluding "I" (i), "L" (l), and "O" (o). Each letter represents a value,
12 as depicted in the table below:

13 A = 10 F = 15 M = 20 S = 25 X = 30

14 B = 11 G = 16 N = 21 T = 26 Y = 31

15 C = 12 H = 17 P = 22 U = 27 Z = 32

16 D = 13 J = 18 Q = 23 V = 28

17 E = 14 K = 19 R = 24 W = 29

18 Each System Tracking Number is 13 alphanumeric characters. Position 1 is the letter 'M'.
19 Positions 2 - 7 are a System Account number. Positions 8 - 12 are a five-digit ID. Position 13
20 is a Check Digit.

21 [0401] To calculate the Check Digit, the System performs the following steps: 1)
22 Consecutively multiply the numeric value of each of positions 2-7; 2) Consecutively multiply
23 the numeric value of each of positions 8 - 12; 3) Add both results; 4) Divide by 31; 5) Convert
24 the remainder value to a Base-33 number. The converted value is the Check Digit.

25 [0402] Referring to FIG. 5 once again, when a Shipper/User ships a package using the
26 System, one or more of the System's Servers, e.g., 21a-21n create a new System tracking
27 number. When a new System tracking number is created, one of the System's Database

1 Servers, e.g., 20a-20n, adds a new package record with the newly created System tracking
2 number to a Package Table 28.

3 [0403] The Package Table 28 resides in the System database 22 and contains package
4 records for System processed packages. An exemplary embodiment of the Package Table
5 contains the following information: 1) Package Tracking State ID; 2) Package Shipping State
6 ID; 3) Actual Delivery Time; 4) Delivered To information; 5) Shipping Date; 6) Carrier
7 Tracking Number; 7) System Tracking Number; 8) Carrier ID; 9) Actual Package Weight; 10)
8 Service Description; and 11) Package OID. The content of these fields are described further
9 below.

10 [0404] The Package Tracking State ID specifies the tracking state of the package. In an
11 exemplary embodiment of the invention, there are four different tracking states: 1) Null (New
12 Packages or Shipped Packages); 2) Manifested (at the end of each day, package information is
13 moved to the Package History Table for tracking purposes); 3) In Transit (The Carrier has
14 picked up packages); 4) Delivered (Packages have been delivered to the shipping destination).

15 [0405] The Package Shipping State ID specifies the shipping state of a package. In an
16 exemplary embodiment of the invention, there are two different shipping states: 1) Shipped
17 (New Packages or Shipped Packages); 2) Manifested (at the end of each day, package
18 information is moved to the Package History Table for tracking purposes).

19 [0406] The Actual Delivery Time specifies the Date/Time that the package was actually
20 delivered. The Delivered To information identifies the person or place to which the package
21 was delivered (e.g., left with receptionist, receptionist front desk, or guard). The Ship Date
22 specifies the date on which the Carrier picked up the package. The Carrier Tracking Number
23 identifies the Carrier-specific package tracking number. The System Tracking Number
24 specifies the unique Package tracking number internally generated by the System (each
25 System tracking number corresponds to exactly one Carrier-specific tracking number). The
26 Carrier ID specifies an identification code for the particular Carrier. The Actual Package
27 Weight specifies the actual weight of the package as opposed to the billed weight. The
28 Service Description describes the type of services used to ship the package e.g., Overnight, 3

1 Day Ground, Second Day Air, etc. The Package OID contains a Globally Unique Identifier
2 (“GUID”) for each package.

3 [0407] When the System creates a new package record, the record remains in the Package
4 Table 28 during an initial period of time, for example, the first day during which the record is
5 created, so that the Shipper/User can modify information about the package or void the
6 package record as appropriate. In an exemplary embodiment of invention, the System
7 performs certain processing on a periodic basis, such as at the end of each business day. This
8 type of processing is referred to herein as “End Of Day” processing. In an exemplary
9 embodiment of the invention, during “End of Day” processing, the System removes all new
10 package records from the Package Table 28 and moves the records to a Package History Table
11 29 which also resides on the System Database 22. In an exemplary embodiment, Package
12 History Table 29 records contain the same data fields as described above regarding Package
13 Table 28 records.

14 [0408] FIG. 68 is a graphic representation of a Shipper online user input screen that is
15 displayed on the Shipper’s display screen 10. If a Shipper/User wants to track a particular
16 package, the Shipper/User enters the tracking number that identifies the particular parcel
17 package of interest in the "Enter tracking number" field 2035. It should be understood by
18 those with ordinary skill in the art that the User may be someone other than the Shipper. For
19 instance, the User may be a Recipient who wishes to track a package being sent to the user.
20 Once the User has entered a tracking number, the User submits a request to track the particular
21 package identified by clicking on the Submit button 2036.

22 [0409] FIG. 69 is a logic flow diagram that depicts the high level logic for tracking the
23 status of a particular package. The User enters 2018a and 2018b a tracking number 19 in the
24 tracking number field 2035 (as was shown in FIG. 68). The System first validates 2050 the
25 tracking number 19. The System performs the validation process by attempting to access the
26 record on the System database 22 that is associated with the tracking number 19. To do this,
27 the System requests that a System database server, e.g., 20a (as depicted in FIG. 5) locate and
28 retrieve the package record that is associated with the tracking number 19. The System

1 database server, e.g., 20a as depicted in, e.g., FIG. 5, uses the entered tracking number 19 to
2 search the System database 22 to locate and retrieve the specified package record. In one
3 embodiment, the System database server, e.g., 20a as depicted in, e.g., FIG. 5, is programmed
4 to perform database accesses using Sequel 7.0.

5 [0410] Through the validation process, the System determines whether the tracking number
6 19 is a System tracking number or a Carrier tracking number. Below are examples of Carrier
7 tracking numbers.

8 UPS - 1z8595610344113190

9 Airborne - 3918984344

10 FedEx - 811152682326

11 USPS - ej585489546us

12 Yellow Freight - 2100003475

13 If a user enters a Carrier tracking number as the tracking number 19, then depending upon the
14 status of the package, or the number of times that the package was tracked, there may be no
15 information in the System database 22 for the Carrier tracking number. In such a case, the
16 System then uses algorithms provided by each Carrier to determine the Carrier identification.

17 [0411] If the System determines that there is information about the package on the System
18 database 22, then the System analyzes the Package Shipping State. If the Package Shipping
19 State of the retrieved record is “Manifested” or “In Transit” and the Package Tracking State is
20 not “Delivered”, then the System prepares to track the package using the appropriate Carrier
21 system. If the Package Shipping State of the retrieved record is “Delivered”, or other final
22 status, then the System reports the status of the package to the user.

23 [0412] If the tracking number 19 is a valid System tracking number, then the System
24 extracts the Carrier’s tracking number and Carrier’s ID from the package record retrieved
25 from the System database 22 before issuing a request 2054. Otherwise, if the tracking number
26 19 is a Carrier tracking number, then the System extracts the Carrier’s ID from the package
27 record before issuing a request 2052 to the Carrier’s Internet system. The System uses the

- 1 Carrier's ID to retrieve from the System database 22 the Internet URL for the Carrier's
- 2 Internet web site. The URL information is configurable.
- 3 [0413] Returning for a moment to FIG. 5, using the Carrier's Internet URL, the System then
- 4 makes an HTTP connection to the Carrier's web server, e.g., 23-2, 24-2, 25-2, 26-2, or 27-2,
- 5 using the URL information for the particular Carrier's web server. Depending upon the
- 6 Carrier, the System's 1 request and report interface with the Carrier's web server is
- 7 programmed in HyperText Markup Language ("HTML") (e.g., 24-1, 25-1, 27-1), Extensible
- 8 Markup Language ("XML") (e.g., 26-1), or both HTML and XML (e.g., 23-1). FIG. 66
- 9 depicts an exemplary XML formatted request for submitting a tracking request to a Carrier.
- 10 FIG. 67 depicts an exemplary successful tracking response, also in XML format, returned by
- 11 the Carrier.
- 12 [0414] Then, as depicted in FIG. 69, the System transmits the Carrier's tracking number
- 13 over the HTTP connection (2052 or 2054). The System instructs the Carrier's web server as
- 14 to what information is requested based on the connection made using the URL.
- 15 [0415] If the Carrier's web server successfully responds 2055 to the System's 1 tracking
- 16 request, the System disconnects from the Carrier's web server and parses the response data.
- 17 Some Carriers' response data contains unnecessary text information. The System strips out
- 18 all of the unnecessary text in order to parse the relevant information.
- 19 [0416] If the System database 22 does not have any previous record of the package, such as
- 20 would be the case if the package had not been shipped using the System shipping application,
- 21 then the System does not store any data about the package in the Package Table or the
- 22 Package History Table.
- 23 [0417] Otherwise, the System then updates the System database 22 and reports the
- 24 information to the Shipper/User 2056. If the package is reported as delivered, the System
- 25 populates the Package History Table 29 in the System database. As was previously
- 26 mentioned, in an exemplary embodiment, Package History Table 29 records contain the same
- 27 data fields as described above regarding Package Table 28 records.
- 28 [0418] If on the other hand, the Carrier's Internet web server returns an unsuccessful report

1 from test 2050, the System reports the failure 2051 to the User. FIG. 70 is a graphic
2 representation of an exemplary unsuccessful tracking report to the User. The Tracking Failure
3 Report Screen as depicted in FIG. 70 informs the User that the System was unable to track the
4 package 2060 and displays 2061 the package tracking number 19 that the User previously
5 entered. The Tracking Failure Report Screen asks the User to verify the accuracy of the
6 tracking number and to specify a Carrier by name 2062. The Tracking Failure Report Screen
7 provides a pull down menu button 2063, that when clicked, displays a list 2064 of the
8 supported Carriers. The user enters a new tracking number 19 in the tracking number field
9 2035 and specifies the Carrier by highlighting one of the Carriers displayed in the list 2064.
10 The user submits the request by clicking on the Submit button 2036 (covered by the pull down
11 selection list 2064 in FIG. 70).

12 [0419] If the Carrier's system successfully returns tracking information, then the System
13 displays the package's current status. As depicted in FIG. 71, if the package has a "Delivered"
14 status, the System reports the Status 2071; status as of Last Scan including date time and
15 location 2072; Delivered To location 2073; Delivery Date 2074; Delivery Time 2075;
16 Delivery Location 2076; Signed by 2077; Carrier Name 2078; Service 2079 and Tracking
17 Number 2080.

18 [0420] Status 2071 reports the Delivery Status, also referred to as the Track, or Tracking,
19 State. Last Scan 2072 reports Last scan information for the particular package. When a
20 package is moved from one location to another, the label of the package is scanned according
21 to each Carrier's processing requirements. Also, many Carriers scan package labels when
22 packages are received by the recipients. Delivered To 2073 reports the person or place to
23 which the package was delivered (e.g., left with receptionist, receptionist front desk, or
24 guard). Delivery Date 2074 reports the date on which the package was delivered. Delivery
25 Location 2076 reports, for most carriers, the city, zip code, and state information for the
26 location to which the package was delivered. However, for some carriers, such as UPS, the
27 delivery location reports where the package was dropped off (e.g., front porch, front door).
28 Signed By 2077 reports the name of the person who signed the package after receiving it.
29 Carrier 2078 reports the name of the Carrier that delivered the package. Service 2079 reports

1 the type of shipping service (i.e., Ground). Tracking Number 2080 reports the System
2 tracking number or carrier tracking number entered by the User.

3 [0421] The User is invited to enter another tracking number 19 in the tracking number field
4 2035 and click the Submit button 2036 to submit the next tracking request.

5 [0422] As depicted in FIG. 72, if the package has not yet been delivered, the System reports
6 the information available, e.g., the Status 2071, Last Scan 2072, Carrier 2078 and Tracking
7 number 2080. In such a case, the System asks the User if the User want to be notified when
8 the identified package is delivered 2090. The System provides the User with input fields to
9 register to receive, and have sent, e-mail notification after the package is delivered. A user
10 can enter up to three names, 2091, 2093 and 2095, and up to three e-mail addresses, 2092,
11 2094, and 2096, to receive the delivery confirmation. The User submits the e-mail notification
12 (with message 2097) by clicking on the Submit button 2036-1.

13 [0423] If the User completes the e-mail notification input fields with at least one e-mail
14 name and address, e.g., 2091 and 2092, the System creates an entry in a Track Response Table
15 30 which is a table contained in the System Database 22 as depicted in FIG. 5. The Track
16 Response Table entry contains the tracking number 19 earlier specified by the User and
17 displayed 2080 in the Tracking Report Screen depicted in FIG. 72. The System uses the
18 Track Response Table 30. The System performs Automatic Tracking for all of the package
19 tracking numbers contained in the Track Response Table 30 at the time that the Automatic
20 Tracking procedure is executed. Automatic Tracking is described in more detail below.

21 [0424] The User can then enter another tracking number 19 in the tracking number field
22 2035 and submit the new request by clicking on the Submit button 2036-2. When the Carrier
23 delivers the package, the System detects the delivery through one of several ways, as will be
24 further explained below, and then sends e-mail with a link to the web page with the most up to
25 date package status.

26 [0425] In an alternative embodiment, if the tracking number 19 is a Carrier tracking
27 number, the Server will validate the Carrier tracking number is a valid tracking number. If the
28 Carrier tracking number is not a valid number, the Server will return an invalid tracking

1 number error. If the Carrier tracking number is a valid number, the Server will not attempt to
2 match the number to a manifested package; the Server will track the package using the
3 particular Carrier's Internet tracking routine; and will return the tracking response to the Web
4 Client of the requesting Shipper/User.

5 [0426] In an alternative embodiment, if the tracking number 19 is a System tracking
6 number, then the System validates the System tracking number to ensure that it is a valid
7 System tracking number. If the System tracking number is not a valid tracking number, the
8 Server will return an invalid tracking number error. If the System tracking number is a valid
9 tracking number the Server queries the System database 22 to find the Carrier tracking
10 number which corresponds to the System tracking number. If no package record is found for
11 the System tracking number, then the Server will return an error to the Web Client of the
12 requesting Shipper. The error message will indicate that no package record was found; it will
13 request the user to verify that the tracking number was from a package which had been
14 dropped off notify the user that a package be tracked on the same day it shipped. If the
15 package record is found and the actual ship date is the same as the current date, the Server will
16 return an error to the Web Client of the requesting Shipper indicating that the user/Shipper
17 cannot track the package on the same day it is shipped.

18 [0427] In this alternative embodiment, once the Server has identified the Carrier tracking
19 number, the Server will track the package using the Carrier's Internet tracking routine. If the
20 tracking response from the Carrier's Internet tracking routing indicates an error, the Server
21 will make another attempt to track the package through the Carrier's Internet tracking routine.
22 If the second tracking request results in an error, the Server will notify the Web Client of the
23 requesting Shipper that the Carrier is unable to track the package, and will log a tracking
24 request error containing the Error Log number, the System tracking number, the Carrier
25 tracking number, the time and date the tracking request occurred, the error response reported
26 by the Carrier, and the Account Name of the user/Shipper making the tracking request, if that
27 information is available.

28 [0428] If, on the other hand, the Carrier returns a valid tracking response, the Server will

1 update the package status in the Server Database with the tracking response and will return the
2 detailed package information to the Web Client of the requesting user/Shipper from the
3 System Database as described below.

4 [0429] If the user supplied a Carrier tracking number, the Web Client will display the basic
5 tracking information provided by the particular Carrier's Internet tracking function. In one
6 embodiment of the invention, when the user provides a Carrier tracking number to track a
7 package, the user/Shipper's Web Client requires the user/Shipper to identify the Carrier.

8 [0430] If the user/Shipper provides a System tracking number, then if the user/Shipper is
9 logged on to the account, or otherwise enters valid logon information, that information must
10 correspond to the Account which shipped the package. In that case, the user/Shipper's Web
11 Client will display the following information: System tracking number; recipient address;
12 drop off location; Carrier and service; Carrier tracking number if available; actual ship date if
13 available; delivery address if available; delivery location if available; delivery date if
14 available; delivery time if available; signed for by information if available; package rate;
15 package weight; package dimensions; packaging; customer reference information; all scan
16 activity.

17 [0431] If on the other hand, the user/Shipper is not logged on to the account, fails to enter
18 valid logon information, or is logged on to an Account which does not correspond to the
19 Account which shipped the package, the user/Shipper's Web Client will display the following
20 information: System tracking number; recipient contact name; recipient company name;
21 Carrier and service; Carrier tracking number if available; actual ship date if available; delivery
22 address if available; delivery location if available; delivery date if available; delivery time if
23 available; signed for by information if available; package weight; customer reference
24 information; all scan activity.

25 2) AUTOMATIC TRACKING

26 [0432] Automatic Tracking of packages with Priority Delivery Notification is performed
27 when the package meets the following criteria: the package is a manifested package; the
28 package was shipped using Priority Delivery Notification; The actual ship date of the

1 package is the earlier than the current date; the package does not have the status of Delivered
2 or Lost.

3 [0433] Automatic Tracking of a particular package can be requested by the User, as
4 depicted in FIG. 72 and as was described above

5 [0434] If the package fulfills all of the above-described automatic tracking criteria, the
6 System places a record in the Track Response Table 30 and thereafter tracks the package on
7 some regular periodic time interval, for example, every four hours beginning at a staggered
8 start time. The start time is determined randomly and is staggered to occur at regular intervals
9 every four hours.

10 [0435] The System tracks the package using the specified Carrier's Internet tracking routine
11 as was previously described above. If the Carrier's Internet tracking routine returns a tracking
12 response that the tracking request is an error, the Server will track the package at the next
13 staggered tracking time. If the second tracking request response is also an error, the Server
14 will track the package at the next scheduled four hour interval. If the third tracking request
15 fails, the Server will log a tracking request error containing the following information: error
16 log number; System tracking number; Carrier tracking number; time and date the tracking
17 request occurred; and the error response from the Carrier. In the event that the third tracking
18 request fails, the Server will issue an Automatic Tracking Alert, for instance, to System
19 Support, containing the error log number.

20 [0436] If the tracking request results in a successful tracking response, the Server will
21 update the package status in the Package History Table 29 in the System Database 22 with the
22 tracking response information. If the package status returned is Delivered, the Server will
23 send delivery notification via e-mail to the notification address(e), e.g., 2091 - 2096 as
24 depicted in FIG. 72, as previously supplied by the Shipper/User. For a Delivered package, the
25 Server will update the Package History Table 29 in the System Database 22 to indicate that
26 the package has been delivered, that a delivery notification e-mail has been sent, and the date
27 and time that the e-mail was sent.

28 [0437] If the manifest package was shipped without Priority Delivery Notification, then on

1 any day after the actual ship date, as long as the status of the package is not Delivered or Lost,
2 the System will track the package every day at a non-peak period. If the tracking response is
3 an error, the Server will not attempt a second tracking request. If the tracking response is
4 successful, the System will update the package status in the System Database 22 with the
5 tracking response information.

6 **[0438]** The System will verify that all packages with a status of Delivered were delivered
7 within the guaranteed delivery time. For each Delivered package for which delivery was not
8 made with the guaranteed delivered time, the Server will generate a Delivery Exception
9 containing the following information: Carrier account number for the Drop Off Location;
10 Carrier tracking number; date of shipment; complete destination address information; delivery
11 exception ID number.

12 **[0439]** In one embodiment of the invention, there are four types of scripts, or procedures,
13 that run regularly to update the Package History Table 29 and the Track Response Table 30 in
14 the System database 22: 1) Track All Scripts, 2) Track Inbound Script, 3) Inbound
15 Confirmation Mail Script and 4) Delivery Confirmation Script. Each is described further
16 below.

17 **[0440]** Track All Scripts are run on a regular basis. There is a Track All script for each
18 Carrier (e.g., FedEx, UPS, Airborne, and Yellow Freight). Each Track All script executes a
19 set of instructions that enumerate the package records in the Package History Table 29 to get
20 updated information from a specific Carrier's database. If a System tracking number has a
21 delivered tracking state, then the next time a user tries to get tracking information for this
22 particular tracking number, the System will not need to connect to the Carrier's web server to
23 get the package status information.

24 **[0441]** Track Inbound Script is run on a regular basis. Track Inbound Script searches the
25 Track Response Table 30 and enumerates all entries in the table to get updated information
26 from multiple Carriers' databases. If a tracking number has a delivered tracking state, then
27 Users are notified via e-mail that their packages have been delivered. Also, if the tracking
28 number is a System tracking number then the Package History Table 29 gets updated with this

1 delivered tracking state information for optimization purposes. By updating the Package
2 History Table 29, the System does not need to re-connect to carriers' web servers to get
3 information about a package that has been already delivered.

4 [0442] Inbound Confirmation Mail Script is run on a regular basis. It searches the Track
5 Response Table 30 for packages that have a delivered track state. When the script finds
6 delivered packages for Users who requested to receive e-mail notifications, it sends e-mail
7 notifications to them with delivery information.

8 [0443] Delivery Confirmation Script is run on a regular basis. It searches the Package
9 History Table 29 and enumerates all entries in the table for which the User has requested
10 delivery notification when the subject package has been delivered to destination. When the
11 script finds delivered packages in the Package History Table 29 for Users who requested to
12 receive e-mail notifications, it sends e-mail notifications to them with delivery information.

13

14 3.) COUNTER MANIFEST SYSTEM (CMS) TRACKING

15 [0444] As an alternative to using an Internet embodiment of the invention, a user can track
16 packages by using the counter Manifest System CMS feature of the invention. In such an
17 embodiment, CMS is a standalone-dedicated system that uses a connection to one of the
18 System's servers (the "CMS Server") to track packages. CMS can be connected to one of the
19 System servers in many different ways, including among others, DSL dial-up, ISDN dial-up,
20 Modems, T1 line, Hughes VSAT link or other communications systems.

21 [0445] In the CMS environment, a company maintains a connection for the CMS to the
22 CMS Server to track packages for customers. The CMS User track packages for the CMS
23 User's customers by entering a tracking number in the CMS tracking page. CMS tracking
24 allows a customer to register for a delivery confirmation to receive e-mail notifications when
25 packages are delivered. Also, customers can register using the System's Internet embodiment
26 to receive inbound delivery notifications for the packages that are shipped using the CMS.

27 [0446] FIG. 73 is a graphic representation of an exemplary CMS online user input screen.
28 The User inputs a tracking number 19 in the input tracking number field 2100 and submits a

1 request to the System to track the package associated with the input tracking number 19 by
2 clicking on the “Track” button 2102 or the “Find Package” button 2101.

3 [0447] FIG. 74 is a graphic representation of an exemplary CMS display screen that reports
4 a successful tracking result 2103. After reading the tracking report, the User can request that
5 another package be tracked by clicking the ‘Track Another’ button 2104.

6 [0448] FIG. 75 is a graphic representation of an exemplary CMS error tracking report
7 display screen. The tracking number 19 is displayed with an error message 2105. The user
8 can request that another package be tracked by clicking the “Track Another” button 2104.

9

10 4.) MANIFEST AND INBOUND TRACKING

11 [0449] A User can register with the System to establish a shipping account. Once a User has
12 established an account, the System will record in the System database 22 information for
13 every package shipped under the User’s account. The information contained in the System
14 database 22 under the User’s account is referred to as the User’s Shipping Log.

15 [0450] The System provides the User with online capability to request information about the
16 User’s Shipping Log. FIG. 76 is a graphic representation of an exemplary embodiment of a
17 “My Tracking” Screen. On the viewer’s left side of the My Tracking Screen display, a “My
18 Tracking submenu 2110 is provided to allow the User to select options. By clicking on and
19 highlighting one of the My Tracking submenu 2110 options, the User can select to view the
20 User’s Account’s Shipping Log 2111, to View Inbound Packages 2112, to Add Inbound
21 Packages 2113, and to indicate Tracking Preferences 2114. The User can also input a tracking
22 number 19 into the Quick Track input field 2115 and request that the System track the
23 identified package by clicking the “go” button 2116.

24 [0451] FIG. 77 is a graphic representation of an exemplary embodiment of a Shipping Log
25 Screen. A logged on registered User enters this display screen by clicking on the My
26 Tracking submenu 2110 User’s Account’s Shipping Log option 2111. If the User is both
27 logged on and registered, then in response to the User clicking on the My Tracking submenu
28 2110, User’s Account’s Shipping Log option 2111, the System presents a Shipping Log

1 Screen with certain selection criteria. In the embodiment depicted in FIG. 77, the System
2 initializes selection criteria fields with certain default values. For instance, the Shipping Log
3 will search the system database 22 for the name of the individual to whom the particular
4 account belongs and displays the name of the person 2109. Further, the Shipping Log
5 application will search the System database 22 for all packages shipped under the User's
6 account that conform to the criteria specified in the input fields of the FIG. 77 screen.

7 **[0452]** The Shipping Log Screen provides for User selection of the Type of package, e.g.,
8 "All Packages" from the Display option 2118 and Display option pull-down menu button
9 2117; "For the Past" time period 2119 with a pull-down menu button 2120, e.g., for the past
10 "Month" during which packages were shipped; and "Sort By" 2121-2122 which allows the
11 User to select the order of the Shipping Log report entries.

12 **[0453]** In response to the Shipping Log request, the System creates a list and displays an
13 online Shipping Log record for the packages shipped under the User's account and which fit
14 the selection criteria. For each such package, the System displays: the Status of the package
15 2125 and the tracking number 2080, the name of the shipper 2126, the Carrier Service 2127,
16 the name of the Carrier 2128, the Ship Date 2129, and the Delivery Date and time 2129-2130.
17 If the User wants more information for a particular package in the Shipping Log, the User
18 highlights the appropriate record in the list and clicks the "Details" button 2124. An "Update
19 View" button 2123 is also provided.

20 **[0454]** FIG. 78 is a graphic representation of an exemplary embodiment of a Detailed
21 Shipping Log Entry Screen which is displayed if the User highlights the appropriate record in
22 the Shipping Log list and clicks the "Details" button 2124. The System displays the Shipping
23 Log date and time 2140, the System tracking number 2141, the estimated weight of the
24 package 2142, the billed weight of the package 2143, the Packaging type 2144, the Carrier
25 and Service 2145, a description of the goods shipped 2146, the shipping status 2071, the
26 Carrier tracking number 2080, the Shipped Date 2147, the Expected data of arrival 2148, the
27 Last Scan information 2072, the Recipient's name and address 2149, the Return name and
28 address 2150, the Ship from location 2153, the base shipping service charge 2151, and the

1 total shipping charge 2152.

2 [0455] FIG. 79 is a graphic representation of an exemplary embodiment of a detailed
3 “Quick Track” result screen which displays the same type of information described above for
4 FIG. 78. The way that a User obtains this display is to enter a tracking number 19 into the
5 Quick Track input field 2115, and by then clicking on the “go” button 2116.

6 [0456] A registered logged on User can view inbound packages if the User first identifies to
7 the System package tracking numbers for each of the packages the status of which the User is
8 interested in monitoring. FIG. 80 is a graphic display of an exemplary embodiment of an
9 “Add Inbound Packages” Screen. The User requests this screen by clicking on the “Add
10 Inbound Package” option 2113 of the “My Tracking” submenu 2110. The User inputs
11 identification information, such as the tracking number 19 in the input tracking number field
12 2035, the Carrier 2128, and the Order/Item 2161. The User can also specify that the System is
13 to provide e-mail notification 2162 with an e-mail message 2163. By clicking on the “E-mail
14 Others” button 2164, the User can request an “E-mail Others” screen providing input similar
15 to that, items 2091-2097, and 2036-1, described above for the tracking screen depicted in FIG.
16 72. By clicking on the “Add” button 2165, the User requests that the record identified in the
17 User’s input be added to a list for that User of Inbound Packages to be monitored. A “Cancel”
18 button 2166 is also provided.

19 [0457] Once the User has input the identification information for the packages the status of
20 which the User wants to monitor, and added all such records to the User’s Inbound Tracking
21 List, the User can then view the status of those identified Inbound packages. To do so, the
22 user clicks on the “View Inbound Packages” option 2112 of the “My Tracking” submenu
23 2110. FIG. 81 is a graphic representation of an exemplary embodiment of a “View Inbound
24 Packages” Summary Screen. Similar to the Shipping Log Screen as discussed above in
25 relation to FIG. 77, the View Inbound Packages Summary Screen displays information about
26 packages identified by the User as Inbound Packages. As depicted on FIG. 81, the User can
27 specify reporting criteria such as Display limitations 2117-2118, and sorting requests 2121-
28 2122. The User can request details about a particular package by highlighting the reporting

1 line on the screen and clicking the “Details” button 2124. The User can delete a particular
2 package from Inbound Package Tracking by highlighting the reporting line on the screen and
3 clicking the “Delete” button 2170. An “Update View” button 2123 is also provided.

4 [0458] FIG. 82 is a graphic representation of a View Inbound Packages Detail Screen. The
5 type of information displayed on this screen is similar to the type of information described
6 with respect to the Shipping Log Detail Screen as depicted in FIG. 78 and discussed above.

7

8 ILLUSTRATIVE EMBODIMENTS

9 [0459] Although this invention has been described in certain specific embodiments, many
10 additional modifications and variations would be apparent to those skilled in the art. It is,
11 therefore, to be understood that this invention may be practiced otherwise than as specifically
12 described. Thus, the embodiments of the invention described herein should be considered in
13 all respects as illustrative and not restrictive, the scope of the invention to be determined by
14 the appended claims and their equivalents rather than the foregoing description.

15

16

17

18

19

20

1 WHAT IS CLAIMED IS:

2

3 1. A computer system, said computer system programmed to:
4 provide a single system available over a global communications network for shipping
5 management for each parcel from a plurality of parcels that each Shipper of a plurality of
6 Shippers ships using any one of a plurality of services offered by any one of a plurality of
7 carriers.

8

9 2. A method using a computer system, said method comprising:
10 providing a single system available over a global communications network for
11 shipping management for each parcel from a plurality of parcels that each Shipper of a
12 plurality of Shippers ships using any one of a plurality of services offered by any one of a
13 plurality of carriers.

14

15 3. A computer program product embodying computer program instructions for
16 execution by a computer system, said computer program product comprising:
17 a set of program instructions for providing a single system available over a global
18 communications network for shipping management for each parcel from a plurality of parcels
19 that each Shipper of a plurality of Shippers ships using any one of a plurality of services
20 offered by any one of a plurality of carriers.

21

22 4. A shipping management computer system, said shipping management
23 computer system programmed to:
24 limit an identification of a plurality of carriers for selection by a second user
25 according to a set of carriers from a plurality of carriers according to a set of specifications of
26 a first user.

27

28 5. A shipping management computer system, said shipping management
29 computer system programmed to:

1 customize a calculation and display of itemized charges and a total for payment by a
2 second user according to a set of itemized charge presentation preferences from a plurality of
3 itemized charge presentation options according to a set of itemized charge presentation
4 preferences specified by a first user.

5

6 6. A shipping management computer system, said shipping management
7 computer system programmed to:

8 collect as itemized charge presentation preferences of a first user a user input from the
9 first user of an identification of itemized charge presentation options; and
10 store in a database the itemized charge presentation preferences of the first user.

11

12 7. A shipping management computer system, said shipping management
13 computer system programmed to:

14 limit an identification of a plurality of payment methods for selection by a second user
15 according to a set of preferred payment methods from a plurality of payment methods
16 according to a set of specifications of a first user.

17

18 8. A shipping management computer system, said shipping management
19 computer system programmed to:

20 collect as preferred payment methods of a first user a first user input of the first user
21 of a selection of at least one payment method from a plurality of payment method; and
22 store in a database the preferred payment methods of the first user.

23

24 9. A computer system for performing a set of actions for a plurality of users,
25 wherein each user accesses the computer system over a global communications network
26 using a client computer device, said computer system programmed to:

27 create at a linkable address on a server computer an electronic commerce site from
28 which a second user can perform a particular activity, the particular activity characterized by
29 a set of options, in accordance with a particular first user's option preferences.

1

2 10. A computer system for performing a set of actions for a plurality of users,
3 wherein each user accesses the computer system over a global communications network
4 using a client computer device, said computer system programmed to:

5 create a hypertext link template containing variable data and global communications
6 address fields;

7 collect user input of data from a first user;

8 populate a plurality of variable data fields in the hypertext link template with the
9 collected user input data; and

10 populate at least one global communications address field with a universal address
11 location corresponding to an address at which program instructions for processing the data in
12 the variable data fields is located.

13

14 11. A computer system for performing a set of actions for a plurality of users,
15 wherein each user accesses the computer system over a global communications network
16 using a client computer device, said computer system programmed to:

17 collect from a first user service information about a service to be provided by the first
18 user;

19 collect from a second user requesting the service from the first user information about
20 delivery of the service; and

21 prepare information about the service according to the requesting information
22 provided by the second user and the service information provided by the first user.

23

24 12. A shipping management computer system, said shipping management
25 computer system programmed to:

26 collect from a first user having access to a first computer device a set of information
27 comprising: parcel specifications for shipping a particular parcel, shipping preferences, and
28 selling preferences; and

29 collect from a second user having access to a second computer device a set of

1 recipient information comprising: a destination zip code, a selection of a carrier and a
2 selection of a service offered by the selected carrier.

3

4 13. A shipping management computer system, said shipping management
5 computer system programmed to:

6 generate a unique tracking number for each parcel to be shipped using a multi-carrier,
7 shipping system.

8

9 14. A shipping management computer system, said shipping management
10 computer system programmed to:

11 identify a relationship between a generated unique tracking number and a
12 corresponding parcel; and

13 store each generated unique tracking number and the corresponding parcel
14 relationship in a database.

15

16 15. A shipping management computer system, said shipping management
17 computer system programmed to:

18 generate a unique tracking number for each parcel to be shipped using the system
19 wherein each parcel is characterized by a set of parcel specifications and each shipment of
20 each parcel is characterized by a set of shipment specifications.

21

22 16. A computer system for performing a set of actions for a plurality of users,
23 wherein each user accesses the computer system over a global communications network
24 using a client computer device, said computer system programmed to:

25 notify a first user that a second user has refused to complete purchase of an item after
26 a point in time that the second user has indicated to the first user that the second user wanted
27 to purchase the item, and after a point in time that the first user has indicated to the second
28 user that the item is available to the second user for purchase, but before the second user has
29 provided delivery and payment information to the first user.

1 17. A computer system for performing a set of actions for a plurality of users,
2 wherein each user accesses the computer system over a global communications network
3 using a client computer device, said computer system programmed to:

4 collect as refusal information an input by a particular second user of a refusal to
5 complete a purchase from a particular first user.

6

7 18. A shipping management computer system, said shipping management
8 computer system programmed to:

9 generate a shipping log entry to a shipping log of a first user in response to a shipping
10 selection by a second user of a service and carrier, wherein said shipping log entry contains a
11 unique identifier corresponding to a particular item to be shipped and further corresponding
12 to a database entry for the particular item further containing information corresponding to the
13 selected service and carrier.

14

15 19. A shipping management computer system, said shipping management
16 computer system programmed to:

17 recognize as a selection of a carrier and a service a selection by the second user of a
18 particular shipping rate from an online interactive comparison display, said shipping rate
19 corresponding to the selected carrier and the selected service shipping a particular item; and
20 generate an entry to a shipping log of a second user for shipping the particular item
21 using a the selected carrier and service.

22

23 20. A computer system for performing a set of actions for a plurality of users, said
24 computer system programmed to:

25 automatically notify a second user that a first user has taken an action with respect to
26 an item ordered by the second user.

27

28 21. A computer system for performing a set of actions for a plurality of users, said
29 computer system programmed to:

1 recognize as an action confirmation for a particular item ordered by a second user a
2 selection by a first user of a unique identifier corresponding to the particular ordered item,
3 said selection of the unique identifier from an online electronic list of ordered items, said list
4 corresponding to a next action status regarding the listed ordered items.

5

6 22. A shipping management computer system, said shipping management
7 computer system programmed to:

8 track a shipping status of each of a plurality of parcels, wherein each parcel is shipped
9 by one of a plurality of services offered by one of a plurality of carriers.

10

11 23. A shipping management computer system, said shipping management
12 computer system programmed to:

13 poll an appropriate carrier shipping status system from a plurality of carrier shipping
14 status systems in response to a user tracking request to obtain current tracking status
15 information for a particular package.

16

17 24. A shipping management computer system, said shipping management
18 computer system programmed to:

19 recognize as a tracking request a request by a user to track a particular parcel, said
20 request comprising a tracking number.

21

22 25. A shipping management computer system, said shipping management
23 computer system programmed to:

24 periodically generate signals to an appropriate carrier shipping status system from a
25 plurality of carrier shipping status systems at the electronic address for the carrier computer
26 system requesting shipping status for a particular parcel.

27

28

29 26. A computer system for managing shipping of a plurality of parcels by a

1 plurality of users using a plurality of carriers, said computer system comprising:
2 a plurality of server computer devices,
3 wherein each server computer device is programmed to perform a plurality of
4 activities in support of a particular function, wherein each server computer device is
5 programmed to support a different particular function, and wherein each particular function
6 contributes to managing shipping of the plurality of parcels.

7

8 27. A shipping management computer system, said shipping management
9 computer system programmed to:

10 apply, in response to a request by any particular user of a plurality of users, a set of
11 shipping location rules for each of a plurality of carriers to a default shipping location and a
12 set of parcel specifications input by the particular requesting user, wherein each user accesses
13 the computer system over a global communications network using a client computer device,
14 each user client computer device having an individual electronic connection to the global
15 communications network.

16

17 28. A shipping management computer system, said shipping management
18 computer system programmed to:

19 apply, in response to a request by any particular user of a plurality of users, a set of
20 parcel handling rules for each of a plurality of Carriers to a set of parcel specifications for a
21 particular package to be shipped input by the particular requesting user, wherein each user
22 accesses the computer system over a global communications network using a client computer
23 device, each user client computer device having an individual electronic connection to the
24 global communications network.

25

26 29. A shipping management computer system, said shipping management
27 computer system programmed to:

28 identify, in response to a request by any particular user of a plurality of users, each
29 carrier from a plurality of carriers that supports shipping a particular parcel according to a set

1 of parcel specifications for a particular package input by the particular requesting user,
2 wherein each user accesses the computer system over a global communications network
3 using a client computer device, each user client computer device having an individual
4 electronic connection to the global communications network.

5

6 30. A shipping management computer system, said shipping management
7 computer system programmed to:

8 collect as parcel specifications for a particular parcel to be shipped by a particular
9 user, user input from the particular user from a plurality of users, said parcel specifications
10 comprising at least one of: a package type, package dimensions, package weight, and a value
11 of the particular parcel, wherein each user accesses the computer system over a global
12 communications network using a client computer device, each user client computer having an
13 individual electronic connection to the global communications network; and

14 store in a database a record corresponding to the particular user, said record
15 comprising an identifier for the particular user and the parcel specifications for the particular
16 parcel.

17

18 31. A shipping management computer system, said shipping management
19 computer system programmed to:

20 instruct each remote user client computer device of a plurality of remote user client
21 computer devices over a global communications network to recognize a weight of a parcel as
22 measured by a digital scale configured with a remote user client computer device; and

23 instruct each remote user client computer device of the plurality of remote user client
24 computer devices to return a weight to the shipping management computer system.

25

26 32. The shipping management computer system of Claim 31, said shipping
27 management computer system further programmed to:

28 receive a weight communicated by each remote user client computer device over a
29 global communications network, wherein the remote user client computer device is

1 configured with a digital scale.

2

3 33. A shipping management computer system, said computer system programmed
4 to:

5 display to each of a plurality of users upon each user's request a preview of shipping
6 rates for the particular user to ship a particular package, wherein each user accesses the
7 computer system over a global communications network using a client computer device,
8 wherein each user having an individual electronic connection to the global communications
9 network.

10

11 34. A shipping management computer system, said computer system programmed
12 to:

13 calculate for each of a plurality of users upon each user's request a shipping rate for
14 each of a plurality of services offered by each of a plurality of carriers for shipping a
15 particular parcel, wherein each user accesses the computer system over a global
16 communications network using a client computer device, wherein each user client computer
17 device having an individual electronic connection to the global communications network.

18

19 35. A shipping management computer system, said computer system programmed
20 to:

21 determine for each of a plurality of users upon each user's request a delivery schedule
22 for each of a plurality of services offered by each of a plurality of carriers for shipping a
23 particular parcel, wherein each user accesses the computer system over a global
24 communications network using a client computer device, wherein each user client computer
25 device having an individual electronic connection to the global communications network.

26

27 36. A shipping management computer system, said computer system programmed
28 to:

29 display to each of a plurality of users, upon each user's request, as to each particular

1 parcel to be shipped by the particular user, an identification of each of a plurality of carriers
2 that provide a plurality of delivery notification service options, wherein each user accesses
3 the computer system over a global communications network using a client computer device,
4 and wherein each user client computer device has an individual electronic connection to the
5 global communications network.

6

7 37. A shipping management computer system, said computer system programmed
8 to:

9 calculate, upon each request by each of a plurality of users, as to each particular
10 parcel to be shipped by a particular user, a service charge by each carrier for each delivery
11 notification service option that the particular carrier supports for delivery of the particular
12 package to be shipped by the particular user, wherein each user accesses the computer system
13 over a global communications network using a client computer device, and wherein each user
14 client computer device has an individual electronic connection to the global communications
15 network.

16

17 38. A shipping management computer system, said computer system programmed
18 to:

19 identify to each of a plurality of users, upon each user's request, as to each particular
20 parcel to be shipped by the particular user, a service charge by each carrier for each delivery
21 notification service option that the particular carrier supports for delivery of the particular
22 package to be shipped by the particular user, wherein each user accesses the computer system
23 over a global communications network using a client computer device, and wherein each user
24 client computer device has an individual electronic connection to the global communications
25 network.

26

27 39. A shipping management computer system, said computer system programmed
28 to:

29 display to each of a plurality of users, upon each user's request, as to each particular

1 parcel to be shipped by the particular user, an identification of each of a plurality of carriers
2 that provide a plurality of delivery service options, wherein each user accesses the computer
3 system over a global communications network using a client computer device, and wherein
4 each user client computer device has an individual electronic connection to the global
5 communications network.

6

7 40. A shipping management computer system, said computer system programmed
8 to:

9 calculate, upon each request by each of a plurality of users, as to each particular
10 parcel to be shipped by a particular user, a service charge by each carrier for each service
11 option that the particular carrier supports for delivery of the particular package to be shipped
12 by the particular user, wherein each user accesses the computer system over a global
13 communications network using a client computer device, and wherein each user client
14 computer device has an individual electronic connection to the global communications
15 network.

16

17 41. A shipping management computer system, said computer system programmed
18 to:

19 identify to each of a plurality of users, upon each user's request, as to each particular
20 parcel to be shipped by the particular user, a service charge by each carrier for each service
21 option that the particular carrier supports for delivery of the particular package to be shipped
22 by the particular user, wherein each user accesses the computer system over a global
23 communications network using a client computer device, and wherein each user client
24 computer device has an individual electronic connection to the global communications
25 network.

26

27 42. A shipping management computer system, said computer system programmed
28 to:

29 display to each of a plurality of users, upon each user's request, as to each particular

1 parcel to be shipped by each user, an online interactive graphic comparison of a plurality of
2 shipping rates calculated for each of a plurality of services offered by each of a plurality of
3 carriers to ship a particular parcel, each shipping rate corresponding to a particular service
4 offered by a particular carrier for delivering the particular parcel to a particular delivery
5 destination at a particular parcel delivery time on a particular parcel delivery date, wherein
6 each user accesses the computer system over a global communications network using a client
7 computer device, and wherein each user has an individual electronic connection to the global
8 communications network.

9

10 43. An online interactive shipping management computer system, said computer
11 system programmed to:

12 regenerate a display of shipping information at any particular remote user client
13 computer device of a plurality of remote user client computer devices, based on modified
14 input by a particular user at a particular remote user client computer device, wherein the
15 computer system communicates with each remote user client computer device over a global
16 communications network.

17

18 44. An online interactive shipping management computer system, said computer
19 system programmed to:

20 execute a set of computer instructions for generating an interactive user interface
21 display of rating and schedule shipping information with a set of data input by a particular
22 user from a particular remote user client computer device connected to the computer system
23 over a global communications network; and

24 generate the interactive user interface shipping information display comprising the
25 data input by the particular user, a result of the executed set of computer instructions, at least
26 one data collection field initialized with a data item from the data input by the particular user,
27 and an instruction to execute the executable set of instructions in response to a user
28 modification of data in the data collection field.

29

1 45. The online interactive shipping management computer system of Claim 43,
2 said computer system further programmed to:

3 distribute with the interactive user interface shipping information display to the client
4 computer device an executable set of the executed computer instructions with the instruction
5 to execute the executable set of instructions in response to a user modification of the
6 initialized data in the data collection field.

7

8 46. A shipping management computer system, said shipping management
9 computer system programmed to:

10 apply, in response to a request by any particular user of a plurality of users, a set of
11 billing option rules for each of a plurality of carriers to a single billing option preference
12 input by the particular requesting user, wherein each user accesses the computer system over
13 a global communications network using a client computer device, each user client computer
14 device having an individual electronic connection to the global communications network.

15

16 47. A shipping management computer system, said shipping management
17 computer system programmed to:

18 identify, in response to a request by any particular user of a plurality of users, each
19 carrier from a plurality of carriers that supports a particular billing option preference input by
20 the particular requesting user for shipping a particular parcel, wherein each user accesses the
21 computer system over a global communications network using a client computer device, each
22 user client computer device having an individual electronic connection to the global
23 communications network.

24

25 48. A shipping management computer system, said shipping management
26 computer system programmed to:

27 collect as a billing option preference for each particular user of a plurality of users a
28 user input from the particular user of an identification of a billing option preference for
29 parcels to be shipped by the particular user, wherein each user accesses the computer system

1 over a global communications network using a client computer device, each user client
2 computer having an individual electronic connection to the global communications network;
3 and
4 store in a database a record corresponding to each particular user, said record
5 comprising an identifier for the particular user and the billing option preference for the
6 particular user.

7
8 49. The shipping management computer system of Claim 48, said shipping
9 management computer system further programmed to:

10 identify, in response to a request by any particular user of a plurality of users, each
11 carrier from a plurality of carriers that supports shipping a particular parcel wherein the
12 particular parcel is characterized by a set of parcel characteristics, wherein said set of parcel
13 characteristics translate into a particular ratable weight according to dimensional weight
14 calculation rules for each of the plurality of carriers, wherein each user accesses the computer
15 system over a global communications network using a client computer device, each user
16 client computer device having an individual electronic connection to the global
17 communications network.

18
19 50. A shipping management computer system, said computer system programmed
20 to:

21 determine for each of a plurality of users upon input by each user of a particular origin
22 postal code and a particular destination postal code an origin rating zone identifier corresponding
23 to the particular origin postal code for each of a plurality of carriers, and a destination rating zone
24 identifier corresponding to the particular destination postal code for each of the plurality of
25 carriers, wherein each user accesses the shipping management computer system over a global
26 communications network using a client computer device, and wherein each user client computer
27 device has an individual electronic connection to the global communications network.

28
29 51. A shipping management computer system, said computer system programmed

1 to:

2 determine from a set of delivery times for each of a plurality of services for each of a
3 plurality of carriers a potential delivery schedule for each of the plurality of services for each of
4 the plurality of carriers in response to a request by each of a plurality of users to ship a particular
5 parcel, wherein each user accesses the shipping management computer system over a global
6 communications network using a client computer device, and wherein each user client computer
7 device has an individual electronic connection to the global communications network.

8

9 52. A shipping management computer system, said computer system programmed
10 to:

11 recognize, in response to a particular user of a plurality of users using a particular
12 remote user client computer device to print a shipping label for shipping a particular parcel
13 using a particular carrier from a plurality of carriers, a set of graphic resolution characteristics
14 of a printer device configured with the particular remote user client computer device,
15 wherein each user accesses the computer system over a global communications network
16 using a remote user client computer device, each remote user client computer device having
17 an individual electronic connection to the global communications network.

18

19 53. The computer system of Claim 52, said computer system further programmed
20 to:

21 create a shipping label image bearing a dimensionally accurate symbology for display
22 on a display device configured with the particular remote user client computer device for
23 printing on the particular printer device.

24

25

26

27

28

29

30

1 APPARATUS, SYSTEMS AND METHODS FOR ONLINE, MULTI-CARRIER, MULTI-
2 SERVICE PARCEL SHIPPING MANAGEMENT

3

4 ABSTRACT OF THE INVENTION.

5 The present invention provides apparatus, systems and methods providing a single
6 system available over a global communications network for shipping management for each
7 parcel from a plurality of parcels that each Shipper of a plurality of Shippers ships using any
8 one of a plurality of services offered by any one of a plurality of carriers.

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29